

803 Transfer

SELF ADHESIVE TAPE

PRODUCT DESCRIPTION

Fiber reinforced, double sided, self-adhesive tape that combines extra strength with long-term durability. Strong floor-laying tape also for hard-wearing floor-covering (carpet, vinyl). Also for accurate mounting of skirting boards made of wood, vinyl and rubber. Suitable on underfloor heating systems.



PRODUCT FEATURES

The integrated fiber guarantees a high resistance to tearing and stability.
The pressure sensitive adhesive film of a modified polyacrylate pressure-sensitive adhesive results in an excellent adhesion

The adhesive tape bridges through the tick adhesive films' low roughness of the subfloor. No contamination arises through adhesive application. Skirting can be pre-work coated.

TECHNICAL DATA

Base	Polyester Fiber net with Polyacrylate adhesive made of silicon paper
Colour	Beige, transparent
Thickness	approx. 0,22 – 0,24 mm
Width	35 mm, 45 mm, 90 mm, as well as on request
Length	50 m
Peel resistance	≥ 25 N/25 mm, (DIN EN 1939)
Processing conditions	15 - 25 °C, 35 - 75 % relative air moisture (recommended 40 - 65 %)
Permitted shelf-life	within approx. 12 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage conditions	packaging to be tightly closed at a dry place (max. 55% air moisture), temperature: 20 - 30 °C, without direct sunlight
Code acc. to GHS	no
Environment/Work safety	Solvent-free adhesive

SUBFLOOR

The subfloor must be leveled, permanently dry, pressure-resistant crack and dust free.

Loose adhesions needs to be removed.

Smaller joints or cracks up to 0,5 mm can be bridged by the adhesion with 803 Eurostrip Transfer and can be leveled with the adhesive.

803

Eurostrip Transfer

Larger joints must be corrected, particularly in rigid skirting/profiles. An additional primer is not usually necessary, but it is recommended for very rough surfaces.

APPLICATION

Put the 803 Eurostrip Transfer to the backside of the skirting or profile boards and cut it in accordance to fit its size. At the roll up of prepared skirting/profiles, make sure that the wrapping tension of the skirting does not lead to overstretching, to the possibly lead to the shrinkage of the bar.

Remove masking tape and press the skirting or profile board to make it fit exactly.

NOTES

Consider technical instructions and the safety data sheets of goods manufactured and/ or delivered by third party.

Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer.

Do not use directly on highly plasticized subfloors (for example, vinyl wallpaper).

PACKING

- Bandwidth 35 mm / 4* 8 rolls/carton, 512/palette
- Bandwidth 45 mm / 4* 6 rolls/carton, 384/palette
- Bandwidth 90 mm / 4* 3 rolls/carton, 192/palette

SPECIAL NOTES

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties.

Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid! Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children. The manufacturer's terms and conditions are binding.

Last update 2017-01-16
Supersedes issue as of 29.6.2004

Version Nr.:02
73115_803-HW01