

Page 1/8

Revision: 28.11.2023

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 7 (replaces version 6)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: 705 Watertight Tile Adhesive
- · Article number: 705
- · **UFI**: *UJX1-E00M-J00U-1DM6*
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / preparation Tile adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271620

E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Portland cement clinker

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)

Printing date 28.11.2023 Version number 7 (replaces version 6) Revision: 28.11.2023

## Trade name: 705 Watertight Tile Adhesive

(Contd. of page 1)

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust. P280 Wear protective gloves.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P404 Store in a closed container.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of cement, fillers and additives.

Dangerous components:		
CAS: 65997-15-1	Portland cement clinker	>25-50%
EINECS: 266-043-4	♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 544-17-2	calcium diformate	>1-5%
EINECS: 208-863-7	♦ Eye Dam. 1, H318	
CAS: 9004-34-6	Cellulose	<1%
EINECS: 232-674-9	substance with a Community workplace exposure limit	

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- After inhalation:

In case of unconsciousness place patient stably in side/recovery position for transportation.

· After skin contact:

Immediately remove contaminated clothing, wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Rinse mouth with water and then drink plenty of water, consult physician immediately.
- · Information for doctor: Product reacts with moisture into alkaline mixture.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GE

Printing date 28.11.2023

Version number 7 (replaces version 6)

Trade name: 705 Watertight Tile Adhesive

(Contd. of page 2)

Revision: 28.11.2023

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Not applicable.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Product itself does not burn.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
- Avoid formation of dust. Avoid contact with eyes and skin.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Pick up mechanically, dry vacuum powder.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure sufficient ventilation and avoid formation of dust. Do not inhale dust. Avoid contact with eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed packaging.
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 65997-15-1 Portland cement clinker

WEL Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust \*\*respirable dust

#### 9004-34-6 Cellulose

WEL Short-term value: 20\* mg/m³
Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust \*\*respirable

- Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

Printing date 28.11.2023 Version number 7 (replaces ve

Version number 7 (replaces version 6) Revision: 28.11.2023

## Trade name: 705 Watertight Tile Adhesive

(Contd. of page 3)

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale dust.

· Respiratory protection:

Use suitable respiratory protective device (filter P2) in case of insufficient ventilation.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

· Material of gloves

Use chemical resistant gloves classified under EN374. Examples of preferred glove materials that form a barrier: butyl rubber or chloroprene rubber. If prolonged or repeated contact can occur, gloves with a protection class of 6 (breakthrough time greater than 480 minutes) are recommended according to EN 374. Ask your glove supplier to advise you on the right type and thickness.

- · Penetration time of glove material ≥ 480 Minutes
- For prolonged contact gloves made of the following materials are suitable: Chloroprene and butylrubber.
- Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- General Information

· Colour: Grev

· Odour: Characteristic
· Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined.
• Flash point: Not applicable.

pH (4000 g/l) at 20 °C >11

· Solubility

water: Slightly soluble.

· Density and/or relative density

• Density at 20 °C: 1.2 g/cm³ • Particle characteristics See item 3.

- · 9.2 Other information
- · Appearance:

· Form: Powder

Important information on protection of health and environment, and on safety.

• Auto-ignition temperature: Product is not self-igniting.

(Contd. on page 5)

Revision: 28.11.2023

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 7 (replaces version 6)

## Trade name: 705 Watertight Tile Adhesive

(Contd. of page 4) Explosive properties: Product does not present an explosion hazard. · Solvent content: · Organic solvents: 0.0 % · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

#### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

#### 544-17-2 calcium diformate

Oral LD50 2,650 mg/kg (rat)

- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation

Causes serious eve damage.

· Respiratory or skin sensitisation

Product can cause irritation on the longer term dermatitis. This impact is caused by alcality of the product in water and on mechanical damage of the skin.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 28.11.2023

Version number 7 (replaces version 6)

## Trade name: 705 Watertight Tile Adhesive

(Contd. of page 5)

Revision: 28.11.2023

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Warm water, if necessary together with cleansing agents.

SECTION 14: Transport information			
14.1 UN number or ID number			
ADR, ADN, IMDG, IATA	Void		
14.2 UN proper shipping name			
ADR	Void		
ADN, IMDG, IATA	Void		

(Contd. on page 7)

Revision: 28.11.2023

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2023

Version number 7 (replaces version 6)

### Trade name: 705 Watertight Tile Adhesive

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class Void · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Not applicable. · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. UN "Model Regulation": Void

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

(Contd. on page 8)

Printing date 28.11.2023

Version number 7 (replaces version 6)

## Trade name: 705 Watertight Tile Adhesive

(Contd. of page 7)

Revision: 28.11.2023

H335 May cause respiratory irritation.

· Department issuing SDS: R&D department

Contact: Ing. T.W. Breeuwer

· Version number of previous version: 6

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

INDG: International Maritime Code for Dangerous Goods

MDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB