

Forbo Environmental Data Sheet

| | |
|------------------------|---|
| Product name | Tessera Inline |
| Product description | Tessera Inline features differential texture and is produced with premium polyamide 6. Inline complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets. |
| Manufacturing location | Bamber Bridge, United Kingdom |
| Site accreditation | ISO14001, ISO 9001, OHSAS 18001, SA8000® |



Our footprint – how it's made

Environmental data

Total recycled content of product by weight 63%

Post industrial recycled content 63%

% renewable electricity & biogas used 100%

Independent assessment and rating

ISO 9001 Quality Management System



ISO 14001 Environmental Management System



OHSAS 18001 Occupational Health and Safety Management



Inline is made in an SA8000® certified facility



Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025 Raw materials and production 11.6 kg CO₂ eq/m²

Use (1 year) 0.804 kg CO₂ eq/m²

Your footsteps – how it performs

Health and well being

Air quality CHPS 01350 Tessera products comply to 01350 Indoor Air Quality Standard

Impact sound reduction 25 dB

Installation

Recommended adhesives Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended. Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.

Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non-hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle used carpet tiles in the UK.

Contribution to Green Building Schemes

BREEAM 2014

| BREEAM ratings | Building Type | | | | Retail (Durability) | Retail (Fashion) |
|----------------|---------------|-----------|--------|----------|---------------------|------------------|
| | Office | Education | Health | Domestic | A | A+ |
| | A | A | A | A | A | A+ |

BREEAM 2018

Compliant through declaration number 4788603145.128.1 Valid until November 2023

LEED (version 4)

| Potential direct or indirect contribution to following categories and credits: | Materials and Resources |
|--|--|
| | Building product disclosure and optimisation - sourcing of raw materials - up to 1 point |
| | Construction and demolition waste management up to 2 points |
| | Indoor environmental quality |
| | Low emitting materials up to 3 points |
| | Acoustic performance up to 1 point |

Forbo design principles (Reduce, Recycle, Reuse, Renew)

| | |
|----------------|---|
| Reduce | Investment in an extruder has reduced our bitumen usage by 50%. |
| Reuse | Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials. |
| Recycle | Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles contain at least 57% recycled content by weight. |
| Renew | All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas). |

visit www.forbo-flooring.co.uk/downloads for more information