



transtex belting
conveyor belts

quiet belt

LIGHTWEIGHT CONVEYOR BELTING

Lightweight conveyor belting (Transtex Belting) is pleased to present our expanded range of "QB" conveyor belting. Developed in response to specific market needs for performance and low noise operation, each product truly lives up to its name, and that is music to anyone's ears.

Lower noise levels 20 db is similar to going from a busy street into the average home. Reduced noise generation means a more comfortable and safer working environment. "QB" products are an excellent choice in large Airport Baggage Handling, Distribution Center, and Package Handling applications that are becoming increasingly sensitive to the environment issues of noise generation.

transtex®—lightweight rubber & pvc



MOVEMENT SYSTEMS

PRODUCT SPECIFICATIONS

Product Specification:	QB 120 FXF-NA BLACK FR	QB 120 HMXF-NA BLACK FR	QB 120 LRXF-NA BLACK FR	QB 120 RTXF-NA BLACK FR	QB 150PH RTXF-NA BLACK FR
Transtex® Product Code:	908131	908132	908133	908134	908137
Nominal Overall Gauge					
inches:	0.100 +/- 0.01	0.100 +/- 0.01	0.145 +/- 0.01	0.225 +/- 0.01	0.250 +/- 0.01
mm:	2.5 +/- 0.25	2.5 +/- 0.25	3.7 +/- 0.25	5.7 +/- 0.25	6.4 +/- 0.25
Rated Working Tension:	120 lbs./in. 21 N/mm. @ 1.5%	120 lbs./in. 21 N/mm. @ 1.5%	120 lbs./in. 21 N/mm. @ 1.5%	120 lbs./in. 21 N/mm. @ 1.5%	150 lbs./in. 26 N/mm. @ 2%
Minimum Pulley Diameter:	1.5 inches / 38 mm.	2.5 inches / 64 mm.	2.5 inches / 64 mm.	2.5 inches / 64 mm.	3 inches / 76 mm.
Special Standards:	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378

PRODUCT SPECIFICATIONS

Product Specification:	QB150PH FXF-NA BLACK FR	QB150PH HMXF-NA BLACK FR	QB150PH LRxF-NA BLACK FR
Transtex® Product Code:	908120	908135	908136
Nominal Overall Gauge			
inches:	0.125 +/- 0.01	0.14 in ± 0.01	0.17 in ± 0.01
mm:	3.18 mm ± 0.25	3.56 mm ± 0.25	4.32 mm ± 0.25
Rated Working Tension:	150 lbs./in. 26 N/mm. @ 2%	150 lbf/in. 26 N/mm. @ 2%	150 lbs./in. 26 N/mm. @ 2%
Minimum Drum Diameter			
Mechanical fastener, bending:	2.5 inches / 64 mm.	3 inches / 76 mm.	3 inches / 76 mm.
Special Standards:	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378	Fire resistant to ASTM D-378



MOVEMENT SYSTEMS

Forbo Movement Systems

Transtex® Belting

10125 South Tryon Street
Charlotte, NC 28273

Toll Free: (800) 922-1735

E-Mail: transtex.us@forbo.com

www.forbo-transtex.com

Forbo Movement Systems is part of the Forbo Group,
a global leader in flooring, bonding and movement systems.