

eurocol

543

the strong connection

17-9-2026



EUROSAFE DECO

Ready-to-use dispersion adhesive with a high, permanent adhesive strength for installing dimensionally stable PVC slats and tiles on leveled subfloors. Because the adhesive is applied with a fur roller, there is no chance of adhesive grooves showing through. This also results in favourable consumption and ergonomic processing. Also suitable for gluing or fixing certain types of carpet tiles. Thanks to EMICODE EC 1PLUS (very low emission) also suitable for BREEAM projects

PRODUCT TYPING

Base	Acrylic dispersion.
------	---------------------

Color	Light blue.
-------	-------------

Consistency	liquid.
-------------	---------

- Very low emission
- Emicode EC 1PLUS
- Pressure sensitive
- High temperature resistant
- Solvent free
- Non-flammable
- Favourable spreading capacity
- No grin through of adhesive trowel marks
- Easy and safe to apply
- High final bond strength

PROPERTIES

Consumption	100-150 g/m ² , on levelled subfloors.
-------------	---

Frost resistance	No.
------------------	-----

Sensitive to frost	Yes.
--------------------	------

Specific weight	1.04 kg/l.
-----------------	------------

APPLICATION

For the installation of dimensionally stable PVC sheet, strips and tiles on levelled subfloors. Suitable for pressure sensitive installation. Also high temperature resistant, up to a structural surface temperature of maximum 50 °C, for installation in areas with direct sunlight.

PROCESSING

Storage	Store cool and free from frost. Protect against high temperatures.
---------	--

Tools	Fur roller and/or brush.
-------	--------------------------

543 EUROSAFE DECO

Curing	24 hours.*
Waiting time	None.
Shelf Life	15 months, in unopened packaging.
Cleaner	Water.

*The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- 543 Eurosafe Deco is suitable for any type of subfloor that has good tensile and compression strength. The subfloor should also be even, clean, permanently dry and free from grease and dirt according to the requirements of BS 8203 or DIN 18 365.
- Anhydrite floors should be sandpapered. Thereafter make the floor dust free and prime with 044 Europrimer Multi. This layer has to dry sufficiently.
- For an optimal final result, apply a 2 mm levelling compound layer on the subfloor.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Instruction manual:

- It is very important to acclimatize the PVC-material for at least 48 hours in the room where it will be installed.
- Apply the 543 Eurosafe Deco with a Fur roller and/or brush.
- The sheets, strips or tiles can be placed directly into the wet, semi moist or dry adhesive.
- Drying time is depending on temperature, relative humidity and the porosity of the subfloor.
- After applying carefully roll and firmly rub the strips or tiles in to the adhesive line.
- Drying time minimal 24 hours.
- Remove fresh adhesive spots immediately with a clean damp cloth.

Working conditions:

Required surrounding temperature : 18 - 23 °C

Temperature for material and subfloor : min. 15° - max. 20 °C.

Relative humidity : 40-80%.

High temperature characteristics: underfloor heating systems and direct sunlight:

543 Eurosafe Deco can be applied on underfloor heating systems. The start protocol of the floor heating needs to be completely executed in accordance with the directives of the supplier. Turn off the heater 24 hours before fixation. Do not heat again until at least 24 hours after fixation, in steps of maximum 5 °C water temperature per day.

If there is the possibility that the PVC- strips or tiles will get warmer than 50 °C (also by sunlight), you have to choose for a polyurethane bonding.

543 Eurosafe Deco is tested in combination with high temperatures. The adhesive is tested suitable for installing PVC-material, exposed to higher temperatures such as direct sunlight provided the surface does not exceed 50 °C. Installation in wet adhesive is preferred for such conditions.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1) and benzisothiazolinone. May produce an allergic reaction.

QUALITY AND GUARANTEE



ENVIRONMENT AND HEALTH

Hazard Class	None.
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Bound material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website www.eurocol.nl .

ITEM DATA

Article	Definition	Packaging	EAN-code
543	Eurosafe Deco	10 kg bucket.	8 710345 543002

543 EUROSAFE DECO



Package 10kg

543 EUROSAFE DECO

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | info.eurocol@forbo.com
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | info.eurocol.de@forbo.com

Eurocol is part of the Forbo Group

