


DoP (declaration of performance)
Declaration of performance
Nr. 924.1.1

924 EUROPLAN HYBRID

| | | |
|---|--|---|
| 1. Unique identification | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar. | |
| 2. Designation | Forbo Eurocol 924 Europlan Hybrid; Self-levelling compound, tension-free curing for both calcium sulphate and cementitious subfloors. | |
| 3. Application | For levelling in coatings from 2 tot 10 mm of cementitious and anhydrite-bound subfloors, mastic asphalt, magnesite, wood granite, chipboard or existing tiling. | |
| 4. Name and contact address manufacturer | <i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i> | |
| 5. Name and contact address authorized | n/a | |
| 6. System of assessment and verification of constancy of performance | 4 | |
| 7. Activity of the notified certification body as required by the harmonized standard | n/a | |
| 8. European Technical Assessment | n/a | |
| 9. Declared performance | CA-C50-F10 In accordance with NEN-EN 13813:2002 Self-levelling compound, tension-free curing for both calcium sulphate and cementitious subfloors. | |
| Essential characteristics | Performance | Test method |
| Tensile strength after 28 days | F10 | NEN-EN 13892-2:2002 |
| Compressive strength after 28 days | C50 | NEN-EN 13892-2:2002 |
| Material behaviour in case of fire | Class F | NEN-EN 13501-1:2007+A1:2009 |
| Released dangerous substances | see MSDS | |
| Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002 | | |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. | | |
| | | Wormerveer, 03-05-2019 signed: ing. T.W. Breeuwer; Manager R&D  |