Technical specifications

Flotex Naturals, Visions and Sottsass sheet meet the requirements of EN 1307

		Flotex Naturals, Visions and Sottsass
Total thickness	ISO 1765	4.3 mm
Commercial use	EN 685	Class 33 heavy
Roll width		2.0 m
Roll length		30 m
Total weight	ISO 8543	1.8 kg/m²
Dimensional stability	EN 986	<0.2%
Abrasion resistance	EN 1307 annex F	> 1000 cycles
Castor chair continuous use	EN 985 Test A	r = ≥ 2.4 continuous use - Pass
Light fastness	EN-ISO 105-B02	≥6
Acoustic	EN-ISO 717-2	Impact sound ΔLw ≥ 20 dB
	ISO 354	Sound absorption = 0.10
Water impermeability	EN 1307 annex G	Pass
Resistance to fungal growth	AS 1157.4: 1978	Total resistance
Creating better environments		
Renewable electricity	Flotex is manufactured using 100% electricity made from renewable sources	
Recycled content	Flotex sheet contains up to 20% recycled content by weight	
Life cycle assessment	LCA is a foundation for securing the lowest environmental impact	
Flotex meets the requirements of EN 14041		C C EN 1404
Reaction to fire	AS/ISO 9239-1	CRF 9.0 kW/m² Smk dvlp 96 %.min
Slip resistance	AS/NZ 4586	R12/P5

0.048 m ² K/W
< 0,2 mg/ m³

Our recommended adhesive for the Flotex sheet collections is F54 or 640 Eurostar Special. For the latest installation instructions please visit www.forbo-flooring.com.au/installation.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have certified Environmental Management Systems in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



