

# Technical specifications

Marmoleum Marbled (Real, Fresco, Vivace , Splash, Terra) / Solid (Cocoa, Walton, Piano, Concrete, Slate) / Linear (Striato) meets the requirements of EN-ISO 24011 / Acoustic meets the requirements of EN 687 / Decibel meets the requirements of EN 686.

**marmoleum®**

		Marmoleum Marbled/Solid/Linear	Marmoleum Real/Fresco 3.2mm	Marmoleum Decibel	Marmoleum Acoustic	
	Total thickness	EN-ISO 24346	2.5 mm	3.2 mm	3.5 mm	4.0 mm
	Surface finish		Topshield <sup>2</sup>	Topshield <sup>2</sup>	Topshield <sup>2</sup>	Topshield <sup>2</sup>
	Domestic use	EN-ISO 10874	Class 23	Class 23	Class 23	Class 23
	Commercial use	EN-ISO 10874	Class 34	Class 34	Class 33	Class 33
	Light Industrial use	EN-ISO 10874	Class 43	Class 43	Class 41	Class 41
	Roll width	EN-ISO 24341	2.00 m	2.00 m	1.90 / 2.00 m	2.00 m
	Roll length	EN-ISO 24341	≤ 33 m	≤ 33 m	≤ 33 m	≤ 33 m
	Total weight <i>Typical value</i>	EN-ISO 24341	2900 g/m <sup>2</sup>	3900 g/m <sup>2</sup>	3100 g/m <sup>2</sup>	4000 g/m <sup>2</sup>
	Residual indentation <i>Typical value</i>	EN-ISO 23997	≤ 0.15 mm ~0.08 mm	≤ 0.15 mm ~0.10 mm	≤ 0.30 mm ~0.20 mm	≤ 0.40 mm ~0.25 mm
	Castor chair continuous use	ISO 4918/ EN 425	Suitable for office chairs with castors			
	Light fastness	EN-ISO 105-B02	Method: 3 blue scale minimum 6			
	Flexibility	EN-ISO 24344	ø 40 mm	ø 50 mm	ø 40 mm	ø 60 mm
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.			
	Bacteriostatic properties*	Marmoleum has natural bacteriostatic properties which are confirmed by independent laboratories, even against the bacteria MRSA.				
	Cigarette resistance	EN 1399	There is no melting of the surface by cigarettes. Marks left on Marmoleum as a result of stubbed-out cigarettes can be removed.			
	Acoustical impact sound reduction	EN-ISO 717-2	≤ 5 dB	≤ 6 dB	≤ 18 dB	≤ 14 dB
	Electrical resistance Marmoleum Ohmex	EN 1081	1-10 <sup>6</sup> < R1 < 1-10 <sup>8</sup> Ω static dissipative	-	-	-
	<b>Creating better environments</b>					
	Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact.				
	CO <sub>2</sub> neutral	Marmoleum 2.5 mm are produced CO <sub>2</sub> neutral (Cradle to gate).**				
	Renewable electricity	Marmoleum is manufactured using 100% electricity from renewable sources.				
	Natural materials (e.g. linseed oil, jute, tree resin, wood flour, limestone)	Marmoleum is made of 94-98% natural materials.				
		Marmoleum contains PEFC certified wood flour.				
		Marmoleum is free of PVC, PET, synthetic rubber and plasticizers.				
	Recycled content	Marmoleum contains recycled content.				
	Application on underfloor heating	yes	yes	yes	yes	yes
Marmoleum meet the requirements of EN 14041						
	Product code	EN 14041	0100201-DoP-306	0100201-DoP-306	0100201-DoP-306	0100201-DoP-306
	Reaction to fire	ISO 9239-1	CRF 9.2 kW/m <sup>2</sup> Smoke Dvlp 78%.min	CRF 5.6 kW/m <sup>2</sup> Smoke Dvlp 330%.min	CRF 5.1 kW/m <sup>2</sup> Smoke Dvlp 338%.min	CRF 6.8 kW/m <sup>2</sup> Smoke Dvlp 380%.min
	Slip resistance	AS 4586:2013	R10	R10	R10	R10
	Body voltage	EN 1815	≤ 2 kV	≤ 2 kV	≤ 2 kV	≤ 2 kV
	Thermal conductivity	EN 12524	0.17 W/m-K	0.17 W/m-K	0.17 W/m-K	0.17 W/m-K
	Indoor Air Emissions: TVOC at 28 days	EN 16516	< 0,05 mg/m <sup>3</sup>	< 0,05 mg/m <sup>3</sup>	< 0,05 mg/m <sup>3</sup>	< 0,05 mg/m <sup>3</sup>

\*Marmoleum sheet can be installed nett fit, or with a welding rod in the seam. Both are proven hygienic solutions.

\*\*For verification and details please consult our Marmoleum EPD.

**Recommended adhesives:** For the latest installation instructions and recommended adhesives please visit [www.forbo-flooring.com.au/installation](http://www.forbo-flooring.com.au/installation)

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites.

Marmoleum is manufactured in a facility certified to SA8000 and ISO 45001.



Whilst Forbo Flooring Systems Pty Ltd does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring Systems Pty Ltd makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

✉ [info.au@forbo.com](mailto:info.au@forbo.com)

☎ 1800 224 471

🌐 [forbo-flooring.com.au/marmoleum](http://forbo-flooring.com.au/marmoleum)

📄 [forbo-flooring.com.au/downloads](http://forbo-flooring.com.au/downloads)

