









Technical specifications

Allura Click underlay (best performance underlay)

allura click underlay

	Total thickness	EN-ISO 24346	1.5 mm
	Roll width	EN-ISO 24341	1 m
	Roll length	EN-ISO 24341	10 m
	Total weight	ISO 23997	1.5 kg/m ²
	Impact noise reduction	EN ISO 717-2	15 dB in combination with Allura Click
	Castor chair continuous use	ISO 4918	Good, with and without Forbo underlay
	Residual indentation <i>Typical value</i>	ISO 24343-1	≤ 0.10 mm in combination with Allura Click ~ 0.05 mm
	Compressive strength	EN 826	390 kPa
	Reaction to fire	EN 13501	B _n -s1 in combination with Allura Click
	Thermal conductivity	EN 12524	0.01 m ² pk/w

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Allura is manufactured in a facility certified to SA8000 and OHSAS 18001.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 0282 162**

w: forbo-flooring.co.uk/allura