

Technical specifications

Sphera meets the requirements of EN ISO 10581

sphera®

		sphera element	sphera energetic	sphera elite
	Total thickness	EN ISO 24346	2.0 mm	2.0 mm
	Surface finish		SMART top	SMART top
	Binder content	EN ISO 10581	Type 1	Type 1
	Collection size		52	42
	Domestic use	EN ISO 10874	Class 23	Class 23
	Commercial use	EN ISO 10874	Class 34	Class 34
	Light industrial	EN ISO 10874	Class 43	Class 43
	Roll width	EN ISO 24341	2.0 m	2.0 m
	Roll length	EN ISO 24341	≤ 27 m	≤ 27 m
	Total weight	EN ISO 23997	2900 g/m ²	2850 g/m ²
	Dimension stability <i>Typical value</i>	EN ISO 23999	≤ 0.4% ~ 0.2%	≤ 0.4% ~ 0.2%
	Slip resistance (ramp test)	DIN 51130	R9	R9
	Castor chair continuous use	ISO 4918	Pass	Pass
	Residual indentation <i>Typical value</i>	EN ISO 24343-1	≤ 0.10 mm ~ 0.03 mm	≤ 0.10 mm ~ 0.03 mm
	Colour fastness to light (method 3)	ISO 105-B02	≥ 7	≥ 7
	Indoor air emissions: TVOC after 28 days	ISO 16516	≤ 0.01 mg/m ³	≤ 0.01 mg/m ³
	Resistance to chemicals	EN ISO 26987	Very good	Very good
	Flexibility	EN ISO 24344	ø 10 mm	ø 10 mm
	Use in wet areas	EN 13553	Yes	Yes
	Cleanroom particle emission	ISO 14644-1	ISO 4	-
	Bacteria resistance	EN 846	Does not support growth	
	Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact		
	Renewable electricity	Sphera is manufactured using 100% electricity made from renewable sources		
	Indoor air quality	All products are tested for indoor air emissions in accordance with ISO 16000-9 after 3 days and 28 days.		
	Back to the Floor	Installation off cuts can be collected via Back to the floor		
	SKA	Sphera meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes		

EN 14041



0200301-DoP-605

Sphera meets the requirements of EN 14041:2004

	Reaction to fire	EN 13501-1	B _f -s1, L, CS	B _f -s1, L, CS	B _f -s1, L, CS
	Slip resistance	EN 13893	μ ≥ 0.30	μ ≥ 0.30	μ ≥ 0.30
	Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK	0.25 W/mK
	Body voltage	EN 1815	≤ 2.0 kV	≤ 2.0 kV	≤ 2.0 kV

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Sphera is manufactured in a facility certified to SA8000 and OHSAS 18001.



BREEAM ratings

Sphera – Homogeneous Floor covering (EN 649)

Commercial	Education	Health	Domestic	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
A	A+	A+	A	A+	A+	✓

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 0282 162**

w: forbo-flooring.co.uk/sphera