

eurocol

896

the strong connection

14-7-2026



EUROCARE OIL

Care and refresh oil, long-lasting protection for wooden floors, extends life of parquet sealing, regenerates the existing coating during maintenance care and fills in slight scratches, the oil provides an additional protective film on the wooded surface.

PRODUCT TYPING

Base	Refined natural oils, < 5% anionic surfactants, <5% non-ionic surfactants, surfactants from coconut fats, < 5% soap, potash, lead-free drying agents, additives, pot preservative (1,2-Benzisothiazol-3(2H)-one (BIT) / zinc pyrithione.
Color	Milky.
Consistency	Thick liquid.

- Effective care combination for initial care, maintenance cleaning and for refreshing parquet and cork floorings impregnated with oil-based Eurocol products as well as for UV-oiled wood surfaces.
- Can be used as wiping water additive for maintenance care.
- Effective and economical to use, as it is water-dilutable.
- Prolongs the life of the impregnation of parquet.
- Regenerates the existing coating during maintenance care and fills light scratches.
- The oil component provides an additional protective film on the wood surface.

PROPERTIES

Consumption	Initial care: dilute approx. 1:1, approx. 2 - 5 ml/ m ² , if necessary, especially with compacted wood surface, dilute approx. 1:2 to 1:3 Maintenance care: approx. 250 ml per 5 l of mopping water, sufficient for approx. 100 m ² (diluted in wiping water).
Flammability	Non-flammable.
Frost resistance	No.
Passableness	First careful use after 1 hr.
Special quality	Cleaning and care in one step.
Specific weight	0,98 kg/l

APPLICATION

Initial care, maintenance cleaning and to refresh oiled wood surfaces.

PROCESSING

Storage	Store cool and dry in unopened packaging.
Tools	Wiper.
Mixing ratio	Initial care: dilute approx. 1:1, especially with compacted wood approx. 1:2 to 1:3. Maintenance care:

896 EUROCORE OIL

	approx. 250 ml per 5 l of mopping water.
Shelf Life	Approx 36 Months, in unopened packaging.
Cleaner	Water.
Remarks	Technical information and safety data sheets of other installation materials and parquet must be observed! Not to be used for the treatment of resilient floorings. Initial care or maintenance must be carried out before the first full load and after the oil used has completely dried through. For care, follow the corresponding care instructions.

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Substrate:

- The sealing of parquet and cork floors must be completely closed.
- Coarse dirt must first be removed by sweeping or vacuuming.

Instruction manual:

- Mechanically clean/suck the floor before use to remove loose dirt.
- Temper the product.
- Shake carefully before use to achieve an even distribution of the oil components.
- The material can be applied with a lint-free cloth or wiping weasel.
- Always treat the area to be treated in one go to avoid build-up.
To care for a new, sufficiently set, tack-free dry oiled surface, apply the material diluted approx. 1:1. Wipe evenly and damply in the longitudinal direction of the wood grain. If the wood surface is very dense, the Care products should be diluted approx. 1:2 to 1:3 with water to avoid oil accumulation on the surface.
- For maintenance care, dilute approx. 250 ml to 5 l water. Use this solution to apply the impregnated wood floor in one direction along the grain.
- For UV-oiled floors, reduce the quantity of the care product to approx. 150 ml per 5 l of wiping water.
- If necessary, allow any adhering dirt to "soak" a little and rub off mechanically - remove. Use a lint-free cloth or white pad for this.
- The drying time is approx. 1 hour in a normal room climate, after that it can be walked on.
If a slight shine and densification of the surface is desired to reduce soiling, the dry floor can be polished with a white pad.
- When used as a refresher for worn floors, make sure that there is no open wood on the surface. At these points the floor should be re-impregnated locally with a Eurocol Oil.

ENVIRONMENT AND HEALTH

GISCODE	GE10
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Bound material residues can be disposed of as household waste.
Substances causing allergy	Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

ITEM DATA

artikel	productname	packaging	shipping unit
896	Eurocare Oil	PE jerrycan à 1 l	4/box 552/pallet

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG175225, Version V04, Stand 2019-09-18, ersetzt Version vom 2019-08-13.

896 EUROCARE OIL

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | info.eurocol@forbo.com
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | info.eurocol.de@forbo.com

Eurocol is part of the Forbo Group

