

841

EC ADDITIVE

PRODUCT DESCRIPTION

Additive to be added in Eurocol 541 Eurofix Anti Slip to create electrically conductive fixing agent.



PRODUCT FEATURES

The dispersion can added to 541 Eurofix Anti Slip.

TECHNICAL DATA

Base	carbon dispersion
Colour	black
Density	approx. 1,2 g/cm ³
Consistency	Low viscosity
Cleaning agent	Water
Processing conditions	not below 15 °C on the subfloor, minimum 18 °C material- and room temperature 35-75% relative air moisture, recommended <65%
Mode of applciation	Roller, brush application in combination to Eurocol 541
Consumption	3,5 kg added to 10 kg 541
Pemitted shelf-life	within approx. 12 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C,
Frost sensitivity	yes
Code acc. to GHS	no
Environment/Work safety	DGNB: VOC 0 %, Quality level: 3 LEED: VOC 49,8 g/l

841

Europrimer EC

SUBFLOOR

See subfloor preparation for Eurocol 541 Eurofix Anti Slip

INSTRUCTIONS OF USE

Shake well before use.

Add in a ratio of 3,5 kg to 10 kg 541 Eurofix Anti Slip and mix thoroughly.

The mixed product consume as fast as possible. Remix it after 1 hr.

See instruction of use for 541 Eurofix Anti Slip.

NOTES

Relevant norms and regulations are to be respected.

Please pay attention to the technical and safety data sheets.

PACKAGING

3,5 kg package (96/palette)

SPECIAL NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.

The manufacturer's terms and conditions are binding.

Last updated 27.8.2018
supersedes issue as of

Version Nr.: 01
BG169216_841

SPACE FOR YOUR REMARKS
