Forbo Environmental Data Sheet

| Product name | Coral Classic Sheet and tiles (Everfort vinyl backing) | |
|------------------------|--|--|
| Product description | Coral Classic entrance systems are a textile floor covering complying with all the requirements of the EN 1307 Class 33 specification | |
| Manufacturing location | Krommenie, Holland | |
| Site accreditation | ISO14001, ISO 9001, SA8000® | |

Our footprint – how it's made

| Environmental data | | Independent assessment and rating | | |
|----------------------------------|-------|--|--|--|
| Total recycled content | 1 50/ | ISO 9001 Quality Management System | LRQA CERTIFIED ISO 9001 | |
| of product by weight | 1.5% | ISO 14001 Environmental Management System | CERTIFIED ISO 14001 | |
| Post industrial recycled content | 1.5% | Coral Classic sheet and tiles are manufactured in a SA8000° certified facility | SAI Accessival Presentation Pre | |
| Post consumer recycled content | 0% | | | |
| % renewable electricity used | 100% | | | |
| Carbon footprint | | | | |

| Estimated carbon footprint using | Raw materials and production | Awaiting update |
|--|------------------------------|-----------------|
| data from Environmental product declaration according to ISO 14025 | | Awaiting update |

Your footsteps – how it performs

| Health and well being | | |
|-----------------------|---|--|
| CHPS 01350 | Coral Brush products comply to 01350 indoor air quality standard. | |
| Installation | | |
| Recommended adhesives | Adoption of best practice in relation to installation techniques including subfloor preparation is essential to ensure the optimum performance and life expectancy of the floor covering Forbo recommends the low emission adhesive Eurocol 640 Eurostar Special. | |

creating better environments



Maintenance Coral entrance mats will, by their nature and location, be one of the most 'abused' of all floor coverings within a building. Thorough and regular cleaning is essential to ensure optimum performance and to extend the lifespan of the products. The frequency of cleaning is determined by the traffic volume and level of soiling. End of life Coral products can be recycled, downcycled or used to recover energy at the end of their life.

Contribution to Green Building Schemes

BREEAM 2018 Value of Credit Awaiting updated EPD LEED (version 4) Potential direct or indirect Materials and resources Regional materials, credit 5 contribution to following categories and credits: Indoor environmental Indoor environmental quality - low emitting materials credit 4.3 quality Forbo design principles (Reduce, Recycle, Reuse, Renew) Reduce Reduce energy consumption by closing down unused compressors. Installing an effective entrance system can reduce cleaning time by up to 65%. Reuse Increase re-use of wastes by introducing more efficient waste separation methods. Recycle Recycle sampling material through the Save a Sample scheme. Any yarn waste is returned to the yarn supplier for recycling. Renew 100% of the electricity used is from a renewable source.

Detailed environmental product declarations and full Life Cycle Analysis

Visit www.forbo-flooring.co.uk/downloads for more information