

ENVIRONMENTAL PRODUCT DECLARATION

MARMOLEUM TILE 2.0 AND 2.5MM

FORBO FLOORING SYSTEMS
RESILIENT LINOLEUM FLOOR COVERING



Marmoleum tile

Color t2874 "Coffee" - t2767 "Rust" - t2707 "Barley"



FLOORING SYSTEMS

Marmoleum the most globally used brand of linoleum has been manufactured by Forbo for more than 150 years. Marmoleum is produced having low environmental impacts as a result of the combination of natural renewable materials and high recycle content.

Forbo was the first flooring manufacturer to publish a complete Life Cycle Assessment (LCA) report verified by CML in 2000. In addition Forbo is now to publish Environmental Product Declarations (EPD) for all products including full LCA reports. This EPD is using all recognized flooring Product Category Rules and is including additional information to show the impacts on human health and eco-toxicity. By offering the complete story we hope that our stakeholders will be able to use this document as a tool that will translate the environmental performance of Marmoleum into the true value and benefits to all our customers and stakeholders alike.

For more information visit:

www.forbo-flooring.com





FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

This declaration is an environmental product declaration in accordance with ISO 14025 and EN15804 that describes the environmental characteristics of the aforementioned product. It promotes the development of sustainable products. This is a certified declaration and all relevant environmental information is disclosed. This EPD may not be comparable to other declarations if they do not comply with ISO 14025, EN 15804 and the reference PCR.



PROGRAM OPERATOR	UL Environment 333 Pfingsten Road Northbrook, IL 60611
DECLARATION HOLDER	Forbo Nairn Ltd Fife KY1 2SB P.O. Box 1 Kirkcaldy, United Kingdom
DECLARATION NUMBER	12CA64879.101.1
DECLARED PRODUCT	Marmoleum 2.0 and 2.5mm Resilient Linoleum Floor Covering
REFERENCE PCR	Flooring: Carpet, Resilient, Laminate, Ceramic, and Wood (NSF 2012)
DATE OF ISSUE	January 18 th , 2013
PERIOD OF VALIDITY	5 Years
CONTENTS OF THE DECLARATION	Product definition and information about building physics Information about basic material and the material's origin Description of the product's manufacture Indication of product processing Information about the in-use conditions Life cycle assessment results Testing results and verifications
The PCR review was conducted by:	NSF International Accepted by PCR Review Panel ncss@nsf.org
This declaration was independently verified in accordance with ISO 14025 and EN 15804 by Underwriters Laboratories ☐ INTERNAL ☒ EXTERNAL	 Loretta Tam, ULE EPD Program Manager
This life cycle assessment was independently verified in accordance with ISO 14044, EN 15804 and the reference PCR by:	 Trisha Montalbo, PE International



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Product Definition

Product Classification and description

This declaration covers a broad range of designs and colors. Marmoleum is a resilient floor covering complying with all the requirements of EN-ISO 24011: Specification for plain and decorative linoleum. Marmoleum is made from natural raw materials making it preferable ecological floor covering with a beautiful and colorful design. The key raw materials include linseed oil, which comes from the flax plant seeds, gum rosin from pine trees, recycled wood waste of wood from controlled forests and limestone. Because of the use of natural raw materials Marmoleum is biodegradable.

Linoleum is produced by Forbo Flooring for more than 150 years and our well known brand Marmoleum is sold worldwide. This declaration refers to Marmoleum sheet of 2.0 and 2.5 mm nominal thickness.

Marmoleum is build up in 3 layers as illustrated in the figure 1. These three layers form one homogeneous product by the cross linking bondings formed during the oxidative curing process:




Figure 1: Illustration of Marmoleum

1. **Surface layer:** This layer gives Marmoleum its design and color. After finishing the product at the trimming department a factory finish is applied to protect the surface layer.
2. **Intermediate layer:** This layer is calendared on the polyester backing.
3. **Backing:** The backing is a polyester fleece.

Range of application

Marmoleum tile is classified in accordance with EN-ISO 24011 to be installed in the following use areas defined in EN-ISO 10874:

Area of application	2.0 mm thickness	2.5 mm thickness
Domestic	Class 23 	Class 23
Commercial	Class 32 	Use class 34
Industrial	Class 41 	Use class 43



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Product Standard

The products considered in this EPD have the following technical specifications:

- o Meets or exceeds all technical requirements in ASTM F 2195 Standard Specification for Linoleum Floor Tile.
- o Meets or exceeds all technical requirements in EN-ISO 24011 Specification for plain and decorative Linoleum.



Marmoleum meets the requirements of EN 14041

EN 13501-1	Reaction to fire	C _{fl} - s1
EN 13893	Slip resistance	DS: ≥ 0.30
EN 1815	Body voltage	< 2 kV
EN 12524	Thermal conductivity	0.17 W/mK

Fire Testing:

- o Class 1 when tested in accordance with ASTM E 648/NFPA 253, Standard Test Method for Critical Radiant Flux.
- o Meets 450 or less when tested in accordance with ASTM E 662/NFPA 258, Standard Test Method for Smoke Density.
- o Class C when tested in accordance to ASTM E 84/NFPA 255, Standard Test Method for Surface Burning Characteristics.
- o FSC1-150; SD-160 when tested in accordance to CAN/ULC S102.2, Standard Test Method for Flame Spread Rating and Smoke Development.
- o Compliant with CHPS 01350 requirements for VOC emissions and indoor air quality.

Accreditation

- o ISO 9001 Quality Management System
- o ISO 14001 Environmental Management System
- o SMART
- o SWAN
- o Nature Plus
- o Good Environmental Choice Australia



The standard for
sustainable living™





FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Delivery Status

Table 1: Specification of delivered product

Characteristics	Nominal Value	Unit
Product thickness	2.5	mm
	2.0	mm
Product Weight 2.5 mm 2.0 mm	3000 2300	g/m ²
Rolls Width Length	333 or 500	mm
	333 or 500	mm

Material Content

Material Content of the Product

Table 2: Composition of Marmoleum tile

Component	Material	Availability	Amount [%]	Origin
Binder	Linseed oil	Bio based crop	20	USA/Canada/Europe Indonesia/China USA
	Gum rosin	Bio based crop	2	
	Tall oil	Bio based waste product from paper Industry	6	
Filler	Wood flour	Bio based waste product from wood processing	31	Germany
	Calcium carbonate	Abundant mineral	8	Germany
	Reused Marmoleum		23	Internal
Pigment	Titanium dioxide	Limited mineral	3	Global
	Various other pigments	Limited mineral	1	Global
Backing	Polyester	Fossil limited	5	Europe
Finish	Lacquer	Fossil limited	1	Netherlands

Production of Main Materials

Linseed oil : Linseed oil is obtained by pressing the seeds of the flax plant. After filtering a clear golden yellow liquid remains.

Gum rosin : Rosin is obtained by wounding pine trees. The crude gum is collected and is separated into turpentine and rosin by distillation.

Tall oil : Tall oil is a post industrial waste product coming from the paper industry and is consisting of vegetable oil and rosin.

Wood flour : Post industrial bio based soft wood waste from the wood industry, which is milled into flour.

Calcium carbonate : An abundant mineral found in all parts of the world as the chief substance in rocks (i.e., marble and limestone). It can be ground to varying particle sizes and is widely used as filler.

Reused Marmoleum : Waste material coming from the Marmoleum production which is reused.

Titanium dioxide : A white pigment produced from the mineral rutile, a naturally occurring form of titanium dioxide. The production of the pigment is a large-scale chemical process

Various other pigments : The vast majority of the used color pigments are iron oxide based.

Polyester : Polyester fibers woven into a fabric which is used as a substrate.

Lacquer : The factory applied lacquer – Topshield 2 – is a waterborne UV cured urethane – acrylate hybrid dispersion.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Production of the Floor Covering




Figure 2: Illustration of the Production process

Marmoleum tile is produced in several stages starting with the oxidation of linseed oil mixed with tall oil and rosin. With the influence of oxygen from the atmosphere a tough sticky material is obtained called linoleum cement. The linoleum cement is stored in containers for a few days for further reaction and after this it is mixed with wood flour, calcium carbonate, reused waste (if applicable), titanium dioxide and pigments. This mixture is calendared on a polyester substrate and stored in drying rooms, to cure till the required hardness is reached. After approximately 14 days the material is taken out from the drying room to the trimming department where the factory finish is applied on the surface of the product and the end inspection is done. Finally the edges are trimmed and the sheet is cut to length into tiles of 333 x 333 or 500 x 500 millimeter. The trimmings and the rejected product are reused.

Health, Safety and Environmental Aspects during Production

- o ISO 14001 Environmental Management System



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Production Waste

Rejected material and the cuttings of the trimming stage are being reused in the manufacturing process. Packaging materials are being collected separately and externally recycled.

Delivery and Installation of the Floor Covering

Delivery

A worldwide distribution by truck and container ship is considered. On average every square meter of Marmoleum is transported as follows:

- | | |
|--|---------|
| o Transport distance 40 t truck | 694 km |
| o Transport distance 7.5t truck (Fine distribution) | 257 km |
| o Capacity utilization trucks (including empty runs) | 85 % |
| o Transport distance Ocean ship | 4916 km |
| o Capacity utilization Ocean ship | 48% |

Installation

Because of the specific techniques used during the installation of Marmoleum tile 6% of the material is cut off as installation waste. For installation of Marmoleum tile on the floor a worst case scenario has been modeled (assuming 0.435 kg/m² of adhesive is required). In practice this amount will almost always be lower. Waste during the installation process may be recycled as floor covering through the manufacturers' facilities or thermally recycled in a waste incineration plant. Since the major part of Marmoleum tile is sold in Europe the European electricity grid mix is used in the calculations for the energy recovery during incineration.

Health, Safety and Environmental Aspects during Installation

Forbo flooring recommends to use (low) zero emission adhesives for installing Marmoleum.

Waste

Waste during the installation process may be recycled as floor covering through the manufacturers' facilities or thermally recycled in a waste incineration plant. Since the major part of Marmoleum tile is sold in Europe the European electricity grid mix is used in the calculations for the energy recovery during incineration.

Packaging

Cardboard tubes, PE-film and wooden pallets can be collected separately and should be used in a local recycling process. In the calculation model 100% incineration is taken into account for which there is a credit received.

Use stage

The service lifetime of a floor covering for a certain application on a floor is too widespread to give one common number. For this EPD model the reference service lifetime (RSL) is set to one year. This means that all impacts for the use phase are based on the cleaning and maintenance model for one year. Depending on the area of use, the technical lifetime advised by the manufacturer and the estimated time on the floor by the customer, the service lifetime



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

can be determined. The use phase impacts should be calculated with the foreseen service life to arrive at the total environmental impact.

Cleaning and Maintenance

Level of use	Cleaning Process	Cleaning Frequency	Consumption of energy and resources
Commercial/Residential/Industrial	Vacuuming	Twice a week	Electricity
	Damp mopping	Once a week	Hot water Neutral detergent

For the calculations the following cleaning regime is considered:

- Dry cleaning with a 1.5 kW vacuum cleaner for 0.21 min/m², twice a week. This equates to 0.55 kWh/m²*year.
- Once a week wet cleaning with 0.062 l/m² water and 0.0008 kg/m² detergent. This result in the use of 3.224 l/m²*year water and 0.04 kg/m²*year detergent. The wet cleaning takes place without power machine usage. Waste water treatment of the arising waste water from cleaning is considered.

The cleaning regime that is recommended in practice will be highly dependent on the use of the premises where the floor covering is installed. In high traffic areas more frequent cleaning will be needed compared to areas where there is low traffic. The use of an entrance mat of at least four steps will reduce the cleaning frequency.

The cleaning regime used in the calculations is suitable for high traffic areas.

Prevention of Structural Damage

All newly laid floor covering should be covered and protected with a suitable non-staining protective covering if other building activities are still in progress. Use protective feet on chairs and tables to reduce scratching. Castor wheels should be suitable for resilient floor coverings

Health Aspects during Usage

Marmoleum tile is complying with:

- o AgBB requirements
- o French act Grenelle: A+
- o CHPS section 01350

End of Life

The deconstruction of installed Marmoleum tile from the floor is done mechanically and the electrical energy needed for this is estimated to be 0.03 kWh/sqm. This amount of energy is taken into account for the calculations. For the end of life stage no landfilling is taken into account, since the vast majority of the countries in which Marmoleum tile is sold are having a non landfill policy. Because of the high calorific value of Marmoleum tile the incineration is very profitable as a waste to energy conversion.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Life Cycle Assessment

A full Life Cycle Assessment has been carried out according to ISO 14040 and ISO 14044.

The following Life Cycle Stages are assessed :

- o Production Stage (Raw material acquisition, transportation to Manufacturing and Manufacturing)
- o Transport Gate to User
- o Installation Stage
- o Use Stage
- o End of Life Stage




Figure 3: Flow chart of the Life Cycle Assessment

Description of the Declared Functional Unit

The functional unit is one square meter of installed product and the use stage is considered for one year of service life.

Cut off Criteria

The cut-off criteria shall be 1% of renewable and non-renewable primary energy usage and 1% of the total mass of the unit process. The total neglected input flows per module shall be a maximum of 5% of energy usage and mass.

In practice, in this assessment, all data from the production data acquisition are considered, i.e. all raw materials used as per formulation, use of water, electricity and other fuels, the required packaging materials, and all direct production waste. Transport data on all considered inputs and output material are also considered.

Allocations

In the present study some allocations have been made. Detailed explanations can be found in the chapters below.

Co-product allocation

No co-product allocation occurs in the product system.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Allocation of multi-input processes

The Production and End of Life stage include incineration plants. In these processes different products are treated together within a process. The allocation procedures followed in these cases are based on a physical classification of the mass flows or calorific values.

Credits from energy substitution are allocated to the production stage, because the gained energy from energy substitution is lower than the energy input in this stage. The same quality of energy is considered.

Allocation procedure of reuse, recycling and recovery

The installation waste and end of life waste is fed into incineration processes. Incineration processes include cogeneration processes which give thermal and power energy as outputs. It is assumed that this recovered energy offsets that produced by the European average grid mix and thermal energy generation from natural gas.

The LCA dataset used to model the incineration of Marmoleum tile is based on data developed by European Resilient Flooring Manufacturers' Institute (ERFMI) and is specific to linoleum flooring products. This indicates that 250 kWh/tonne electricity and 9744 MJ/tonne thermal energy is recovered during incineration. This model is part of the ERFMI 2008 LCA study on resilient floorings; critical reviewed by Dr ir Jeroen Guinée (Institute of Environmental Sciences CML) /ERFMI 2008/.

Description of the allocation processes in the LCA report

The description of allocation rules in of this LCA report meets the requirements of the PCR.

LCA Data

As a general rule, specific data derived from specific production processes or average data derived from specific production processes have been used as the first choice as a basis for calculating an EPD.

For life cycle modeling of the considered products, the GaBi 5 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG has been used. All relevant LCA datasets are taken from the GaBi 5 software database. The datasets from the database GaBi are documented in the online documentation. To ensure comparability of results in the LCA, the basic data of GaBi database were used for energy, transportation and auxiliary materials.

Data Quality

The requirements for data quality and LCA data correspond to the specifications of the PCR.

Foreground data are based on 1 year averaged data (year 2011). The reference ages of LCA datasets vary but are given in the table in the Appendix. The time period over which inputs to and outputs from the system is accounted for is 100 years from the year for which the data set is deemed representative. The technological LCA of the collected data reflects the physical reality of the declared product. The datasets are complete, conform to the system boundaries and the criteria for the exclusion of inputs and outputs and are geographical representative for the supply chain of Forbo flooring.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

For life cycle modeling of the considered products the GaBi 5 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG, is used. All relevant LCA datasets are taken from the GaBi 5 software database. The last revision of the used data sets took place within the last 10 years.

System Boundaries

Production Stage includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of waste state or disposal of final residues during the product stage.

Transport and Installation Stage includes provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction stage. These information modules also include all impacts and aspects related to any losses during this construction stage (i.e. production, transport, and waste processing and disposal of the lost products and materials). For the transportation a worldwide distribution is considered.

Use Stage includes provision and transport of all materials, products and related energy and water use, as well as waste processing up to the end-of-waste state or disposal of final residues during this part of the use stage. These information modules also include all impacts and aspects related to the losses during this part of the use stage (i.e. production, transport, and waste processing and disposal of the lost products and materials).

End of Life Stage includes provision and all transports, provision of all materials, products and related energy and water use. It also includes any declared benefits and loads from net flows leaving the product system that have not been allocated as co-products and that have passed the end-of-waste state in the form of reuse, recovery and/or recycling potentials.

Power mix

The selection of LCA data for the electricity generation is in line with the PCR.

The products are manufactured in Kirkcaldy, United Kingdom. The GaBi 5 Hydropower, Wind-power and Biomass dataset for the United Kingdom have therefore been used (reference year 2008). The energy supplier is providing Forbo with a certificate every year.

CO₂-Certificates

No CO₂-certificates are considered in this study.

Life Cycle Inventory Analysis

The total primary energy for one square meter installed Marmoleum tile 2.0 mm and 2.5 mm are presented in table 3 and 4 with their specific energy resources.

Table 3: Primary energy for all life cycle stages for Marmoleum tile 2.0 mm for one year

Non-renewable primary energy by resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1 yr)	End of Life
Total non renewable primary energy	MJ	124.17	123.03	3.96	15.91	6.12	-24.85
Crude oil	MJ	37.30	25.48	3.65	6.87	0.72	0.58
Hard coal	MJ	7.20	6.76	0.01	0.31	1.09	-0.97
Lignite	MJ	4.71	4.26	0.01	0.37	0.68	-0.61



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Natural gas	MJ	67.62	79.54	0.28	8.14	1.89	-22.23
Uranium	MJ	7.33	6.98	0.01	0.22	1.72	-1.61
Renewable primary energy by resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1 yr)	End of Life
Total renewable primary energy	MJ	87.89	87.59	0.06	0.22	0.71	-0.66
Geothermal	MJ	0.03	0.03	0	0	0.02	-0.02
Hydro power	MJ	8.04	8.03	0	0	0.31	-0.31
Solar energy	MJ	74.56	74.37	0.05	0.11	0.18	-0.15
Wind power	MJ	5.26	5.16	0	0.09	0.20	-0.19

Table 4: Primary energy for all life cycle stages for Marmoleum tile 2.5 mm for one year

Nonrenewable primary energy by resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1 yr)	End of Life
Total non renewable primary energy	MJ	130.57	133.88	4.72	15.60	6.12	-29.75
Crude oil	MJ	42.65	30.02	4.35	6.87	0.72	0.69
Hard coal	MJ	7.89	7.66	0.01	0.30	1.09	-1.17
Lignite	MJ	5.26	4.95	0.01	0.36	0.68	-0.74
Natural gas	MJ	66.53	83.01	0.33	7.88	1.89	-26.58
Uranium	MJ	8.22	8.22	0.02	0.19	1.72	-1.94
Renewable primary energy by resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1 yr)	End of Life
Total renewable primary energy	MJ	97.26	97.10	0.07	0.18	0.71	-0.79
Geothermal	MJ	0.03	0.03	0	0	0.02	-0.02
Hydro power	MJ	8.10	8.16	0	-0.01	0.31	-0.37
Solar energy	MJ	83.79	83.62	0.06	0.10	0.18	-0.18
Wind power	MJ	5.33	5.27	0	0.09	0.20	-0.23

The renewable primary energy is mainly determined by the raw materials from renewable resources (linseed oil, jute hessian, tall oil).

The nonrenewable primary energy is mainly determined by the production stage for a one year usage; within the production stage the main contributors are the raw material production and energy generation. Installation is also a significant contributor due to the use of adhesive. Energy substitution in the End of Life stage results to a credit in the total nonrenewable primary energy.

Waste and non-renewable resource consumption

In the tables 5 and 6 the nonrenewable resource consumption and waste production are shown for all life cycle stages for a one year usage.

Table 5: Waste categories and nonrenewable resources for Marmoleum tile 2.0 mm (one year)

Wastes	Unit	Total Life cycle	Production	Transport	Installation	Use (1yr)	End of Life
Hazardous waste	[kg]	0	0	0	0	0	0
Non-hazardous waste	[kg]	8.18	7.54	0.01	0.76	1.11	-1.24
Radioactive waste	[kg]	2.77E-03	2.64E-03	5.30E-06	2.46E-04	7.03E-04	-8.23E-04
Resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1yr)	End of Life
Nonrenewable resources	[kg]	9.76	8.97	0.01	0.65	1.12	-1.00



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Table 6: Waste categories and non renewable resources for Marmoleum tile 2.5 mm (one year)

	Unit	Total Life cycle	Production	Transport	Installation	Use (1yr)	End of Life
Hazardous waste	[kg]	0	0	0	0	0	0
Non-hazardous waste	[kg]	9.10	8.67	0.01	0.76	1.11	-1.46
Radioactive waste	[kg]	3.10E-03	3.11E-03	6.31E-06	2.46E-04	7.03E-04	-9.66E-04
Resources	Unit	Total Life cycle	Production	Transport	Installation	Use (1yr)	End of Life
Nonrenewable resources	[kg]	10.90	10.33	0.01	0.64	1.12	-1.20

Life Cycle Assessment

In table 7 the environmental impacts for one lifecycle are presented for Marmoleum tile 2.0 and 2.5 mm. In the tables 8 and 9 the environmental impacts are presented for all the lifecycle stages.

Table 7: Results of the LCA – Environmental impacts one lifecycle (one year) – Marmoleum tile 2.0 mm & 2.5 mm

Impact Category : CML 2001 – Nov. 2010	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm	Unit
Global Warming Potential (GWP 100 years)	9.37	10.14	kg CO2-Equiv.
Ozone Layer Depletion Potential (ODP, steady state)	1.34E-07	1.55E-07	kg R11-Equiv.
Acidification Potential (AP)	5.70E-02	6.30E-02	kg SO2-Equiv.
Eutrophication Potential (EP)	1.18E-02	1.38E-02	kg Phosphate-Equiv.
Photochem. Ozone Creation Potential (POCP)	3.68E-03	4.21E-03	kg Ethene-Equiv.
Abiotic Depletion Potential Elements (ADPE)	3.10E-06	3.41E-06	kg Sb-Equiv.
Abiotic Depletion Potential Fossil (ADPF)	115.58	120.85	[MJ]

Table 8: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Impact Category : CML 2001 – Nov. 2010	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Global Warming Potential	kg CO2-Equiv.	3.98	0.48	1.46	0.36	3.86
Ozone Layer Depletion Potential	kg R11-Equiv.	1.57E-07	4.45E-10	-2.36E-09	1.97E-08	-1.96E-08
Acidification Potential	kg SO2-Equiv.	5.30E-02	8.29E-03	1.88E-03	1.29E-03	-1.47E-03
Eutrophication Potential	kg PSO4-Equiv.	1.25E-02	8.97E-04	2.50E-04	1.08E-04	6.80E-05
Photochem. Ozone Creation Potential	kg Ethene-Equiv.	3.92E-03	2.10E-04	2.54E-04	6.38E-05	-2.34E-04
Abiotic Depletion Elements	kg Sb-Equiv.	3.07E-06	1.19E-08	2.66E-07	5.90E-08	6.43E-09
Abiotic Depletion Fossil	MJ	124.39	4.76	15.38	4.34	-28.01

Table 9: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm (one year)

Impact Category : CML 2001 – Nov. 2010	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Global Warming Potential	kg CO2-Equiv.	3.95	0.40	1.43	0.36	3.23
Ozone Layer Depletion Potential	kg R11-Equiv.	1.32E-07	3.74E-10	-2.11E-09	1.97E-08	-1.63E-08
Acidification Potential	kg SO2-Equiv.	4.80E-02	6.96E-03	1.90E-03	1.29E-03	-1.22E-03
Eutrophication Potential	kg PSO4-Equiv.	1.06E-02	7.53E-04	2.50E-04	1.08E-04	5.74E-05
Photochem. Ozone Creation Potential	kg Ethene-Equiv.	3.38E-03	1.76E-04	2.57E-04	6.38E-05	-1.95E-04
Abiotic Depletion Elements	kg Sb-Equiv.	2.76E-06	9.99E-07	2.66E-07	5.90E-08	5.57E-09
Abiotic Depletion Fossil	MJ	115.00	3.99	15.66	4.34	-23.41

The relative contribution of each process stage to each impact category for Marmoleum tile 2.0 mm and 2.5 mm is shown in the figures 4 and 5.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Figure 4: relative contribution of each process stage to each impact category for Marmoleum tile 2.0 mm for a one year usage.





Figure 5: relative contribution of each process stage to each impact category for Marmoleum tile 2.5 mm for a one year usage.





FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Interpretation

The interpretation of the results has been carried out considering the assumptions and limitations declared in the EPD, both methodology- and data-related for a one year usage.

In all impact categories the production stage has the main contribution to the overall impact. For the categories ODP, AP, EP and ADPE the main contributor in the production stage is the Raw material supply with a share of 77-98% of total impacts from the production stage. For the categories POCP and ADPF the Raw material supply and the Manufacturing have an almost equal share in the production. For the GWP the production stage and the end of life are the main contributors with a total share of 77%. In the production stage the manufacturing of the tiles accounts for 92% of the impact during the production stage.

For GWP, POCP, ADPE and ADPF the adhesive for the flooring installation has a significant impact. The LCA for the installation is based on a conservative assumption of 435g/m² adhesive. In practice this amount will almost always be lower.

Forbo declares in the EPD a worldwide distribution by truck (951km) and container ship (4916 km). For this scenario the transport has a relevance of 4%-13% in the impact categories GWP, AP, EP and POCP.

The LCA profile for the results of ODP is different. After the production stage (77-79%) the use stage accounts for the main contribution to ODP (10-12%). For the production stage the raw materials are responsible for most of the impact (98%) while for the use stage the contribution is mainly due to the consumption of electricity (EU power grid mix) for cleaning. The third main impact on ODP comes from the End Of Life stage.

The LCA for GWP reflects the use of renewable raw materials for the production of Marmoleum tile (linseed oil). Carbon dioxide, a greenhouse gas, is locked in from the atmosphere in the course of the plant growth via photosynthesis and stored during the use stage. This carbon dioxide is not released until the end of life when it is incinerated with energy recovery – this process accounts for almost 40% of the emission of greenhouse gases in the life cycle of the product.

Energy recovery from incineration and the respective energy substitution at the end of life results in a credit for all impact categories as reported in the End of Life stage.

Additional Environmental Information

To be fully transparent Forbo Flooring does not only want to declare the environmental impacts required in the PCR, but also the impacts on human health and eco-toxicity. Furthermore the outcome of the calculations according to the European Standard EN15804 are published in this section.

Toxicity

For this calculations the USEtoxTM model is used as being the globally recommended preferred model for characterization modelling of human and eco-toxic impacts in LCIA by the United Nations Environment Programme SETAC Life Cycle Initiative.

According to the "ILCD Handbook: Recommendations for Life Cycle Impact Assessment in the European context" the recommended characterization models and associated characterization factors are classified according to their quality



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

into three levels:

- o Level I (recommended and satisfactory).
- o level II (recommended but in need of some improvements)
- o level III (recommended. but to be applied with caution).

A mixed classification sometimes is related to the application of the classified method to different types of substances. USEtox™ is classified as Level II / III, unlike for example the CML impact categories which are classified as Level I.

Table 10: Results of the LCA – Environmental impacts one lifecycle (one year) – Marmoleum tile 2.0 mm & 2.5 mm

Impact Category : USEtox	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm	Unit
Ecotoxicity	2.14E-03	2.31E-03	PAF m3.day
Human toxicity, cancer	3.16E-10	3.16E-10	Cases
Human toxicity, non-canc.	1.42E-10	1.43E-10	Cases

In the following two tables the impacts are subdivided into the lifecycle stages.

Table 11: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Impact Category : USEtox	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Ecotoxicity	PAF m3.day	1.93E-03	8.16E-05	4.79E-04	8.69E-05	-2.64E-04
Human toxicity, cancer	cases	4.03E-10	4.36E-13	1.52E-11	1.36E-11	-1.16E-10
Human toxicity, non-canc.	cases	2.57E-11	2.36E-13	1.18E-10	7.45E-13	-2.20E-12

Table 12: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm

Impact Category : USEtox	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Ecotoxicity	PAF m3.day	1.73E-03	6.85E-05	4.82E-04	8.69E-05	-2.21E-04
Human toxicity, cancer	cases	3.83E-10	3.66E-13	1.61E-11	1.36E-11	-9.69E-11
Human toxicity, non-canc.	cases	2.44E-11	1.98E-13	1.18E-10	7.45E-13	-1.83E-12

Interpretation

The interpretation of the results has been carried out considering the assumptions and limitations declared in the EPD, both methodology- and data-related for a one year usage.

The Eco-toxicity is predominated by the production stage in which the raw materials are having a big impact with a share of around 67-70%. The main contributors in the manufacturing are the thermal energy and electricity used. The other main contributor is the adhesive used for installing the floor

In the Human toxicity (cancer) a significant benefit is coming from the incineration of the Marmoleum tile as energy recovery (EU27 Thermal energy from natural gas). The largest contribution in this impact category is coming from the production stage in which the Manufacturing (Thermal energy and Electricity) is the main contributor with a share of 66-69% of the total production impact.

The adhesive used for the installation of Marmoleum tile has by far the biggest impact on the Human toxicity (non-canc.), this is calculated as a worst case and will in practice probably be lower.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

EN15804 Results

In this section the calculations have been conducted and verified according to the requirements of the European Standard EN 15804. In addition, calculations followed the document “Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report”, however, Part A was not included as a part of the verification.

Table 13: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
GWP	[kg CO ₂ -Equiv.]	3.98	0.47	1.23	0.36	0.01	0.09	6.36	-2.37
ODP	[kg CFC11-Equiv.]	1.57E-07	1.31E-10	1.94E-09	1.97E-08	9.57E-10	4.78E-12	2.12E-09	-2.70E-08
AP	[kg SO ₂ -Equiv.]	5.30E-02	8.27E-03	2.27E-03	1.29E-03	6.25E-05	3.56E-04	8.43E-04	-3.11E-03
EP	[kg PO ₄ ³⁻ -Equiv.]	1.25E-02	8.96E-04	2.65E-04	1.08E-04	3.35E-06	8.52E-05	2.61E-04	-2.97E-04
POCP	[kg Ethen Equiv.]	5.46E-03	3.00E-04	4.40E-04	9.51E-05	3.80E-06	-1.23E-04	1.11E-04	-3.74E-04
ADPE	[kg Sb Equiv.]	3.07E-06	1.15E-08	2.72E-07	5.90E-08	1.20E-09	4.07E-09	1.00E-07	-1.06E-07
ADPF	[MJ]	124.00	4.70	20.40	4.35	0.17	1.22	2.28	-36.70

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources

Table 14: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
GWP	[kg CO ₂ -Equiv.]	3.95	0.40	1.18	0.36	0.01	0.08	5.42	-2.02
ODP	[kg CFC11-Equiv.]	1.32E-07	1.10E-10	1.92E-09	1.97E-08	9.57E-10	4.05E-12	1.81E-09	-2.31E-08
AP	[kg SO ₂ -Equiv.]	4.80E-02	6.94E-03	2.26E-03	1.29E-03	6.25E-05	3.02E-04	7.18E-04	-2.66E-03
EP	[kg PO ₄ ³⁻ -Equiv.]	1.06E-02	7.52E-04	2.62E-04	1.08E-04	3.35E-06	7.23E-05	2.23E-04	-2.53E-04
POCP	[kg Ethen Equiv.]	4.71E-03	2.52E-04	4.40E-04	9.51E-05	3.80E-06	-1.04E-04	9.47E-05	-3.18E-04
ADPE	[kg Sb Equiv.]	2.76E-06	9.65E-09	2.71E-07	5.90E-08	1.20E-09	3.45E-09	8.55E-08	-9.01E-08
ADPF	[MJ]	115.00	3.94	20.40	4.35	0.17	1.04	1.94	-31.30

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources

Table 15: Results of the LCA – Resource use for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
PERE	[MJ]	58.03	-	-	-	-	-	-	-
PERM	[MJ]	39.07	-	-	-	-	-	-	-
PERT	[MJ]	97.10	0.07	0.36	0.71	0.04	0.05	0.01	-1.06
PENRE	[MJ]	117.25	-	-	-	-	-	-	-
PENRM	[MJ]	16.75	-	-	-	-	-	-	-
PENRT	[MJ]	134.00	4.72	21.00	6.12	0.26	1.23	2.58	-39.20
SM	[kg]	1.50	-	-	-	-	-	-	-
RSF	[MJ]	2.30E-03	3.13E-05	2.64E-04	3.40E-04	3.41E-06	1.04E-05	0.00E+00	-3.83E-04
NRSF	[MJ]	2.30E-02	3.29E-04	2.76E-03	3.56E-03	3.57E-05	1.09E-04	0.00E+00	-4.02E-03
FW	[kg]	5.82E+01	1.35E-01	3.85E+00	2.29E+00	1.14E-01	6.86E-02	-3.07E-02	-3.68E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Table 16: Results of the LCA – Resource use for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
PERE	[MJ]	56.30	-	-	-	-	-	-	-
PERM	[MJ]	31.30	-	-	-	-	-	-	-
PERT	[MJ]	87.60	0.0552	0.355	0.706	0.0374	0.0414	0.00803	-0.907
PENRE	[MJ]	109.59	-	-	-	-	-	-	-
PENRM	[MJ]	13.41	-	-	-	-	-	-	-
PENRT	[MJ]	123.00	3.96	21	6.12	0.256	1.04	2.2	-33.4
SM	[kg]	1.24	-	-	-	-	-	-	-
RSF	[MJ]	2.10E-03	2.63E-05	2.65E-04	3.40E-04	3.41E-06	8.81E-06	0.00E+00	-3.27E-04
NRSF	[MJ]	2.10E-02	2.76E-04	2.77E-03	3.56E-03	3.57E-05	9.24E-05	0.00E+00	-3.43E-03
FW	[kg]	5.57E+01	1.13E-01	3.85E+00	2.29E+00	1.14E-01	5.82E-02	-2.61E-02	-3.14E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water

Table 17: Results of the LCA – Output flows and Waste categories for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
HWD	[kg]	0	0	0	0	0	0	0	0
NHWD	[kg]	8.67	0.0125	0.762	1.11	0.0548	0.00649	0.0434	-1.56
RWD	[kg]	0.00311	0.00000631	0.000246	0.000703	0.0000366	0.00000174	0.0000258	-0.00103
CRU	[kg]	-	-	-	-	-	-	-	0
MFR	[kg]	-	-	-	-	-	-	-	0
MER	[kg]	-	-	-	-	-	-	-	3.30
EE Power	[MJ]	-	-	0.17	-	-	-	2.97	-
EE Thermal energy	[MJ]	-	-	1.87	-	-	-	32.20	-

HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier

Table 18: Results of the LCA – Output flows and Waste categories for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
HWD	[kg]	0	0	0	0	0	0	0	0
NHWD	[kg]	7.54	0.0105	0.762	1.11	0.0548	0.0055	0.037	-1.34
RWD	[kg]	0.00264	0.0000053	0.000246	0.000703	0.0000366	0.00000147	0.000022	-0.000883
CRU	[kg]	-	-	-	-	-	-	-	0
MFR	[kg]	-	-	-	-	-	-	-	0
MER	[kg]	-	-	-	-	-	-	-	2.71
EE Power	[MJ]	-	-	0.121	-	-	-	2.58	-
EE Thermal energy	[MJ]	-	-	1.31	-	-	-	27.9	-

HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier

Interpretation

The interpretation of the environmental impacts are similar to the interpretation on page 14. A more detailed interpretation is published in the appendix.



FLOORING SYSTEMS

Marmoleum tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

References

GABi 5 2012	PE INTERNATIONAL AG; GaBi 5: Software-System and Database for Life Cycle Engineering. Copyright. TM. Stuttgart. Echterdingen. 1992-2012.
GABi 5 2012D	GaBi 5: Documentation of GaBi 5: Software-System and Database for Life Cycle Engineering. Copyright. TM. Stuttgart. Echterdingen. 1992-2012. http://documentation.gabi-software.com/
NSF International May 22. 2012	Product Category Rule for Environmental Product Declarations
UL ENVIRONMENT ERFMI 2008	<i>Flooring: Carpet. Resilient. Laminate. Ceramic. Wood</i> UL Environment's Program Operator Rules Final report: LCA. Environmental Information Sheet and Ecodesign Model of Resilient Flooring by order of ERFMI. PE International. 2008
IBU 2011	PCR - Part A: Calculation rules for the Life Cycle Assessment and Requirements on the Background Report. Institut Bauen und Umwelt e.V.
PE 2012	Description of Selected Impact Categories. PE International AG. 2012
ILCD Handbook: General guide for Life Cycle Assessment - Detailed guidance	European Commission - Joint Research Centre - Institute for Environment and Sustainability: International Reference Life Cycle Data System (ILCD) Handbook - General guide for Life Cycle Assessment - Detailed guidance. First edition March 2010. EUR 24708 EN. Luxembourg. Publications Office of the European Union; 2010
STANDARDS AND LAWS	
DIN EN ISO 14044	Environmental management - Life cycle assessment - Requirements and guidelines (ISO 14044:2006); German and English version EN ISO 14044
ISO 14025 2006	DIN EN ISO 14025: Environmental labels and declarations — Type III environmental declarations — Principles and procedures
ISO 14040 2006	Environmental management - Life cycle assessment - Principles and framework (ISO 14040); German and English version EN ISO 14040
CEN/TR 15941	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data; German version CEN/TR 15941
EN 15804	EN 15804: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products
ISO 24011	Resilient floor coverings - Specification for plain and decorative linoleum
CPR	REGULATION (EU) No 305/2011 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC
EN-ISO 10874	Resilient. textile and laminate floor coverings - Classification

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Appendix

The following life cycle assessment study of the company Forbo Flooring, a manufacturer of resilient floor coverings, has been performed by Forbo Flooring under support of PE International and has been conducted according to the requirements of the European Standard /EN 15804/ following the document "Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report" /IBU 2011/.



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

LCA Report for Environmental Product Declarations (EPD)

Marmoleum Tile 2.0 and 2.5 mm



FLOORING SYSTEMS

Forbo Flooring

Title of the study:

Environmental product declarations of Marmoleum Tile 2.0 and 2.5 mm

Part of the project: Life Cycle assessment (LCA)

LCA study conducted by:

Forbo Flooring

Industrieweg 12

1566 JP Assendelft

The Netherlands

January 2013

Supported by:

PE INTERNATIONAL AG

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Authors:

Floris Zeitler, Forbo

Supported by Peter Shonfield, Julia Goerke

Forbo Nairn Ltd.

Fife KY1 2SB

P.O. Box 1, Kirkcaldy, United Kingdom

Tel. +31 (0) 75 6477477

Fax +31 (0) 75 6477707

E-mail floris.zeitler@forbo.com

Internet www.forbo-flooring.com

Supported by:

PE INTERNATIONAL AG

Hauptstraße 111 – 115

D – 70771 Leinfelden – Echterdingen

Tel. +49 (0) 711 34 18 17 – 0

Fax +49 (0) 711 34 18 17 – 25

E-mail info@pe-international.com

Internet www.pe-international.com

Nomenclature

Abbreviation	Explanation
ADP	Abiotic Depletion Potential
AP	Acidification Potential
BLBSB	Benefits and Loads Beyond the System Boundary
CRU	Components for re-use
EE	Exported energy per energy carrier
EP	Eutrophication Potential
EPD	Environmental Product Declaration
FW	Use of net fresh water
GWP	Global Warming Potential
HWD	Hazardous waste disposed
LCA	Life Cycle Assessment
MER	Materials for energy recovery
MFR	Materials for recycling
NRSF	Use of non-renewable secondary fuels
ODP	Ozone Layer Depletion Potential
PENRE	Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials
PENRM	Use of non-renewable primary energy resources used as raw materials
PENRT	Total use of non-renewable primary energy resources
PERE	Use of renewable primary energy excluding renewable primary energy resources used as raw materials
PERM	Use of renewable primary energy resources used as raw materials
PERT	Total use of renewable primary energy resources
PCR	Product Category Rules
POCP	Photochemical Ozone Creation Potential
RSF	Use of renewable secondary fuels
RSL	Reference Service Life
RWD	Radioactive waste disposed
SM	Use of secondary material



General

The present LCA study of the company Forbo Flooring, a manufacturer of resilient floor coverings, has been performed by Forbo Flooring under support of PE International and has been conducted according to the requirements of the European Standard following the document "Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report". The LCA report was sent to verification on 12/10/12

Scope

This document is the LCA report for the "Environmental Product Declaration" (EPD) of "Marmoleum tile 2.0 & 2.5 mm". The provision of an LCA report is required for each EPD of the EPD-program holder (UL Environment). This document shows how the calculation rules were applied and describes additional LCA information on the Life Cycle Assessment in accordance with the requirements of ISO 14040 series.

Content, structure and accessibility of the LCA report

The LCA report provides a systematic and comprehensive summary of the project documentation supporting the verification of an EPD. The report documents the information on which the Life Cycle Assessment is based, while also ensuring the additional information contained within the EPD complies with the requirements of ISO 14040 series. The LCA report contains all of the data and information of importance for the details published in the EPD. Care is given to all explanations as to how the data and information declared in the EPD arises from the Life Cycle Assessment. The verification of the EPD is aligned towards the structure of the rule document based on ISO 14025 and EN15804.

Goal of the study

The reason for performing this LCA study is to publish an EPD based on EN 15804 and ISO 14025. This study contains the calculation and interpretation of the LCA results for Marmoleum tile complying with EN-ISO 24011 in two different thicknesses:

- Marmoleum tile 2.5 mm
- Marmoleum tile 2.0 mm

Manufactured by:

Forbo Nairn Ltd.
Fife KY1 2SB
P.O. Box 1, Kirkcaldy
United Kingdom.

The following life cycle stages were considered:

- Product stage
- Transport stage
- Installation stage
- Use stage
- End-of-life stage
- Benefits and loads beyond the product system boundary

The main purpose of EPD is for use in business-to-business communication. As all EPD are publicly available on the website of UL Environment and therefore are accessible to the end consumer they can also be used in business-to-consumer communication.

The intended use of the EPD is to communicate environmentally related information and LCA results to support the assessment of the sustainable use of resources and of the impact of construction works on the environment

Scope of the study

Declared / functional unit

The declaration refers to the declared/functional unit of 1m² installed flooring product.

Declaration of construction products classes

The LCA report refers to a manufacturer declaration of type 1a): Declaration of a specific product from a manufacturer's plant. They are produced at the following manufacturing site:

Forbo Nairn Ltd.
Fife KY1 2SB
P.O. Box 1, Kirkcaldy
United Kingdom


Product Definition

Product Classification and description

This declaration covers a broad range of designs and colors. Marmoleum is a resilient floor covering complying with all the requirements of EN-ISO 24011: Specification for plain and decorative linoleum. Marmoleum is made from natural raw materials making it preferable ecological floor covering with a beautiful and colorful design. The key raw materials include linseed oil, which comes from the flax plant seeds, gum rosin from pine trees, recycled wood waste of wood from controlled forests and limestone. Because of the use of natural raw materials Marmoleum is biodegradable.

Linoleum is produced by Forbo Flooring for more than 150 years and our well known brand Marmoleum is sold worldwide. This declaration refers to Marmoleum sheet of 2.0 and 2.5 mm nominal thickness.

Marmoleum is build up in 3 layers as illustrated in the figure 1. These three layers form one homogeneous product by the cross linking bondings formed during the oxidative curing process :



1. **Surface layer:** This layer gives Marmoleum tile its design and color. After finishing the product at the trimming department a factory finish is applied to protect the surface layer.
2. **Intermediate layer:** This layer is calendared on the polyester backing.
3. **Backing:** The backing is a Polyester fleece.

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Range of application

Marmoleum tile is classified in accordance with EN-ISO 24011 to be installed in the following use areas defined in EN-ISO 10874:

Area of application	2.0 mm thickness	2.5 mm thickness
Domestic	Class 23 	Class 23 
Commercial	Class 32 	Class 34 
Industrial	Class 41 	Class 43 

Product Standard

The products considered in this EPD have the following technical specifications:

- o Meets or exceeds all technical requirements as set forth in ASTM F 2195 Standard Specification for Linoleum Floor Tile.
- o Compliant with CHPS 01350 requirements for VOC emissions and indoor air quality.
- o Meets or exceeds all technical requirements as set in EN-ISO 24011 Specification for plain and decorative Linoleum.



Marmoleum tile meets the requirements of EN 14041

EN 13501-1	Reaction to fire	C _{fl} - s1
EN 13893	Slip resistance	DS: ≥ 0.30
EN 1815	Body voltage	< 2 kV
EN 12524	Thermal conductivity	0.17 W/mK

Fire Testing:

- o Class 1 when tested in accordance with ASTM E 648/NFPA 253, Standard Test Method for Critical Radiant Flux.
- o Meets 450 or less when tested in accordance with ASTM E 662/NFPA 258, Standard Test Method for Smoke Density.
- o Class C when tested in accordance to ASTM E 84/NFPA 255, Standard Test Method for Surface Burning Characteristics.
- o FSC1-150; SD-160 when tested in accordance to CAN/ULC S102.2, Standard Test Method for Flame Spread Rating and Smoke Development.

Accreditation

- o ISO 9001 Quality Management System
- o ISO 14001 Environmental Management System
- o SMART
- o SWAN
- o Nature Plus
- o Good Environmental Choice Australia

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Delivery status

Characteristics	Nominal Value	Unit
Product thickness	2.5 2.0	mm mm
Product Weight 2.5 mm 2.0 mm	3000 2300	g/m ²
Tiles Width Length	333 or 500 333 or 500	mm mm

Material Content

Component	Material	Availability	Amount [%]	Origin
Binder	Linseed oil	Bio based crop	20	USA/Canada/Europe
	Gum rosin	Bio based crop	2	Indonesia/China
	Tall oil	Bio based waste product from paper Industry	6	USA
Filler	Wood flour	Bio based waste product from wood processing	31	Germany
	Calcium carbonate	Abundant mineral	8	Germany
	Reused Marmoleum tile		23	Internal
Pigment	Titanium dioxide	Limited mineral	3	Global
	Various other pigments	Limited mineral	1	Global
Backing	Polyester	Fossil limited	5	Europe
Finish	Lacquer	Fossil limited	1	Netherlands

Production of Main Materials

- **Linseed oil** : Linseed oil is obtained by pressing the seeds of the flax plant. After filtering a clear golden yellow liquid remains.
- **Gum rosin** : Rosin is obtained by wounding pine trees. The crude gum is collected and is separated into turpentine and rosin by distillation.
- **Tall oil** : Tall oil is a post industrial waste product coming from the paper industry and is consisting of vegetable oil and rosin.
- **Wood flour** : Post industrial bio based soft wood waste from the wood industry, which is milled into flour.
- **Calcium carbonate** : An abundant mineral found in all parts of the world as the chief substance in rocks (i.e., marble and limestone). It can be ground to varying particle sizes and is widely used as filler.
- **Reused Marmoleum tile** : Waste material coming from the Marmoleum tile production which is reused.
- **Titanium dioxide** : A white pigment produced from the mineral rutile, a naturally occurring form of titanium dioxide. The production of the pigment is a large-scale chemical process
- **Various other pigments** : The vast majority of the used color pigments are iron oxide based.
- **Polyester** : Polyester fibers woven into a fabric which is used as a substrate.
- **Lacquer** : The factory applied lacquer – Topshield 2 – is a waterborne UV cured urethane – acrylate hybrid dispersion.

Production of the Floor Covering




Figure 2: Illustration of the Production process

Marmoleum tile is produced in several stages starting with the oxidation of linseed oil mixed with tall oil and rosin. With the influence of oxygen from the atmosphere a tough sticky material is obtained called linoleum cement. The linoleum cement is stored in containers for a few days for further reaction and after this it is mixed with wood flour, calcium carbonate, reused waste (if applicable), titanium dioxide and pigments. This mixture is calendared on a polyester substrate and stored in drying rooms, to cure till the required hardness is reached. After approximately 14 days the material is taken out from the drying room to the trimming department where the factory finish is applied on the surface of the product and the end inspection is done. Finally the edges are trimmed and the sheet is cut to length into tiles of 333x333 or 500x500 millimeter. The trimmings and the rejected product are reused.

Health, Safety and Environmental Aspects during Production

- o ISO 14001 Environmental Management System

Production Waste

Rejected material and the cuttings of the trimming stage are being reused in the manufacturing process. Packaging materials are being collected separately and externally recycled.

Delivery and Installation of the Floor Covering

Delivery

A worldwide distribution by truck and container ship is considered. On average every square meter of Marmoleum tile is transported as follows:

- | | |
|--|---------|
| o Transport distance 40 t truck | 694 km |
| o Transport distance 7.5t truck (Fine distribution) | 257 km |
| o Capacity utilization trucks (including empty runs) | 85 % |
| o Transport distance Ocean ship | 4916 km |
| o Capacity utilization Ocean ship | 48% |

Installation

Because of the specific techniques used during the installation of Marmoleum tile 6% of the material is cut off as installation waste. For installation of Marmoleum tile on the floor a worst case scenario has been modeled (assuming 0.435 kg/m² of adhesive is required). In practice this amount will almost always be lower. Waste during the installation process may be recycled as floor covering through the manufacturers' facilities or thermally recycled in a waste incineration plant. Since the major part of Marmoleum tile is sold in Europe the European electricity grid mix is used in the calculations for the energy recovery during incineration.



Health, Safety and Environmental Aspects during Installation

Forbo flooring recommends using (low) zero emission adhesives for installing Marmoleum tile.

Waste

Waste during the installation process may be recycled as floor covering through the manufacturers' facilities or thermally recycled in a waste incineration plant. Since the major part of Marmoleum tile is sold in Europe the European electricity grid mix is used in the calculations for the energy recovery during incineration.

Packaging

Cardboard tubes, PE-film and wooden pallets can be collected separately and should be used in a local recycling process. In the calculation model 100% incineration is taken into account for which there is a credit received.

Use stage

The service lifetime of a floor covering for a certain application on a floor is too widespread to give one common number. For this EPD model the reference service lifetime (RSL) is set to one year. This means that all impacts for the use phase are based on the cleaning and maintenance model for one year. Depending on the area of use, the technical lifetime advised by the manufacturer and the estimated time on the floor by the customer, the service lifetime can be determined. The use phase impacts should be calculated with the foreseen service life to arrive at the total environmental impact.

Cleaning and Maintenance

Level of use	Cleaning Process	Cleaning Frequency	Consumption of energy and resources
Commercial/Residential/Industrial	Vacuuming	Twice a week	Electricity
	Damp mopping	Once a week	Hot water Neutral detergent

For the calculations the following cleaning regime is considered:

- Dry cleaning with a 1.5 kW vacuum cleaner for 0.21 min/m^2 , twice a week. This equates to $0.55 \text{ kWh/m}^2\text{year}$.
- Once a week wet cleaning with 0.062 l/m^2 water and 0.0008 kg/m^2 detergent. This results in the use of $3.224 \text{ l/m}^2\text{year}$ water and $0.04 \text{ kg/m}^2\text{year}$ detergent. The wet cleaning takes place without power machine usage. Waste water treatment of the arising waste water from cleaning is considered.

The cleaning regime that is recommended in practice will be highly dependent on the use of the premises where the floor covering is installed. In high traffic areas more frequent cleaning will be needed compared to areas where there is low traffic. The use of an entrance mat of at least four steps will reduce the cleaning frequency.

The cleaning regime used in the calculations is suitable for high traffic areas.

Prevention of Structural Damage

All newly laid floors should be covered and protected from with a suitable non-staining protective covering if other building activities are still in progress.

Use protective feet on chairs and tables to reduce scratching. Castor wheels should be suitable for resilient floor coverings

Health Aspects during Usage

Marmoleum tile is complying with:

- o AgBB requirements
- o French Act Grenelle: A+
- o CHPS section 01350

End of Life

The deconstruction of installed Marmoleum tile from the floor is done mechanically and the electrical energy needed for this is estimated to be 0.03 kWh/sqm. This amount of energy is taken into account for the calculations. For the end of life stage no landfilling is taken into account, since the vast majority of the countries in which Marmoleum tile is sold are having a non landfill policy. Because of the high calorific value of Marmoleum tile the incineration is very profitable as a waste to energy conversion.

Life Cycle Assessment

A full Life Cycle Assessment has been carried out according to ISO 14040 and ISO 14044.

The following Life Cycle Stages are assessed :

- o Production Stage (Raw material acquisition, transportation to Manufacturing and Manufacturing)
- o Transport Gate to User
- o Installation Stage
- o Use Stage
- o End of Life Stage




Figure 3 : Flow chart of the Life Cycle Assessment

Description of the declared Functional Unit

The functional unit is one square meter of installed product and the use stage is considered for one year of service life.

Cut off Criteria

The cut-off criteria shall be 1% of renewable and non-renewable primary energy usage and 1% of the total mass of the unit process. The total neglected input flows per module shall be a maximum of 5% of energy usage and mass.

In practice, in this assessment, all data from the production data acquisition are considered, i.e. all raw materials used as per formulation, use of water, electricity and other fuels, the required packaging materials, and all direct production waste. Transport data on all considered inputs and output material are also considered.

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

LCA Data

As a general rule, specific data derived from specific production processes or average data derived from specific production processes have been used as the first choice as a basis for calculating an EPD.

For life cycle modeling of the considered products, the GaBi 5 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG, has been used. All relevant LCA datasets are taken from the GaBi 5 software database. The datasets from the database GaBi are documented in the online documentation. To ensure comparability of results in the LCA, the basic data of GaBi database were used for energy, transportation and auxiliary materials.

Data Quality

The requirements for data quality and LCA data correspond to the specifications of the PCR.

Foreground data are based on 1 year averaged data (year 2011). The reference ages of LCA datasets vary but are given in the table in the Appendix. The time period over which inputs to and outputs from the system is accounted for is 100 years from the year for which the data set is deemed representative. The technological LCA of the collected data reflects the physical reality of the declared product. The datasets are complete, conform to the system boundaries and the criteria for the exclusion of inputs and outputs and are geographical representative for the supply chain of Forbo flooring.

For life cycle modeling of the considered products the GaBi 5 Software System for Life Cycle Engineering, developed by PE INTERNATIONAL AG, is used. All relevant LCA datasets are taken from the GaBi 5 software database. The last revision of the used data sets took place within the last 10 years.

Table 3: LCA datasets used in the LCA model

Data set	Region	Reference year
Linseed oil	Germany	2010
Limestone flour	Germany	2010
Tall oil	Europe	2010
Iron oxide	Germany	2010
Pigment	Germany	2007
Titanium dioxide	Europe	2010
Wood flour	Europe	2006
Colophony	France	2010
Polyester	Europe	2005
Urethane / acrylic hybrid dispersion	Europe	2005
Water (desalinated; deionised)	Germany	2010
Detergent (ammonia based)	Germany	2006
Adhesive for resilient flooring	Germany	2010
Waste incineration of linoleum	Europe	2006
Electricity from Hydro power	United Kingdom	2008
Electricity from Wind power	United Kingdom	2008
Electricity from Biomass	United Kingdom	2008
Power grid mix	Europe	2008
Thermal energy from natural gas	United Kingdom	2008
Thermal energy from natural gas	Europe	2008
Trucks	Global	2010
Municipal waste water treatment (Sludge incineration).	Germany	2010
Container ship	Global	2010
Diesel mix at refinery	Europe	2008
Heavy fuel oil at refinery (1.0wt.% S)	Europe	2008
Corrugated board	Europe	2002

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Wooden pallets	Germany	2006
Polyethylene film	Europe	2005

The documentation of the LCA data sets can be taken from the GaBi documentation.

System Boundaries

Production Stage includes provision of all materials, products and energy, packaging processing and its transport, as well as waste processing up to the end-of waste state or disposal of final residues during the product stage.

Transport and Installation Stage includes provision of all materials, products and energy, as well as waste processing up to the end-of-waste state or disposal of final residues during the construction stage. These information modules also include all impacts and aspects related to any losses during this construction stage (i.e. production, transport, and waste processing and disposal of the lost products and materials). For the transportation a worldwide distribution is considered.

Use Stage includes provision and transport of all materials, products and related energy and water use, as well as waste processing up to the end-of-waste state or disposal of final residues during this part of the use stage. These information modules also include all impacts and aspects related to the losses during this part of the use stage (i.e. production, transport, and waste processing and disposal of the lost products and materials).

End of Life Stage includes provision and all transports, provision of all materials, products and related energy and water use. It also includes any declared benefits and loads from net flows leaving the product system that have not been allocated as co-products and that have passed the end-of-waste state in the form of reuse, recovery and/or recycling potentials.

Power mix

The selection of LCA data for the electricity generation is in line with the PCR.

The products are manufactured in Kirkcaldy, United Kingdom. The GaBi 5 Hydropower, Wind-power and Biomass datasets for the United Kingdom have therefore been used (reference year 2008). The energy supplier is providing Forbo with a certificate every year.

CO₂-Certificates

No CO₂-certificates are considered in this study.

Allocations

In the present study some allocations have been made. Detailed explanations can be found in the chapters below.

Co-product allocation

No co-product allocation occurs in the product system.

Allocation of multi-Input processes

The Production and End of Life stage include incineration plants. In these processes different products are treated together within a process. The allocation procedures followed in these cases are based on a physical classification of the mass flows or calorific values.

Credits from energy substitution are allocated to the production stage, because the gained energy from energy substitution is lower than the energy input in this stage. The same quality of energy is considered.

Allocation procedure of reuse, recycling and recovery

The installation waste and end of life waste is fed into incineration processes. Incineration processes include cogeneration processes which give thermal and power energy as outputs. It is assumed that this recovered energy

offsets that produced by the European average grid mix and thermal energy generation from natural gas.

The LCA dataset used to model the incineration of Marmoleum tile is based on data developed by European Resilient Flooring Manufacturers' Institute (ERFMI) and is specific to linoleum flooring products. This indicates that 250 kWh/tonne electricity and 9744 MJ/tonne thermal energy is recovered during incineration. This model is part of the ERFMI 2008 LCA study on resilient floorings; critical reviewed by Dr ir Jeroen Guinée (Institute of Environmental Sciences CML).

Description of the allocation processes in the LCA report

The description of allocation rules in of this LCA report meets the requirements of the PCR.

Description of the unit processes in the LCA report

The modeling of the unit processes reported for the LCA are documented in a transparent way, respecting the confidentiality of the data present in the LCA report.

In the following tables the type and amount of the different input and output flows are listed for 1m² produced flooring; installed flooring includes the material loss during installation (6%):

Table 4: Composition of linoleum surface layer

Process data	Unit	Marmoleum tile (2.0 mm)	Marmoleum tile (2.5 mm)
Limestone flour	kg/m ²	0.1701	0.2051
Linseed oil	kg/m ²	0.4800	0.5689
Iron oxide (Fe ₂ O ₃)	kg/m ²	0.0050	0.0062
Pigment	kg/m ²	0.0020	0.0025
Colophony (rosin)	kg/m ²	0.0480	0.0590
Tall oil (Bio based waste product from paper Industry)	kg/m ²	0.1120	0.1370
Titanium dioxide	kg/m ²	0.0754	0.0754
Wood flour (Bio based waste product from wood processing)	kg/m ²	0.7200	0.8780

Table 5: Composition of linoleum intermediate layer (same for both products)

Process data	Unit	Marmoleum tile (2.0 mm)	Marmoleum tile (2.5 mm)
Limestone	kg/m ²	0.0367	0.0426
Linseed oil	kg/m ²	0.0438	0.0523
Iron oxide (Fe ₂ O ₃)	kg/m ²	0.0007	0.0008
Pigment	kg/m ²	0.0003	0.0003
Tall oil (Bio based waste product from paper Industry)	kg/m ²	0.0398	0.0475
Titanium dioxide	kg/m ²	0.0080	0.0095
Wood flour (Bio based waste product from wood processing)	kg/m ²	0.0708	0.0846
Linoleum for recycling	kg/m ²	0.6000	0.7125

Table 6: Composition of linoleum substrate layer (same for both products)

Process data	Unit	Marmoleum tile
Polyester	kg/m ²	0.150

Table 7: Composition of lacquer (same for both products)

Process data	Unit	Marmoleum tile
Urethane / acrylic hybride dispersion	kg/m ²	0.012
Water (desalinated; demonized)	kg/m ²	0.018

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Table 8: Production related inputs/outputs

Process data	Unit	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm
INPUTS			
Linoleum surface layer	kg	1.600	1.950
Linoleum intermediate layer	kg	0.800	0.950
Linoleum substrate layer	kg	0.150	0.150
Lacquer	kg	0.012	0.012
Electricity	MJ	12.911	12.911
Thermal energy from natural gas	MJ	52.13	52.13
OUTPUTS			
Marmoleum tile	kg	2.562	3.062
Waste	kg	0.705	0.844

Table 9: Packaging requirements (per m² manufactured product)

Process data	Unit	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm
Corrugated board boxes	kg	0.051	0.051
Wooden pallets	kg	0.042	0.042
PE film	kg	0.0004	0.0004

Table 10: Transport distances (same for both products)

Process data	Unit	Road	Truck size	Ship
Limestone flour	km	417	14 - 20t gross weight / 11,4t payload capacity	-
Linseed oil	km	212		6326
Iron oxide (Fe ₂ O ₃)	km	568		-
Pigment	km	372		-
Colophony (rosin)	km	246		15831
Tall oil	km	200		5260
Titanium dioxide	km	420		-
Wood flour	km	200		-
Polyester	km	263		-
Lacquer	km	225		655
Corrugated board boxes	km	150		-
PE film	km	145		-
Wooden pallets	km	123		-
Transport to construction site : -Transport distance 40 t truck	km	951 694	34 - 40 t gross weight / 27t payload capacity 7,5 t - 12t gross weight / 5t payload capacity	4916
-Transport distance 7.5t truck (Fine distribution)		257		
Waste transport to incineration	km	200	7,5 t - 12t gross weight / 5t payload capacity	-

Table 11: Inputs/outputs from Installation

Process data	Unit	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm
INPUTS			
Marmoleum tile	kg	2.562	3.062
Adhesive (30% water content)	kg	0.435	0.435
- Water			
- Acrylate co-polymer			

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

- Styrene Butadiene co-polymer			
- Limestone flour			
- Sand			
OUTPUTS			
Installed marmoleum tile	kg	2.408	2.878
Installation Waste	kg	0.154	0.184

Table 12: Inputs from use stage (per m².year of installed product)

Process data	Unit	Marmoleum tile
Detergent	kg/year	0.04
Electricity	kWh/year	0.55
Water	kg/year	3.224

Table 13: Disposal

Process data	Unit	Marmoleum tile
Post consumer Marmoleum tile to incineration	%	100

Life Cycle Inventory Analysis

In table 14 the environmental impacts for one lifecycle are presented for Marmoleum tile 2.0 and 2.5 mm. In the tables 15 and 16 the environmental impacts are presented for all the lifecycle stages.

Table 14: Results of the LCA – Environmental impacts one lifecycle (one year) – Marmoleum tile 2.0 mm & 2.5 mm

Impact Category : CML 2001 – Nov. 2010	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm	Unit
Global Warming Potential (GWP 100 years)	9.37	10.14	kg CO2-Equiv.
Ozone Layer Depletion Potential (ODP. steady state)	1.34E-07	1.55E-07	kg R11-Equiv.
Acidification Potential (AP)	5.70E-02	6.30E-02	kg SO2-Equiv.
Eutrophication Potential (EP)	1.18E-02	1.38E-02	kg Phosphate-Equiv.
Photochem. Ozone Creation Potential (POCP)	3.68E-03	4.21E-03	kg Ethene-Equiv.
Abiotic Depletion Potential Elements (ADPE)	3.10E-06	3.41E-06	kg Sb-Equiv.
Abiotic Depletion Potential Fossil (ADPF)	115.58	120.85	[MJ]

Table 15: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Impact Category : CML 2001 – Nov. 2010	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Global Warming Potential	kg CO2-Equiv.	3.98	0.48	1.46	0.36	3.86
Ozone Layer Depletion Potential	kg R11-Equiv.	1.57E-07	4.45E-10	-2.36E-09	1.97E-08	-1.96E-08
Acidification Potential	kg SO2-Equiv.	5.30E-02	8.29E-03	1.88E-03	1.29E-03	-1.47E-03
Eutrophication Potential	kg PSO4-Equiv.	1.25E-02	8.97E-04	2.50E-04	1.08E-04	6.80E-05
Photochem. Ozone Creation Potential	kg Ethene-Equiv.	3.92E-03	2.10E-04	2.54E-04	6.38E-05	-2.34E-04
Abiotic Depletion Elements	kg Sb-Equiv.	3.07E-06	1.19E-08	2.66E-07	5.90E-08	6.43E-09
Abiotic Depletion Fossil	MJ	124.39	4.76	15.38	4.34	-28.01

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering


According to ISO 14025 & EN 15804

Table 9: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm (one year)

Impact Category : CML 2001 – Nov. 2010	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Global Warming Potential	kg CO2-Equiv.	3.95	0.40	1.43	0.36	3.23
Ozone Layer Depletion Potential	kg R11-Equiv.	1.32E-07	3.74E-10	-2.11E-09	1.97E-08	-1.63E-08
Acidification Potential	kg SO2-Equiv.	4.80E-02	6.96E-03	1.90E-03	1.29E-03	-1.22E-03
Eutrophication Potential	kg PSO4-Equiv.	1.06E-02	7.53E-04	2.50E-04	1.08E-04	5.74E-05
Photochem. Ozone Creation Potential	kg Ethene-Equiv.	3.38E-03	1.76E-04	2.57E-04	6.38E-05	-1.95E-04
Abiotic Depletion Elements	kg Sb-Equiv.	2.76E-06	9.99E-07	2.66E-07	5.90E-08	5.57E-09
Abiotic Depletion Fossil	MJ	115.00	3.99	15.66	4.34	-23.41

The relative contribution of each process stage to each impact category for Marmoleum tile 2.0 mm and 2.5 mm is shown in the figures 4 and 5.

Figure 4: relative contribution of each process stage to each impact category for Marmoleum tile 2.0 mm for a one year usage.



ENVIRONMENTAL PRODUCT DECLARATION




FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Figure 5: relative contribution of each process stage to each impact category for Marmoleum tile 2.5 mm for a one year usage.



Interpretation

The interpretation of the results has been carried out considering the assumptions and limitations declared in the EPD, both methodology- and data-related for a one year usage.

In all impact categories the production stage has the main contribution to the overall impact. For the categories ODP, AP, EP and ADPE the main contributor in the production stage is the Raw material supply with a share of 77-98% of total impacts from the production stage. For the categories POCP and ADPF the Raw material supply and the Manufacturing have an almost equal share in the production. For the GWP the production stage and the end of life are the main contributors with a total share of 77%. In the production stage the manufacturing of the tiles accounts for ± 92% of the impact during the production stage.

For GWP, POCP, ADPE and ADPF the adhesive for the flooring installation has a significant impact. The LCA for the installation is based on a conservative assumption of 435g/m² adhesive. In practice this amount will almost always be lower.

Forbo declares in the EPD a worldwide distribution by truck (951km) and container ship (4916 km). For this scenario the transport has a relevance of 4%-13% in the impact categories GWP, AP, EP and POCP.

The LCA profile for the results of ODP is different. After the production stage (77-79%) the use stage accounts for the main contribution to ODP (10-12%). For the production stage the raw materials are responsible for most of the impact (98%) while for the use stage the contribution is mainly due to the consumption of electricity (EU power grid mix) for cleaning. The third main impact on ODP comes from the End Of Life stage.

The LCA for GWP reflects the use of renewable raw materials for the production of Marmoleum tile (linseed oil). Carbon dioxide, a greenhouse gas, is locked in from the atmosphere in the course of the plant growth via photosynthesis and stored during the use stage. This carbon dioxide is not released until the end of life when it is incinerated with energy recovery – this process accounts for almost 40% of the emission of greenhouse gases in the life cycle of the product.

Environment



Energy recovery from incineration and the respective energy substitution at the end of life results in a credit for all impact categories as reported in the End of Life stage.

Additional Environmental Information

To be fully transparent Forbo Flooring does not only want to declare the environmental impacts required in the PCR, but also the impacts on human health and eco-toxicity. Furthermore the outcome of the calculations according to the European Standard EN15804 are published in this section.

Toxicity

For this calculations the USEtoxTM model is used as being the globally recommended preferred model for characterization modelling of human and eco-toxic impacts in LCIA by the United Nations Environment Programme SETAC Life Cycle Initiative.

According to the "ILCD Handbook: Recommendations for Life Cycle Impact Assessment in the European context" the recommended characterization models and associated characterization factors are classified according to their quality into three levels:

- o Level I (recommended and satisfactory),
- o level II (recommended but in need of some improvements)
- o level III (recommended, but to be applied with caution).

A mixed classification sometimes is related to the application of the classified method to different types of substances.

USEtoxTM is classified as Level II / III, unlike for example the CML impact categories which are classified as Level I.

Table 17: Results of the LCA – Environmental impacts one lifecycle (one year) – Marmoleum tile 2.0 mm & 2.5 mm

Impact Category : USEtox	Marmoleum tile 2.0 mm	Marmoleum tile 2.5 mm	Unit
Ecotoxicity	2.14E-03	2.31E-03	PAF m3.day
Human toxicity, cancer	3.16E-10	3.16E-10	Cases
Human toxicity, non-canc.	1.42E-10	1.43E-10	Cases

In the following two tables the impacts are subdivided into the lifecycle stages.

Table 18: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Impact Category : USEtox	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Ecotoxicity	PAF m3.day	1.93E-03	8.16E-05	4.79E-04	8.69E-05	-2.64E-04
Human toxicity, cancer	cases	4.03E-10	4.36E-13	1.52E-11	1.36E-11	-1.16E-10
Human toxicity, non-canc.	cases	2.57E-11	2.36E-13	1.18E-10	7.45E-13	-2.20E-12

Table 19: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm

Impact Category : USEtox	Unit	Production	Transport	Installation	Use (1yr)	End of Life
Ecotoxicity	PAF m3.day	1.73E-03	6.85E-05	4.82E-04	8.69E-05	-2.21E-04
Human toxicity, cancer	cases	3.83E-10	3.66E-13	1.61E-11	1.36E-11	-9.69E-11
Human toxicity, non-canc.	cases	2.44E-11	1.98E-13	1.18E-10	7.45E-13	-1.83E-12

Interpretation

The interpretation of the results has been carried out considering the assumptions and limitations declared in the EPD, both methodology- and data-related for a one year usage.

The Eco-toxicity is predominated by the production stage in which the raw materials are having a big impact with a share of around 67-70%. The main contributors in the manufacturing are the thermal energy and electricity used.

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

The other main contributor is the adhesive used for installing the floor

In the Human toxicity (cancer) a significant benefit is coming from the incineration of the Marmoleum tile as energy recovery (EU27 Thermal energy from natural gas). The largest contribution in this impact category is coming from the production stage in which the Manufacturing (Thermal energy and Electricity) is the main contributor with a share of 66-69% of the total production impact.

The adhesive used for the installation of Marmoleum tile has by far the biggest impact on the Human toxicity (non-canc.), this is calculated as a worst case and will in practice probably be lower.

EN15804 results

In this section the calculations have been conducted according to the requirements of the European Standard EN 158024 following the document "Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report".

Table 20: Results of the LCA – Environmental impact for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
GWP	[kg CO ₂ -Equiv.]	3.98	0.47	1.23	0.36	0.01	0.09	6.36	-2.37
ODP	[kg CFC11-Equiv.]	1.57E-07	1.31E-10	1.94E-09	1.97E-08	9.57E-10	4.78E-12	2.12E-09	-2.70E-08
AP	[kg SO ₂ -Equiv.]	5.30E-02	8.27E-03	2.27E-03	1.29E-03	6.25E-05	3.56E-04	8.43E-04	-3.11E-03
EP	[kg PO ₄ ³⁻ -Equiv.]	1.25E-02	8.96E-04	2.65E-04	1.08E-04	3.35E-06	8.52E-05	2.61E-04	-2.97E-04
POCP	[kg Ethen Equiv.]	5.46E-03	3.00E-04	4.40E-04	9.51E-05	3.80E-06	-1.23E-04	1.11E-04	-3.74E-04
ADPE	[kg Sb Equiv.]	3.07E-06	1.15E-08	2.72E-07	5.90E-08	1.20E-09	4.07E-09	1.00E-07	-1.06E-07
ADPF	[MJ]	124.00	4.70	20.40	4.35	0.17	1.22	2.28	-36.70
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources								

Table 21: Results of the LCA – Environmental impact for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
GWP	[kg CO ₂ -Equiv.]	3.95	0.40	1.18	0.36	0.01	0.08	5.42	-2.02
ODP	[kg CFC11-Equiv.]	1.32E-07	1.10E-10	1.92E-09	1.97E-08	9.57E-10	4.05E-12	1.81E-09	-2.31E-08
AP	[kg SO ₂ -Equiv.]	4.80E-02	6.94E-03	2.26E-03	1.29E-03	6.25E-05	3.02E-04	7.18E-04	-2.66E-03
EP	[kg PO ₄ ³⁻ -Equiv.]	1.06E-02	7.52E-04	2.62E-04	1.08E-04	3.35E-06	7.23E-05	2.23E-04	-2.53E-04
POCP	[kg Ethen Equiv.]	4.71E-03	2.52E-04	4.40E-04	9.51E-05	3.80E-06	-1.04E-04	9.47E-05	-3.18E-04
ADPE	[kg Sb Equiv.]	2.76E-06	9.65E-09	2.71E-07	5.90E-08	1.20E-09	3.45E-09	8.55E-08	-9.01E-08
ADPF	[MJ]	115.00	3.94	20.40	4.35	0.17	1.04	1.94	-31.30
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources								

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Table 22: Results of the LCA – Resource use for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
PERE	[MJ]	58.03	-	-	-	-	-	-	-
PERM	[MJ]	39.07	-	-	-	-	-	-	-
PERT	[MJ]	97.10	0.07	0.36	0.71	0.04	0.05	0.01	-1.06
PENRE	[MJ]	117.25	-	-	-	-	-	-	-
PENRM	[MJ]	16.75	-	-	-	-	-	-	-
PENRT	[MJ]	134.00	4.72	21.00	6.12	0.26	1.23	2.58	-39.20
SM	[kg]	1.50	-	-	-	-	-	-	-
RSF	[MJ]	2.30E-03	3.13E-05	2.64E-04	3.40E-04	3.41E-06	1.04E-05	0.00E+00	-3.83E-04
NRSF	[MJ]	2.30E-02	3.29E-04	2.76E-03	3.56E-03	3.57E-05	1.09E-04	0.00E+00	-4.02E-03
FW	[kg]	5.82E+01	1.35E-01	3.85E+00	2.29E+00	1.14E-01	6.86E-02	-3.07E-02	-3.68E+00
Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water								

Table 23: Results of the LCA – Resource use for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
PERE	[MJ]	56.30	-	-	-	-	-	-	-
PERM	[MJ]	31.30	-	-	-	-	-	-	-
PERT	[MJ]	87.60	0.0552	0.355	0.706	0.0374	0.0414	0.00803	-0.907
PENRE	[MJ]	109.59	-	-	-	-	-	-	-
PENRM	[MJ]	13.41	-	-	-	-	-	-	-
PENRT	[MJ]	123.00	3.96	21	6.12	0.256	1.04	2.2	-33.4
SM	[kg]	1.24	-	-	-	-	-	-	-
RSF	[MJ]	2.10E-03	2.63E-05	2.65E-04	3.40E-04	3.41E-06	8.81E-06	0.00E+00	-3.27E-04
NRSF	[MJ]	2.10E-02	2.76E-04	2.77E-03	3.56E-03	3.57E-05	9.24E-05	0.00E+00	-3.43E-03
FW	[kg]	5.57E+01	1.13E-01	3.85E+00	2.29E+00	1.14E-01	5.82E-02	-2.61E-02	-3.14E+00
Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water								

Table 24: Results of the LCA – Output flows and Waste categories for Marmoleum tile 2.5 mm (one year)

Parameter	Unit	Manufacturing	Installation		Use	End of Life			Credits
		A1-3	A4	A5	B2	C1	C2	C3	D
HWD	[kg]	0	0	0	0	0	0	0	0
NHWD	[kg]	8.67	0.0125	0.762	1.11	0.0548	0.00649	0.0434	-1.56
RWD	[kg]	0.00311	0.00000631	0.000246	0.000703	0.0000366	0.00000174	0.0000258	-0.00103
CRU	[kg]	-	-	-	-	-	-	-	0
MFR	[kg]	-	-	-	-	-	-	-	0
MER	[kg]	-	-	-	-	-	-	-	3.30
EE Power	[MJ]	-	-	0.17	-	-	-	2.97	-
EE Thermal energy	[MJ]	-	-	1.87	-	-	-	32.20	-
Caption	HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier								

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804


Table 25: Results of the LCA – Output flows and Waste categories for Marmoleum tile 2.0 mm (one year)

Parameter	Unit	Manufacturing	Installation			Use		End of Life			Credits
		A1-3	A4	A5		B2	C1	C2	C3	D	
HWD	[kg]	0	0	0		0	0	0	0	0	0
NHWD	[kg]	7.54	0.0105	0.762		1.11	0.0548	0.0055	0.037	-1.34	
RWD	[kg]	0.00264	0.0000053	0.000246		0.000703	0.0000366	0.00000147	0.000022	-0.000883	
CRU	[kg]	-	-	-		-	-	-	-	0	
MFR	[kg]	-	-	-		-	-	-	-	0	
MER	[kg]	-	-	-		-	-	-	-	2.71	
EE Power	[MJ]	-	-	0.121		-	-	-	2.58	-	
EE Thermal energy	[MJ]	-	-	1.31		-	-	-	27.9	-	
Caption	HWD = Hazardous waste disposed; NHWD = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier										

Interpretation

The interpretation of the environmental impacts calculated according to EN 15804 are similar to the interpretation on the earlier pages. A more detailed interpretation for a one year usage is presented in following figures and tables.

Figure 6: relative contribution of each process stage to each impact category for Marmoleum tile 2.5 mm for a one year usage.



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Table 26: Main modules and flows contributing to the total impact in each impact category for Marmoleum tile 2.5 mm for a one year usage

Impact Category	Stage	Module		Main contributor	Main contributing flows
GWP	Production	Raw Material Extraction	0.03 kg CO ₂ -equiv.	Linseed oil (-2.22 kg CO ₂ eq.) Titanium dioxide (0.47 kg CO ₂ eq.) Polyester (1.6 kg CO ₂ -eq.)	Production : Renewable resources, Carbon dioxide Production : Inorganic emissions to air, Carbon dioxide
		Transport of Raw materials	0.21 kg CO ₂ -equiv.	Means of transport (truck, container ship) and their fuels	
		Manufacturing	3.78 kg CO ₂ -equiv.	91% Thermal energy (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, Carbon dioxide
	Installation	Installation		67% Adhesive	
	Use	Use		74% Electricity 26% Detergent and waste water treatment	Use : Inorganic emissions to air, Carbon dioxide
	EOL	EOL		Incineration of post consumer linoleum flooring Energy substitution from incineration	EOL : Inorganic emissions to air, Carbon dioxide
ODP	Production	Raw Material Extraction	98%	3% Tall oil 4% Titanium dioxide 84% Polyester	Production : Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)
		Transport of Raw materials	< 0.01%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	2%	87% Pallet and card packaging	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Halogenated organic emissions to air, R114 (Dichlorotetrafluor-ethane)
	Installation	Installation		94% Adhesive	
	Use	Use		89% Electricity 11% Detergent and waste water treatment	Use : Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)
	EOL	EOL		Energy substitution from incineration	EOL: Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)
AP	Production	Raw Material Extraction	77%	45% Linseed oil 41% Titanium dioxide 9% Polyester	Production : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide Production : inorganic emissions to fresh water, Hydrogen chloride
		Transport of Raw materials	8%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	15%	20% Thermal energy (GB) 78% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
	Installation	Installation		97% Adhesive	
	Use	Use		89% Electricity 11% Detergent and waste water treatment	Use : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
	EOL	EOL		Incineration of post consumer linoleum flooring Energy substitution from incineration	EOL : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
EP	Production	Raw Material Extraction	87%	91% Linseed oil	Production : Inorganic emissions to air, Ammonia, NO _x Production : Inorganic emissions to fresh water, Nitrate, Nitrogen organic bounded, Phosphate
		Transport of Raw materials	4%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	9%	27% Thermal energy (GB) 70% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, NO _x Transport & Installation : Inorganic emissions to fresh water : Ammonium, Ammonia
	Installation	Installation		92% Adhesive	
	Use	Use		58% Electricity	Use : Inorganic emissions to air, NO _x

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

				42% Detergent and waste water treatment	Use : Inorganic emissions to fresh water, Phosphorus
	EOL	EOL		Incineration of post consumer linoleum flooring Energy substitution from incineration	EOL : Inorganic emissions to air, NO _x , Ammonia
POCP	Production	Raw Material Extraction	50%	33% Linseed oil 23% Titanium dioxide 37% Polyester	Production : Inorganic emissions to air, Carbon monoxide, NO _x , Sulphur dioxide Production : Group NMVOC to air, VOC (unspecified)
		Transport of Raw materials	1%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	49%	63% Thermal energy (GB) 36% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, Carbon monoxide, Sulphur dioxide Transport & Installation : Group NMVOC to air, NMVOC (unspecified)
	Installation	Installation		100% Adhesive	
	Use	Use		73% electricity 27% Detergent and waste water treatment	Use : Inorganic emissions to air, Sulphur dioxide, NO _x Use : Group NMVOC to air, NMVOC (unspecified)
	EOL	EOL		Energy substitution from incineration	EOL : Inorganic emissions to air, Carbon monoxide , NO _x , Sulphur dioxide EOL : Group NMVOC to air, NMVOC (unspecified) , Methane
ADPe	Production	Raw Material Extraction	92%	23% Tall oil 41% Titanium dioxide	Production : Non renewable elements, Chromium, Copper, Lead, Phosphorus Production : Non renewable resources, Sodium chloride (Rock salt)
		Transport of Raw materials	<0,3%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	8%	79% Electricity (GB) 14% Thermal energy (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Non renewable resources, Sodium chloride (Rock salt) Transport & Installation : Non renewable elements, Lead
	Installation	Installation		98% Adhesive	
	Use	Use		37% Electricity 63% Detergent and waste water treatment	Use : Non renewable resources, Sodium chloride (Rock salt) Use : Non renewable elements, Chromium, Copper
	EOL	EOL		Incineration of post consumer linoleum flooring Energy substitution from incineration	EOI : Non renewable resources, Magnesium Chloride leach (40%), Sodium chloride (Rock salt) EOL : Non renewable elements, Chromium, Copper, Lead
ADPf	Production	Raw Material Extraction	49%	31% Linseed oil 42% Polyester 9% Titanium dioxide	Production : Crude oil resource, Crude oil (in MJ) Production : Hard coal resource, hard coal (in MJ) Production : Natural gas (resource), Natural gas (in MJ)
		Transport of Raw materials	2%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	49%	94% Thermal energy	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Crude oil resource, Transport & Installation : Natural gas (resource),
	Installation	Installation		99% Adhesive	
	Use	Use		70% electricity 30% Detergent and waste water treatment	Use : Hard coal resource, hard coal (in MJ) Use : Natural gas resource, Natural gas (in MJ)
	EOL	EOL		Energy substitution from incineration	EOL : Natural gas (resource), Natural gas (in MJ)
Ecotoxicity	Production	Raw Material Extraction	70%	44% Linseed oil 31% Polyester 14% Titanium dioxide	Production : Group NMVOC to air, Acetic acid, Formaldehyde (Methanal)
		Transport of Raw materials	2%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	28%	64% Thermal energy (GB) 32% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & installation : Group NMVOC to air, Formaldehyde (Methanal), Acetic acid

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

	Installation	Installation		99% Adhesive	
	Use	Use		63% Detergent and waste water treatment 37% Electricity	Use : Hydrocarbons to fresh water, Phenol, Methanol Use : Group NMVOC to air, Formaldehyde (Methanal), Acetic acid
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, Formaldehyde (Methanal), Acetic acid
Human toxicity, cancer	Production	Raw Material Extraction	34%	16% Linseed oil 52% Polyester 9% Tall oil 13% Titanium dioxide	Production : Group NMVOC to air, Formaldehyde (Methanal)
		Transport of Raw materials	< 0.1%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	66%	60% Thermal energy (GB) 40% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Group NMVOC to air, Formaldehyde (Methanal)
	Installation	Installation		97% adhesive	
	Use	Use		82% Electricity	Use : Group NMVOC to air, Formaldehyde (Methanal)
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, Formaldehyde (Methanal)
Human toxicity, non canc.	Production	Raw Material Extraction	43%	28% Lacquer (Polymethylmethacrylate) 24% Polyester 28% Linseed oil	Production : Group NMVOC to air, NMVOC (unspecified), Methyl Methacrylate (MMA), Hexane (Isomers), Xylene (Dimethylbenzene)
		Transport of Raw materials	< 0.5%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	57%	18% Thermal energy (GB) 82% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Group NMVOC to air, Hexane, Methyl Methacrylate (MMA)
	Installation	Installation		100% adhesive	
	Use	Use		73% electricity 25% detergent	Use : Group NMVOC to air, Xylene, Formaldehyde
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, Formaldehyde (Methanal), Benzene, Xylene

ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

Figure 7: Relative contribution of each process stage to each impact category for Marmoleum tile 2.0 mm for a one year usage.




Table 27: Relevant modules and flows contributing to the impact in each impact category for Marmoleum tile 2.0 mm for a one year usage

Impact Category	Stage	Module		Main contributor	Main contributing flows
GWP	Production	Raw material extraction	0.09 kg CO ₂ -equiv.	Linseed oil (-1.86 kg CO ₂ eq.) Titanium dioxide (0.46kg CO ₂ eq.) Polyester (1.34 kg CO ₂ eq.)	Production : Renewable resources, Carbon dioxide Production : Inorganic emissions to air, Carbon dioxide
		Transport of Raw material	0.18 kg CO ₂ -equiv.	Means of transport (truck, container ship) and their fuels	
		Manufacturing	3.72 kg CO ₂ -equiv.	92% Thermal energy	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, Carbon dioxide
	Installation	Installation		70% adhesive 30% Impact from Incineration of installation waste and packaging	
	Use	Use		74% Electricity 26% detergent and waste water treatment	Use : Inorganic emissions to air, Carbon dioxide
	EOL	EOL		Energy substitution from incineration	EOL : Inorganic emissions to air, Carbon dioxide
ODP	Production	Raw Material Extraction	98%	84% Polyester	Production : Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)
		Transport of Raw materials	<0,1%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	2%	Wooden pallets and cardboard boxes production	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Halogenated organic emissions to air, Halon (1301)
	Installation	Installation		95% Adhesive	
	Use	Use		89% Electricity 11% detergent and waste water treatment	Use : Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

	EOL	EOL		Energy substitution from incineration	EOL: Halogenated organic emissions to air, R114 (Dichlorotetrafluorethane)
AP	Production	Raw Material Extraction	77%	42% Linseed oil 45% Titanium dioxide	Production : Inorganic emissions to air, Hydrogen chloride, NO _x , Sulphur dioxide Production : inorganic emissions to fresh water, Hydrogen chloride
		Transport of Raw materials	7%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	16%	20% Thermal energy (GB) 79% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
	Installation	Installation		98% Adhesive	
	Use	Use		89% Electricity (EU27) 11% detergent and waste water treatment	Use : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
	EOL	EOL		Incineration of post consumer linoleum flooring Energy substitution from incineration	EOL : Inorganic emissions to air, Ammonia, NO _x , Sulphur dioxide
EP	Production	Raw Material Extraction	86%	92% Linseed oil	Production : Inorganic emissions to air, Ammonia, NO _x Production : Inorganic emissions to fresh water, Nitrate, Nitrogen organic bounded, Phosphate
		Transport of Raw materials	4%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	10%	28% Thermal energy (GB) 70% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, NO _x
	Installation	Installation		94% Adhesive	
	Use	Use		60% electricity (EU27) 40% detergent and waste water	Use : Inorganic emissions to air, NO _x
	EOL	EOL		Truck and diesel to incineration plant Incineration of post consumer linoleum flooring Energy substitution from incineration	EOL : Inorganic emissions to air, NO _x
POCP	Production	Raw Material Extraction	51%	32% Linseed oil 26% Titanium dioxide 36% Polyester	Production : Inorganic emissions to air, Carbon monoxide, NO _x , Sulphur dioxide Production: Group NMVOC to air, NMVOC (unspecified), VOC (unspecified)
		Transport of Raw materials	1%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	48%	60% Thermal energy (GB) 40% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Inorganic emissions to air, NO _x Transport & Installation : Group NMVOC to air, NMVOC (unspecified)
	Installation	Installation		100% Adhesive	
	Use	Use		73% electricity (EU27) 27% detergent and waste water	Use : Inorganic emissions to air, Sulphur dioxide
	EOL	EOL		Energy substitution from incineration	EOL : Inorganic emissions to air, Carbon monoxide, NO _x , Sulphur dioxide EOL : Group NMVOC to air, NMVOC (unspecified), Methane
ADPe	Production	Raw Material Extraction	91%	22% Tall oil 46% Titanium dioxide	Production : Non renewable elements, Chromium, Copper Production : Non renewable resources, Sodium chloride (Rock salt), Colemanite ore, Gypsum (natural gypsum)
		Transport of Raw materials	< 0.1	Means of transport (truck, container ship) and their fuels	
		Manufacturing	9%	94% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Non renewable resources, Sodium chloride (Rock salt)
	Installation	Installation		98% Adhesive	
	Use	Use		38% Electricity 62% detergent and waste water	Use : Non renewable resources, Sodium chloride (Rock salt) Use : Non renewable elements, Chromium, Copper

Environment



ENVIRONMENTAL PRODUCT DECLARATION



FLOORING SYSTEMS

Marmoleum Tile 2.0 and 2.5 mm
Resilient Linoleum Floor Covering

According to ISO 14025 & EN 15804

	EOL	EOL		Energy substitution from incineration	EOL : Non renewable elements, Chromium, Copper, Lead
ADPf	Production	Raw Material Extraction	40%	34% Linseed oil 36% Polyester 13% Titanium dioxide	Production : Crude oil resource, Crude oil (in MJ) Production : Hard coal resource, hard coal (in MJ) Production : Natural gas (resource), Natural gas (in MJ)
		Transport of Raw materials	2%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	58%	95% Thermal energy (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Crude oil resource, Transport & Installation: Natural gas (resource),
	Installation	Installation		100% Adhesive	
	Use	Use		76% electricity 24% detergent and waste water	Use : Hard coal resource, hard coal (in MJ), Natural gas (in MJ)
	EOL	EOL		Energy substitution from incineration	EOL : Natural gas (resource), Natural gas (in MJ)
Ecotoxicity	Production	Raw Material Extraction	67%	43% Linseed oil 30% Polyester 17% Titanium dioxide	Production : Hydrocarbons to fresh water, Methanol, Phenol Production : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
		Transport of Raw materials	2%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	31%	65% Thermal energy (GB) 32% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & installation : Group NMVOC to air, Formaldehyde (Methanal)
	Installation	Installation		99% Adhesive	
	Use	Use		63% Detergent and waste water treatment 37% Electricity	Use : Group NMVOC to air, NMVOC (unspecified), formaldehyde (Methanal)
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
Human toxicity, cancer	Production	Raw Material Extraction	31%	16% Linseed oil 51% Polyester 15% Titanium dioxide	Production : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
		Transport of Raw materials	< 0.1%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	69%	60% Thermal energy (GB) 40% Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
	Installation	Installation		97% adhesive	
	Use	Use		82% Electricity	Use : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal)
Human toxicity, non canc.	Production	Raw Material Extraction	40%	32% Lacquer (Polymethylmethacrylate) 22% Polyester 26% Linseed oil	Production : Group NMVOC to air, NMVOC (unspecified), Methyl Methacrylate (MMA)
		Transport of Raw materials	< 0.5%	Means of transport (truck, container ship) and their fuels	
		Manufacturing	60%	18% Thermal energy (GB) 82 Electricity (GB)	
	Transport	Transport Gate to User		Means of transport (truck, container ship) and their fuels	Transport & Installation : Group NMVOC to air, NMVOC (unspecified), Hexane, Methyl Methacrylate (MMA)
	Installation	Installation		100% adhesive	
	Use	Use		73% electricity 27% detergent and waste water treatment	Use : Group NMVOC to air, Formaldehyde (methanal), Xylene (dimethyl benzene)
	EOL	EOL		Energy substitution from incineration	EOL : Group NMVOC to air, NMVOC (unspecified), Formaldehyde (Methanal), Xylene (dimethyl benzene)

Environment





Description of Selected Impact Categories

Abiotic Depletion Potential

The abiotic depletion potential covers all natural resources such as metal containing ores, crude oil and mineral raw materials. Abiotic resources include all raw materials from non-living resources that are non-renewable. This impact category describes the reduction of the global amount of non-renewable raw materials. Non-renewable means a time frame of at least 500 years. This impact category covers an evaluation of the availability of natural elements in general, as well as the availability of fossil energy carriers.

ADP (elements) describes the quantity of non-energetic resources directly withdrawn from the geosphere. It reflects the scarcity of the materials in the geosphere and is expressed in Antimony equivalents. The characterization factors are published by the CML, Oers 2010.

Are fossil energy carriers included in the impact category, it is ADP (fossil). Fossil fuels are used similarly to the primary energy consumption; the unit is therefore also MJ. In contrast to the primary fossil energy ADP fossil does not contain uranium, because this does not count as a fossil fuel.

Primary energy consumption

Primary energy demand is often difficult to determine due to the various types of energy source. Primary energy demand is the quantity of energy directly withdrawn from the hydrosphere, atmosphere or geosphere or energy source without any anthropogenic change. For fossil fuels and uranium, this would be the amount of resource withdrawn expressed in its energy equivalent (i.e. the energy content of the raw material). For renewable resources, the energy-characterised amount of biomass consumed would be described. For hydropower, it would be based on the amount of energy that is gained from the change in the potential energy of water (i.e. from the height difference). As aggregated values, the following primary energies are designated:

The total “**Primary energy consumption non-renewable**”, given in MJ, essentially characterises the gain from the energy sources natural gas, crude oil, lignite, coal and uranium. Natural gas and crude oil will both be used for energy production and as material constituents e.g. in plastics. Coal will primarily be used for energy production. Uranium will only be used for electricity production in nuclear power stations.

The total “**Primary energy consumption renewable**”, given in MJ, is generally accounted separately and comprises hydropower, wind power, solar energy and biomass. It is important that the end energy (e.g. 1 kWh of electricity) and the primary energy used are not miscalculated with each other; otherwise the efficiency for production or supply of the end energy will not be accounted for. The energy content of the manufactured products will be considered as feedstock energy content. It will be characterised by the net calorific value of the product. It represents the still usable energy content.

Waste categories

There are various different qualities of waste. For example, waste can be classed according to German and European waste directives. The modelling principles have changed with the last GaBi4 database update in October 2006. Now all LCA data sets (electricity generation, raw material etc.) already contain the treatment of the waste with very low waste output at the end of the stage. So the amount of waste is predominantly caused by foreground processes during the production phase. This is important for the interpretation of waste amounts.

From a balancing point of view, it makes sense to divide waste into three categories. The categories overburden/tailings, industrial waste for municipal disposal and hazardous waste will be used.

Overburden / tailings in kg: This category consists of the layer which must be removed in order to access raw material extraction, ash and other raw material extraction conditional materials for disposal. Also included in this category are tailings such as inert rock, slag, red mud etc.

Industrial waste for municipal disposal in kg: This term contains the aggregated values of industrial waste for municipal waste according to 3. AbfVwV TA SiedlABf.

Hazardous waste in kg: This category includes materials that will be treated in a hazardous waste incinerator or hazardous waste landfill, such as painting sludges, galvanic sludges, filter dusts or other solid or liquid hazardous waste and radioactive waste from the operation of nuclear power plants and fuel rod production.

Global Warming Potential (GWP)

The mechanism of the greenhouse effect can be observed on a small scale, as the name suggests, in a greenhouse. These effects are also occurring on a global scale. The occurring short-wave radiation from the sun comes into contact with the earth's surface and is partly absorbed (leading to direct warming) and partly reflected as infrared radiation. The reflected part is absorbed by so-called greenhouse gases in the troposphere and is re-radiated in all directions, including back to earth. This results in a warming effect on the earth's surface.

In addition to the natural mechanism, the greenhouse effect is enhanced by human activities. Greenhouse gases that are considered to be caused, or increased, anthropogenically are, for example, carbon dioxide, methane and CFCs. *Figure A1* shows the main processes of the anthropogenic greenhouse effect. An analysis of the greenhouse effect should consider the possible long term global effects.

The global warming potential is calculated in carbon dioxide equivalents ($\text{CO}_2\text{-Eq.}$). This means that the greenhouse potential of an emission is given in relation to CO_2 . Since the residence time of the gases in the atmosphere is incorporated into the calculation, a time range for the assessment must also be specified. A period of 100 years is customary.




Figure A1: Greenhouse effect (KREISSIG 1999)

Acidification Potential (AP)

The acidification of soils and waters predominantly occurs through the transformation of air pollutants into acids. This leads to a decrease in the pH-value of rainwater and fog from 5.6 to 4 and below. Sulphur dioxide and nitrogen oxide and their respective acids (H_2SO_4 and HNO_3) produce relevant contributions. This damages ecosystems, whereby forest dieback is the most well-known impact.

Acidification has direct and indirect damaging effects (such as nutrients being elutriated from soils or an increased solubility of metals into soils). But even buildings and building materials can be damaged. Examples include metals and natural stones which are corroded or disintegrated at an increased rate.

When analysing acidification, it should be considered that although it is a global problem, the regional effects of acidification can vary. *Figure A2* displays the primary impact pathways of acidification.

The acidification potential is given in sulphur dioxide equivalents (SO₂-Eq.). The acidification potential is described as the ability of certain substances to build and release H⁺ - ions. Certain emissions can also be considered to have an acidification potential, if the given S-, N- and halogen atoms are set in proportion to the molecular mass of the emission. The reference substance is sulphur dioxide.




Figure A2: Acidification Potential (KREISSIG 1999)

Eutrophication Potential (EP)

Eutrophication is the enrichment of nutrients in a certain place. Eutrophication can be aquatic or terrestrial. Air pollutants, waste water and fertilization in agriculture all contribute to eutrophication.

The result in water is an accelerated algae growth, which in turn, prevents sunlight from reaching the lower depths. This leads to a decrease in photosynthesis and less oxygen production. In addition, oxygen is needed for the decomposition of dead algae. Both effects cause a decreased oxygen concentration in the water, which can eventually lead to fish dying and to anaerobic decomposition (decomposition without the presence of oxygen). Hydrogen sulphide and methane are thereby produced. This can lead, among others, to the destruction of the ecosystem.

On eutrophicated soils, an increased susceptibility of plants to diseases and pests is often observed, as is a degradation of plant stability. If the nitrification level exceeds the amounts of nitrogen necessary for a maximum harvest, it can lead to an enrichment of nitrate. This can cause, by means of leaching, increased nitrate content in groundwater. Nitrate also ends up in drinking water.

Nitrate at low levels is harmless from a toxicological point of view. However, nitrite, a reaction product of nitrate, is toxic to humans. The causes of eutrophication are displayed in Figure A3. The eutrophication potential is calculated in phosphate equivalents (PO₄-Eq). As with acidification potential, it's important to remember that the effects of eutrophication potential differ regionally.




Figure A3: Eutrophication Potential (KREISSIG 1999)

Photochemical Ozone Creation Potential (POCP)

Despite playing a protective role in the stratosphere, at ground-level ozone is classified as a damaging trace gas. Photochemical ozone production in the troposphere, also known as summer smog, is suspected to damage vegetation and material. High concentrations of ozone are toxic to humans.

Radiation from the sun and the presence of nitrogen oxides and hydrocarbons incur complex chemical reactions, producing aggressive reaction products, one of which is ozone. Nitrogen oxides alone do not cause high ozone concentration levels. Hydrocarbon emissions occur from incomplete combustion, in conjunction with petrol (storage, turnover, refuelling etc.) or from solvents. High concentrations of ozone arise when the temperature is high, humidity is low, when air is relatively static and when there are high concentrations of hydrocarbons. Today it is assumed that the existence of NO and CO reduces the accumulated ozone to NO₂, CO₂ and O₂. This means, that high concentrations of ozone do not often occur near hydrocarbon emission sources. Higher ozone concentrations more commonly arise in areas of clean air, such as forests, where there is less NO and CO (Figure A4).

In Life Cycle Assessments, photochemical ozone creation potential (POCP) is referred to in ethylene-equivalents (C₂H₄-Equiv.). When analyzing, it's important to remember that the actual ozone concentration is strongly influenced by the weather and by the characteristics of the local conditions.




Figure A4: Photochemical Ozone Creation Potential

Ozone Depletion Potential (ODP)

Ozone is created in the stratosphere by the disassociation of oxygen atoms that are exposed to short-wave UV-light. This leads to the formation of the so-called ozone layer in the stratosphere (15 - 50 km high). About 10 % of this ozone reaches the troposphere through mixing processes. In spite of its minimal concentration, the ozone layer is essential for life on earth. Ozone absorbs the short-wave UV-radiation and releases it in longer wavelengths. As a result, only a small part of the UV-radiation reaches the earth.

Anthropogenic emissions deplete ozone. This is well-known from reports on the hole in the ozone layer. The hole is currently confined to the region above Antarctica, however another ozone depletion can be identified, albeit not to the same extent, over the mid-latitudes (e.g. Europe). The substances which have a depleting effect on the ozone can essentially be divided into two groups; the fluorine-chlorine-hydrocarbons (CFCs) and the nitrogen oxides (NOX). Figure A5 depicts the procedure of ozone depletion.

One effect of ozone depletion is the warming of the earth's surface. The sensitivity of humans, animals and plants to UV-B and UV-A radiation is of particular importance. Possible effects are changes in growth or a decrease in harvest crops (disruption of photosynthesis), indications of tumors (skin cancer and eye diseases) and decrease of sea plankton, which would strongly affect the food chain. In calculating the ozone depletion potential, the anthropogenically released halogenated hydrocarbons, which can destroy many ozone molecules, are recorded first. The so-called Ozone Depletion Potential (ODP) results from the calculation of the potential of different ozone relevant substances.

This is done by calculating, first of all, a scenario for a fixed quantity of emissions of a CFC reference (CFC 11). This results in an equilibrium state of total ozone reduction. The same scenario is considered for each substance under study whereby CFC 11 is replaced by the quantity of the substance. This leads to the ozone depletion potential for each respective substance, which is given in CFC 11 equivalents. An evaluation of the ozone depletion potential should take the long term, global and partly irreversible effects into consideration.




Figure A5: Ozone Depletion Potential (KREISSIG 1999)

References

GABI 5 2012	PE INTERNATIONAL AG; GaBi 5: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2012.
GABI 5 2012D	GaBi 5: Documentation of GaBi 5: Software-System and Database for Life Cycle Engineering. Copyright, TM. Stuttgart, Echterdingen, 1992-2012. http://documentation.gabi-software.com/
NSF International May 22, 2012	Product Category Rule for Environmental Product Declarations <i>Flooring: Carpet, Resilient, Laminate, Ceramic, Wood</i>
UL ENVIRONMENT ERFMI 2008	UL Environment's Program Operator Rules Final report: LCA, Environmental Information Sheet and Ecodesign Model of Resilient Flooring by order of ERFMI, PE International, 2008
IBU 2011	PCR - Part A: Calculation rules for the Life Cycle Assessment and Requirements on the Background Report, Institut Bauen und Umwelt e.V.
PE 2012	Description of Selected Impact Categories, PE International AG, 2012
ILCD Handbook: General guide for Life Cycle Assessment - Detailed guidance	European Commission - Joint Research Centre - Institute for Environment and Sustainability: International Reference Life Cycle Data System (ILCD) Handbook - General guide for Life Cycle Assessment - Detailed guidance. First edition March 2010. EUR 24708 EN. Luxembourg. Publications Office of the European Union; 2010
STANDARDS AND LAWS	
DIN EN ISO 14044	Environmental management - Life cycle assessment - Requirements and guidelines (ISO 14044:2006); German and English version EN ISO 14044
ISO 14025 2006	DIN EN ISO 14025: Environmental labels and declarations — Type III environmental declarations — Principles and procedures
ISO 14040 2006	Environmental management - Life cycle assessment - Principles and framework (ISO 14040); German and English version EN ISO 14040
CEN/TR 15941	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data; German version CEN/TR 15941
EN 15804	EN 15804: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products
ISO 24011	Resilient floor coverings - Specification for plain and decorative linoleum
CPR	REGULATION (EU) No 305/2011 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC
EN-ISO 10874	Resilient, textile and laminate floor coverings - Classification