
















Technical specifications

Flotex Edge meets the requirements of EN 1307





	Total Thickness	ISO 1765	5.0mm
	Total Weight	ISO 8543	2.85kg/m ²
	Commercial Use	EN-ISO 10874	Class 33 (Heavy)
	Tile Size	-	50 x 50 cm
	Quantity of tiles per box	-	12 (3m ²)
	Dimensional stability	ISO 2551 / EN986	<0.1%
	Castor Chair	ISO 4918	r ≥ 2.4 continuous use - Pass
	Impact Sound Reduction	EN ISO 717-2	≥ 21dB
	Sound Absorption	EN ISO 354	Sound Absorption = 0.10
	Fire Classification	EN13501-1	B _s s1, L, CS
	Light Fastness	EN-ISO 105-B02	≥ 5
	Water Impermeability	EN 1307 annex G	Pass
	Abrasion test	EN 1307 Annex F	> 1000 cycles
	Creating better environments		
	Renewable electricity	Flotex is manufactured using 100% electricity made from renewable sources	
	Recycled content	Flotex sheet contains up to 20% recycled content by weight	
	Indoor air quality	Flotex is approved by Allergy UK. All Flotex products are tested for indoor air emissions in accordance with EN 16516 after 3 days and 28 days.	

EN 14041



1200203-DOP-908

Flotex meets the requirements of EN 14041

	Reaction to fire	EN 13501	B _s s1, L, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2kV
	Thermal Resistance	EN 12667	0.055m ² .K/W

