

# eurocol

# 849

the strong connection

21-9-2026



## EUROTAPE U

Seam Tape, universal, very high tensile strength.

### PRODUCT TYPING

|             |                                            |
|-------------|--------------------------------------------|
| Base        | Two-layer polyester-fibre-based non-woven. |
| Color       | White                                      |
| Consistency | Non-woven.                                 |

- High-quality, tear-resistant polyester non-woven fabric tape for bonding artificial turf coverings in the seam area, in combination with Eurocol artificial turf adhesives
- Two-layer version.
- Universal application.
- Can be glued on one side.

### PROPERTIES

|                  |                             |
|------------------|-----------------------------|
| Weight           | 170 g/m <sup>2</sup>        |
| Frost resistance | Yes.                        |
| Special quality  | Very high tensile strength. |

### APPLICATION

Underlay for bonding artificial grass in the seam area.

### PROCESSING

|                 |                                           |
|-----------------|-------------------------------------------|
| Layer thickness | 0,43 mm                                   |
| Storage         | Store cool and dry in unopened packaging. |
| Shelf Life      | Minimum 72 Months, in unopened packaging. |

*\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Substrate:

Instruction manual:

- The individual sheets of artificial turf are laid next to each other with butt joints.
- The edges of the seams are partially turned over and the Eurocol seam tape is laid out in the middle of the web edge joint.
- The reactive Eurocol synthetic turf adhesive is applied to the Eurocol Seam Tape and then the covering is laid and rolled on.

### ENVIRONMENT AND HEALTH

849 EUROTAPE U

---

**ITEM DATA**

---

| artikel | productname | packaging           | shipping unit |
|---------|-------------|---------------------|---------------|
| 849     | Eurotape U  | roll à 100 m, 30 cm | 60/pallet     |

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG144502, Version 03, Stand 2019-04-25, ersetzt Ausgabe vom 2018-04-25.

**849 EUROTAPÉ U**