eurocol

886

EUROSEAL FINISHER

Ready-to-use, biodegradable finishing fluid for easy smooth finishing of various sealants based on silicone, epoxy, silane (MS) and PU. In a handy spray bottle



Soap and water.		
Transparent.		
ral		
1.03 kg/l.		
y spray bottle for easy smooth finishing of various sealants based on silicone, epoxy, silane (MS) and PU.		
Dry and frost-free in closed packaging at a temperature between + 5° and +25 °C		
Minimum 24 months		
From +5° to +40 °C		

* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- Finishing fluid facilitates the smooth finishing of freshly applied sealant joints, also known as wet smoothing.
- If in doubt about the applications, set up a preliminary test area or contact our Technical Advice department.

Instruction manual:

- Apply the sealant evenly with a hand or air pressure sealant gun.
- Shake the 886 Euroseal Finisher before use.
- Then finish the sealant within 10 min. (to prevent skin formation) tightly and smoothly using 886 Euroseal Finisher. Use this in combination with a moistened sealant spatula/knife or bevelled PVC pipe.
- After finishing the sealant joints tightly, rinse the entire surface thoroughly with clean water to remove excess residues of finishing fluid

886 EUROSEAL FINISHER



ENVIRONMENT AND HEALTH

MSDS For detailed safety and environmental information, please refer to our website www.eurocol.nl.

ITEM DATA

Article	Definition	Packaging	EAN-code
886	Euroseal Finisher	500 ml spray bottle	8 710345 886017
886	Euroseal Finisher	12 pieces per box	8 710345 886000

886 EUROSEAL FINISHER

