

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this adhesive.	
2. Designation		
3. Application		
4. Name and contact address manufacturer		
5. Name and contact address authorized		
6. System of assessment and verification of constancy of performance	3	
7. Activity of the notified certification body as required by the harmonized standard		
8. European Technical Assessment		
9. Declared performance		
Essential characteristics	Performance	Test method
Initial adhesive strength	$\geq 1 \text{ N/mm}^2$	NEN-EN 1324:2008 §7.2
Heat exposure	$\geq 1 \text{ N/mm}^2$	NEN-EN 1324:2008 §7.4
Open time 20 minutes	$\geq 0.5 \text{ N/mm}^2$	NEN-EN 1346:2008
Material behaviour in case of fire	Class E	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Optional characteristics	Performance	Test method
Increased sagging resistance	$\leq 0.5 \text{ mm}$	NEN-EN 1308:2008
Adhesive strength after water exposure	$\geq 0.5 \text{ N/mm}^2$	NEN-EN 1324:2008 §7.3
Increased temperature	$\geq 1 \text{ N/mm}^2$	NEN-EN 1324:2008 §7.5
Extended open time 30 minutes	$\geq 0.5 \text{ N/mm}^2$	NEN-EN 1346:2008
This declaration of performance was drafted in accordance with Annex ZA of NEN-EN 12004:2007+A1:2012;		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 22-08-2013 signed: ing. T.W. Breeuwer; Manager R&D 