

Page 1/9

Revision: 22.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: 683 Fibrecoat

· Article number: 683

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / preparation Moisture insulation

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271600 - Fax +31 75 6283564 E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

Contains 1,2-benzisothiazol-3(2H)-one, mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Primer based on acrylate copolymer dispersion.

(Contd. on page 2)

Printing date 22.11.2022 Version number 4 (replaces version 3) Revision: 22.11.2022

Trade name: 683 Fibrecoat

	(Contd. of	page 1
Dangerous components:		
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<1%
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ♠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ♠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<1%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Not applicable.
- · After skin contact: Wash with water and soap.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a physician.

- · After swallowing: Rinse mouth with water and then drink plenty of water, consult physician immediately.
- Information for doctor: Product is weak alkaline and after drying hardly soluble in water.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Dilute with plenty of water.

(Contd. on page 3)

Version number 4 (replaces version 3) Revision: 22.11.2022 Printing date 22.11.2022

Trade name: 683 Fibrecoat

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Collect product in waste container. Rinse floor with water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

No dangerous substances are released.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special measures required.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool, but frost-proof location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Recommended storage temperature between 15 and 25 ℃.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs				
2634-33-5	1,2-benzisothiazol-3(2H)-one			
Dermal	DNEL long term	0.966 mg/kg KG/d (wrk)		
	DNEL short term systemic health problems	0.345 mg/kg/d (Consumer)		
Inhalative	DNEL Inhalative long terme	1.2 /mg/m³ (Consumer)		
	DNEL	6.81 mg/m³ (wrk)		
55965-84-	55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)			
Oral	DNEL	0.09 mg/kg (Consumer)		
Inhalative	DNEL Inhalative long terme	0.02 /mg/m³ (Consumer)		
·PNECs				
2634-33-5	1,2-benzisothiazol-3(2H)-one			
PNEC	4.99 μg/kg (Sea Water Sediment)			
	49.9 μg/kg (Fresh Water Sediment)			
PNEC ug/	0.403 μg/l (Sea Water)			
	4.03 μg/l (Fresh Water)			
		(Contd. on page 4		

(Contd. on page 4)

Printing date 22.11.2022 Version number 4 (replaces version 3) Revision: 22.11.2022

Trade name: 683 Fibrecoat

(Contd. of page 3)

PNEC mg/kg | 3 mg/kg (Soil)

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

PNEC mg/kg | 0.01 mg/kg (Soil)

0.027 mg/kg (Sea Water Sediment) 0.027 mg/kg (Fresh Water Sediment)

- · Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Not required.
- Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

Material of gloves

Suitable chemical-resistant gloves (EN 374) even with longer direct contact (recommendation: protection index 6, corresponding> 480 minutes permeation time (permeation) according to EN 374) e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and others. Due to several factors that can influence (e.g. temperature), it must be taken into account that the service life of a chemical glove can in practice be considerably shorter than the permeation time indicated by the test.

- Penetration time of glove material
- > 480 Minutes.

The exact break through time has to be established by the manufacturer of the protective gloves and has to be observed.

· For prolonged contact gloves made of the following materials are suitable:

Chloroprene and butylrubber.

Nitrile rubber

· Eye/face protection Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: Purple

Odour: CharacteristicOdour threshold: Not determined.

• Melting point/freezing point: Undetermined.

(Contd. on page 5)

Printing date 22.11.2022 Version number 4 (replaces version 3) Revision: 22.11.2022

Trade name: 683 Fibrecoat

	(Contd. of page
Boiling point or initial boiling point and boiling	
range	100 ℃
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
· Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20 ℃	8
· Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	80,000 mPas
Solubility	
· water:	Not determined.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.4 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
• •	Not determined.
9.2 Other information	
Appearance:	
Form:	Paste
Important information on protection of health and	d
environment, and on safety.	
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	,
Organic solvents:	0.0 %
VOC(EC%)	0.0 %
Change in condition	0.0 /0
Evaporation rate	Not determined.
<u> </u>	
Information with regard to physical hazar	d
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
	V 17117

(Contd. on page 6)

Printing date 22.11.2022 Version number 4 (replaces version 3) Revision: 22.11.2022

Trade name: 683 Fibrecoat

(Contd. of page 5)

· Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
 Desensitised explosives 	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

		64-66 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rat)

- · Skin corrosion/irritation Possible irritation with prolonged or frequent contact.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/3h 13 mg/l (Not specified)

(Contd. on page 7)

Printing date 22.11.2022

Version number 4 (replaces version 3)

Trade name: 683 Fibrecoat

(Contd. of page 6)

Revision: 22.11.2022

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50/96h | 0.28 mg/l (LM) 0.188 mg/l (OM) EC50/48 h | 0.126 mg/l (DM)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Warm water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	

(Contd. on page 8)

Printing date 22.11.2022 Version number 4 (replaces version 3) Revision: 22.11.2022

Trade name: 683 Fibrecoat

(Contd. of page 7)

	(conta. or page 1)	
· 14.7 Maritime transport in bulk according to IMO		
instruments	Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D department
- · Contact: Ing. T.W. Breeuwer
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

(Contd. on page 9)

Printing date 22.11.2022

Version number 4 (replaces version 3)

Trade name: 683 Fibrecoat

(Contd. of page 8)

Revision: 22.11.2022

Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

·* Data compared to the previous version altered.

CR