

Technical specifications

Coral meets the requirements of EN 1307

		Coral Classic (47xx)		Coral Classic tile (47xx)	Coral Classic FR (47xx)	
Total thickness		Approx. 9 mm		Approx. 9 mm	Approx. 8 mm	
Area of use		33, commercial heavy		33, commercial heavy	33, commercial heavy	
Colours						
Available sizes (all sizes are approx.)		Rolls	Mats	Tiles	Rolls	Mats
		105cm	55 x 90 cm	50x50cm	185cm (FR)	No mats
All sizes are including edge		155cm	90 x 155 cm	3m ² , 12 tiles in a box. 28 boxes on a pallet 110x110cm	Roll lengths approx. 27.5m	
Rolls FR have no edges		205cm	135 x 205 cm			
		Roll lengths approx. 27,5m	205 x 300 cm			
Colour fastness ratings:						
Light	EN ISO 105/B02	7-8		7-8	7-8	
Rubbing	EN ISO 105/X12	4,5		4,5	4,5	
Water	EN ISO 105/E01	4,5		4,5	4,5	
Seawater	EN ISO 105/E02	4,5		4,5	4,5	
Waterstains	EN 1307 annex G	4,5		4,5	4,5	
Shampoo	BS 1006	4,5		4,5	4,5	
Organic solvents	EN ISO 105/X05	4,5		4,5	4,5	
Manufacturing method/type		Tufted, 5/32' cut-pile		Tufted, 5/32' cut-pile	Tufted, 5/32' cut-pile	
Designs		Multi coloured designed/coloured		Multi coloured designed/coloured	Multi coloured designed/coloured	
Pile material		100% polyamide-BCF solution dyed		100% polyamide-BCF solution dyed	100% polyamide-BCF solution dyed	
Tuft base		Non-woven polyester		Non-woven polyester	Non-woven polyester	
Backing		EVERFORT vinyl		EVERFORT Vinyl tile	FR-latex	
Total weight	ISO 8543	Approx. 4000 gram/m ²		Approx. 4700 gram/m ²	Approx. 3400 gram/m ²	
Pile installation weight	ISO 8543	Approx. 870 gram/m ²		Approx. 870 gram/m ²	Approx. 870 gram/m ²	
Pile thickness	ISO 1766	Approx. 7 mm		Approx. 7 mm	Approx. 6 mm	
Pile density	ISO 8543	0,100 gram/cm ³		0,10 gram/cm ³	0,141 gram/cm ³	
Number of tufts	ISO 1763	Approx. 61500/m ²		Approx. 61500/m ²	Approx. 61500/m ²	
Comfort class	EN 1307	LC3		LC3	LC3	
Other remarks						
All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs						
Fire behaviour	EN 13501-1					
Slip resistance	EN 13893					
Personal charging	ISO 6356	< 2 kV		< 2 kV	< 2 kV	