












coral® move FR coral® move vision FR

Technical specifications

Coral meets the requirements of EN 1307

Coral move FR

Coral Move Vision FR

	Total thickness	ISO 1765	8 mm
	Roll width	EN-ISO 24341	185 cm
	Roll length	EN-ISO 24341	27.5 m
	Total weight	ISO 8543	3000 g/m ²
	Pile installation weight		750 g/m ²
	Pile thickness	ISO 1766	5.5 mm
	Pile material		100% polyamide BCF ECONYL®
	Light fastness	EN-ISO 105/B02	≥ 6
	Electrical resistance	ISO 10965	≥ 10 ⁹ Ω
	Impact noise reduction	EN ISO 717-2	Δ L _w ≥ 28 dB
	Area of use		Heavy Use
	Tested flammability standards	EN 45545-2	HL3*
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2 kV
	Thermal resistance	ISO 8302	0.108 m ² K/W

*EN45545-2 testing has been carried out on different substrates/adhesives. This is the highest achieving result.

For a full overview of specific results on aluminium and plywood subfloors please ask.

Forbo Flooring Systems does its best to ensure that the contents of these technical documents are accurate at the time of publication.

However for up to date technical specifications please refer to our website at: www.forbo-flooring.com/transport