

**DoP (declaration of performance)**  
**Declaration of performance**  
**Nr. 923.1.3**

## 923 EUROPLAN EXTREME

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Forbo Eurocol Nederland 923 Europlan Extreme; a self-levelling, humidity and freeze-resistance, fast curing levelling mortar for extreme conditions.	
3. Application	Levelling stony sub-floors in layers of 2 to 20 mm thick that need to be covered with flooring. Suitable for use in so-called wet rooms, swimming pools and various exterior applications such as balconies and terraces. Also suitable for pouring drains, gutters and piping ducts.	
4. Name and contact address manufacturer	<i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i>	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	n/a	
8. European Technical Assessment	n/a	
9. Declared performance	CT-C30-F10 in accordance with NEN-EN 13813:2002 Cement-bound self-levelling levelling mortar for interior and exterior use.	
<b>Essential characteristics</b>	<b>Performance</b>	<b>Test method</b>
Tensile strength after 28 days	F10	NEN-EN 13892-2:2002
Compressive strength after 28 days	C30	NEN-EN 13892-2:2002
Material behaviour in case of fire	Class F	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 24-05-2017 signed: ing. T.W. Breeuwer; Manager R&D 