Technical specifications

Earthscape carpet tiles meet the requirements of EN 1307

tessera® earthscape

	Description		Tufted multi-height loop pile carpet tile
Î. €}	Dimensions		50cm x 50cm
Ě	Total thickness		7.1mm ± 10%
_	Pile height		4.0mm ± 0.5mm
Ħ	Collection size		12 colourways, 4m ² per box
iii iii	Commercial use	EN ISO 10874	Class 33, Suitable for any type of heavy contract application
	Pile composition		100% Invista Antron [®] Lumena polyamide 6.6
	Dye method		100% solution dyed
	Stitch density		208,032 per m² ± 10%
ŝ	Pile weight		978 gsm ± 10%
	Total weight		4,493 gsm ± 10%
	Primary backing		Polyester
	Secondary backing		ProBac recycled mineral filler with low amount of modified bitumen and polyester fleece. Contains over 76% recycled content
٩	Acoustic	ISO 10140-3	Impact sound $\Delta L_W = 26 \text{ dB}$
)))		ISO 354	Sound absorption = 0.15
6	Castor chair use	ISO 4918	r ≥2.4 continuous use
R	Light fastness	EN ISO 105-B02	≥5
ר א ע א	Dimensional stability	EN 986	≤0.4%
Ŷ	Creating Better Environr		
Ţ	Renewable Energy		All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas
- 63	Recycled Content		Earthscape carpet tiles contain 57% recycled content by weight
<u> </u>	Indoor air quality		Earthscape carpet tiles products comply to 01350 Indoor Air Quality Standard
Rodbo back to the floor rooking failer floor	Back to the Floor		Installation off cuts can be collected via Back to the Floor
	Ska rating		Earthscape meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Prodis-GUT	www.pro-dis.info	3140E7F6
\oplus	Installation method		Monolithic or quarter turn
	Earthscape carpet tiles meet the requirements of EN 14041		
CE	Product code	EN 14041	1170100-DoP-306
G st NCS	Reaction to fire	EN 13501-1	B _{fl} -s1, G, NCS
°?€7 ≥0,30	Slip resistance	EN 13893	μ ≥ 0.30
ジネ <2.0 KV	Body voltage	ISO 6356	< 2.0kV
° R ₂₃ †††	Thermal resistance	ISO 8302	0.079 m².K/W

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Earthscape carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.



www.forbo-flooring.co.uk

