

Forbo Environmental Data Sheet

Product name	Tessera Earthscape
Product description	Tessera Earthscape is a heavy multi-level loop carpet tile with a polyamide 6.6 pile, available in 12 organic trend led colours. Earthscape complies with all requirements of EN1307: Textile Floor Coverings - Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, OHSAS 18001, SA8000°



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content of product by weight	57%	ISO 9001 Quality Management System	CENTRE CENTRE CONTROL CENTRE CONTROL CENTRE
Post industrial recycled content	57%	ISO 14001 Environmental Management System	ISO 14001
% renewable electricity	100%	OHSAS 18001 Occupational Health and Safety Management	DE DESC DESC DESC DESC DESC DESC DESC DESC
% gas	100% biogas	Earthscape is made in an SA8000° certified facility	SAL

Your footsteps – how	it performs
Health and well being	
Air quality CHPS 01350	Tessera products comply to 01350 Indoor Air Quality Standard
AgBB/DiBt	Pass
Impact sound reduction	26 dB
Installation	
Recommended adhesives	Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 540 Eurosafe Special, again a solvent free adhesive, is recommended.
	Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent nonrelease bond.
	Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission

Eurocol 640 Eurostar special.

adhesive Eurocol 542 Eurofix tack plus should be used. If a permanent bond is required, please use



creating better environments

Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK.

Contribution to Green Building Schemes

LEED (version 4)

Potential direct or indirect contribution to following	Materials and Resources	Materials and Resources		
categories and credits:		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point		
		Construction and demolition waste management up to 2 points		
	Indoor environmental quality	Low emitting materials up to 3 points		
	quanty	Acoustic performance up to 1 point		
Forbo design principles (Rec		as reduced our bitumen usage by 50%.		
Forbo design principles (Red		as reduced our bitumen usage by 50%.		
	Investment in an extruder ha	used in the production of new Tessera Carpet tiles. : tiles can be reprocessed and turned into backing at our Bamber Bridge p process. All Tessera samples can be returned allowing them to be reused		
Reduce	Investment in an extruder had Yarn ends are rewound and Cutting waste and imperfect plant – creating a closed loo or recycled, reducing the new Fillers and compounds all co	used in the production of new Tessera Carpet tiles. I tiles can be reprocessed and turned into backing at our Bamber Bridge p process. All Tessera samples can be returned allowing them to be reused ed for virgin material.		