























Technické specifikace

Kobercové čtverce Earthscape splňují požadavky normy EN 1307

	Popis	Kobercový čtverec s vpichovanou víceúrovňovou smyčkou	
	Rozměry	50cm x 50cm	
	Celková tloušťka	7.1mm ± 10%	
	Výška vlákna	4.0mm ± 0.5mm	
	Velikost kolekce	12 dekorů; 4m ² v balení	
	Komerční použití	EN ISO 10874	Class 33, suitable for any type of heavy contract application
	Složení vlákna	100% Invista Antron® Lumena polyamid 6.6	
	Metoda barvení vlákna	100% plně probarvené vlákno	
	Hustota vpichů	208,032 na m ² ± 10%	
	Hmotnost vláken	978 g/m ² ± 10%	
	Celková hmotnost	4,493 g/m ² ± 10%	
	Primární nosná vrstva	Polyester	
	Sekundární rubová vrstva	ProBac recycled mineral filler with low amount of modified bitumen and polyester fleece. Contains over 76% recycled content.	
	Akustika	ISO 10140-3	Impact sound $\Delta L_W = 26$ dB
		ISO 354	Absorpce zvuku = 0.15
	Použití kolečkové židle	ISO 4918	$r \geq 2.4$ stále používání
	Light fastness	EN ISO 105-B02	≥ 5
	Dimensional stability	EN 986	≤ 0.4 %
	Creating Better Environments		
	Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)	
	Recycled Content	Earthscape carpet tiles contain 57% recycled content by weight	
	Indoor air quality	Earthscape carpet tiles products comply to 01350 Indoor Air Quality Standard	
	Back to the Floor	Installation off cuts can be collected via Back to the Floor	
	Ska rating	Earthscape meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
	Prodis-GUT	www.pro-dis.info	3140E7F6
	Installation method	Monolithic or quarter turn	

Earthscape carpet tiles meet the requirements of EN 14041

	Product code	EN 14041	1170100-DoP-306
	Reaction to fire	EN 13501-1	B _{fl} -s1, G, NCS
	Slip resistance	EN 13893	$\mu \geq 0.30$
	Body voltage	ISO 6356	< 2.0kV
	Thermal resistance	ISO 8302	0.079 m ² .K/W

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Earthscape carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

