

# eurocol

# 857

the strong connection



## EUROPRIME BLOCK PLUS

Aqua Safe Block,  
parquet primer, especially for exotic woods, smoked oak.

---

### PRODUCT TYPING

---

Base	Acrylate Copolymer.
Color	Milky white.
Consistency	Liquid.

---

- Ready-to-use, odourless roller primer for parquet.
  - Before using Eurocol parquet varnishes with blocking effect against wood ingredients that can lead to varnish adhesion problems and discolouration.
  - Especially suitable for smoked oak, corc and common exotic woods. Ideal for their new installation.
  - Also for use as a primer in parquet renovations of all types of wood.
  - GISCODE W2+, NMP-free
  - Emission-tested building product according to DIBt principles.
- 

### PROPERTIES

---

Consumption	ca. 90 ml/m <sup>2</sup> per coat.
Flammability	Non-flammable.
Frost resistance	No.
Special quality	Especially parquet flooring from exotic wood.
Specific weight	1.03 kg/l.

---

### 857 EUROPRIME BLOCK PLUS

---

## APPLICATION

---

Primer to be applied before the application of Eurocol parquet varnishes.

---

## PROCESSING

---

Storage	Store cool and dry in unopened packaging.
Tools	Microfibre roller.
Curing	Approx. 6 hours.
Waiting time	Application with roller appr. 2-3 hours.
Drying	Approx. 2 - 4 hours between two applications, 6 hours until recoating, depending on the room climate.
Shelf Life	Approx 12 months, in unopened packaging. After use close the open packaging well.
Cleaner	Water.
Remarks	

*\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

### Substrate:

- The surfaces to be sealed must be clean and free of residues of oil, wax, silicone and other adhesion-reducing layers.
- Joints are closed with suitable Eurocol joint sealant.
- The fine sanding depends on the type of wood. The surface and edge sanding must be levelled with a sanding grid.
- In case of defects, reservations must be made in writing.

### Instruction manual:

Before use, temper the product according to the processing conditions.

- Shake well before use!
- Preferably decant the varnish into a Eurocol sealing bucket and use a scraper grid when applying.
- The application has to be done with a clean Eurocol Aqua microfibre roller 25 cm.
- Smoked oak, steamed beech, merbau, wenge, acacia and other highly absorbent wood species should be rolled twice.
- During application on the prepared parquet floor, use shoe covers for the shoes to avoid footprints.
- After complete drying, seal with Eurocol water-based varnishes.

During the drying process, ensure even ventilation. Avoid draughts and direct sunlight.

### **Working conditions:**

Required surrounding temperature: min. 18°C.

Material and subfloor temperature: min. 15°C.

Relative humidity: 35 - 75%, recommended <65%.

---

## ENVIRONMENT AND HEALTH

---

GISCODE	W2+
LEED	VOC 36,2 g/l, meets: IEQ Credit 4.1
DGNB	VOC 3,2 %, quality level: 3
Hazard Class	None.
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website <a href="http://www.eurocol.nl">www.eurocol.nl</a> .
Substances causing allergy	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

---

## ITEM DATA

---

artikel	productname	packaging	shipping unit
857	Europrime Block Plus	PE jerrycan à 5 l	102/pallet

### 857 EUROPRIME BLOCK PLUS

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturer's liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturer's influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG175106, Version 07, Stand 2021-04-08, ersetzt Ausgabe vom 2021-04-06.

## **857 EUROPRIME BLOCK PLUS**

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | [info.eurocol@forbo.com](mailto:info.eurocol@forbo.com)  
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | [info.eurocol.de@forbo.com](mailto:info.eurocol.de@forbo.com)

Eurocol is part of the Forbo Group

