





# Teknisk informasjon

Eternal oppfyller kravene i ISO 10582 og EN 649

	Total tykkelse	ISO 24346 / EN 428	2,0 mm
	Tykkelse på slitesjikt	ISO 24340 / EN 429	0,7 mm
	Kolleksjonsstørrelse		113
	Offentlig - kraftig, meget kraftig	ISO 10874 / EN 685	34
	Industri - vanlig, kraftig	ISO 10874 / EN 685	43
	Rullbredde	ISO 24341 / EN 426	2,00 m
	Rullengde	ISO 24341 / EN 426	± 25 m
	Total vekt	ISO 23997 / EN 430	2,8 kg/m <sup>2</sup>
	Dimensjonsstabilitet	ISO 23999 / EN 434	< 0,1 %
	Inntrykksbestandighet	ISO 24343-1 / EN 433	≤ 0,05 mm
	Slitestyrke	EN 660-2	Gruppe T
	Rullende stolhjul	ISO 4918 / EN 425	Ingen effekt
	Lysbestandighet	ISO 105-B02	≥ 6
	Bøyelighet	ISO 24344 / EN 435	ø 10 mm
	Bestandighet mot kjemikalier	ISO 26787 / EN 423	Svært god
	Sklisikkerhet	DIN 51130	R10
	Elektrisk motstand	EN 1081	R1 > 1·10 <sup>9</sup> Ω
	Egnet for montering på gulv med gulvvarme		Ja*
	Vårromsgodkjent	EN 13553	Nei

Eternal oppfyller kravene i EN 14041

**CE**  
EN 14041

	Brannegenskaper	EN 13501-1	B <sub>f</sub> -s1
	Sklisikkerhet	EN 13893	DS - μ ≥ 0,30
	Generering av kroppsspenning	EN 1815	≤ 2 kV
	Varmeledningsevne	EN 12524	0,25 W/m·K

\* Temperature < 27 °C



Kvalitets- og miljøsystemene hos Forbo Coevorden (NL), hvor Forbo Eternal er produsert, er sertifisert med ISO 9001 og ISO 14001

