

| | | |
|---|--|---|
| 1. Unique identification | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar. | |
| 2. Designation | Forbo Eurocol 955 Wandostuc; cement-bound, fast curing levelling mortar for walls. | |
| 3. Application | For levelling and repairing cement-bound and other stony walls, such as concrete, aerated concrete, sand-lime brick, etc. as well as plaster-like walls such as plasterboard, plaster brick, etc. to which tiling is to be applied. For interior use in layers between 2 and app. 50 mm thick. Suitable for applying with a spray-gun. | |
| 4. Name and contact address manufacturer | <i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600 - Fax +31 75 6283564</i> <i>Email: info.eurocol.nl@forbo.com</i> | |
| 5. Name and contact address authorized | n/a | |
| 6. System of assessment and verification of constancy of performance | 4 | |
| 7. Activity of the notified certification body as required by the harmonized standard | n/a | |
| 8. European Technical Assessment | n/a | |
| 9. Declared performance | GP-CSIV in accordance with NEN-EN 998-1:2010; Multifunctional plaster mortar with increased compressive strength (CSIV) for use under tiling in interior situations. | |
| Essential characteristics | Performance | Test method |
| Dry bulk density | 1300 Kg/m ³ | NEN-EN 1015-10:1999+A1:2007 |
| Compressive strength after 28 days | CSIV = > 6 N/mm ² | NEN-EN 1015-11:1999+A1:2007 |
| Initial adhesive strength | 1.2 N/mm ² | NEN-EN 1015-12:2000 |
| Breakage pattern | 100% CF-A | |
| Heat conduction coefficient | λ 0,27W/mK | NEN-EN 1745:2012 tabel A.12 |
| Material behaviour in case of fire | Class F | NEN-EN 13501-1:2007+C1:2009 |
| Released dangerous substances | see MSDS | |
| Declaration drafted in accordance with Annex ZA of NEN-EN 998-1:2010. | | |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. | | |
| | | Wormerveer, 09-11-2016 signed: ing. T.W. Breeuwer; Manager R&D  |