

FORBO NUWAY® TUFTIGUARD TECHNICAL DATA

1. PRODUCT NAME & MANUFACTURER

1.1 Product:

Forbo Nuway® Tuftiguard entrance flooring

1.2 Manufacturer:

Forbo Flooring Systems
Humboldt Industrial Park
Hazleton, PA 18202

www.forboflooringNA.com

Phone: +1-800-842-7839 (US)

+1-800-268-8108 (CA)

Fax: +1-570-450-0258

1.3 Product Description:

Construction: Forbo Nuway® Tuftiguard engineered entrance flooring is constructed of scrapers and wiper materials connected by high tensile steel wire. It can have an open or closed construction. Forbo Nuway® Tuftiguard is designed for use outside doorways and immediately inside heavily trafficked entrance areas to scrape off the worst of soil being tracked in on the soles of shoes or wheeled vehicles.

1.4 Physical Characteristics:

(dimensions are approximate)

Depth -----12 mm (7/16")
17 mm (11/16")

Length -----Maximum of 98.43" (2,500 mm)

Width -----Maximum of 29.53" (750 mm)

Scraper Bars -----Aluminum

Wiper Materials -----Rubber

Wiper Designs -----Plain, Natural Fibers or Colored
Fibers

Pile Material -----100% polyamide

Connectors -----High Tensile Steel Wire

Size -----Made to Order

2. PRODUCT PERFORMANCE & TECHNICAL DATA

2.1 Application Areas:

Zone 1: Outside and Inside entrances to the building.
Refer to Forbo's Entrance Systems brochure for additional information.

2.2 Environmental:

Forbo Nuway® Tuftiguard contributes to LEED® v4 credits.
For additional information, contact Forbo Flooring Systems.

2.3 Slip Resistance:

Meets or exceeds the industry recommendation of >0.5 for flat surfaces when tested in accordance with ASTM D 2047, Standard Test Method for Static Coefficient of Friction.

2.4 Durability:

100 hours of salt fog with no notable change in appearance when tested in accordance with ASTM B 117, Corrosion Resistance Test.

2.5 Fire Testing:

Class 1 when tested in accordance with ASTM E 648/ NFPA 253, Standard Test Method for Critical Radiant Flux. Meets 450 or less when tested in accordance with ASTM E 662/ NFPA 258, Standard Test Method for Smoke Density.

3. INSTALLATION

Refer to Forbo's Installation Guidelines for complete installation recommendations.

4. WARRANTY

Limited 15-year warranty. For complete details, contact Forbo Flooring Systems.

5. CARE & CLEANING

Refer to Forbo's Floor Care Guidelines for complete care recommendations.