

eurocol

905

the strong connection



EUROPLAN FILL

Universal fast drying repair mortar for floor, simple in use, fast drying, applicable from 0 mm, very smooth finishing and directly usable.

PRODUCT TYPING

| | |
|-------------|-------------------------------------|
| Base | Cement-based powder with additives. |
| Color | Grey. |
| Consistency | Powder. |

- Simple in use
- Very fast drying
- Applicable from 0 mm
- Very smooth finishing
- Directly usable

PROPERTIES

| | |
|--------------------|---------------------|
| Flammability | Non-flammable. |
| Sensitive to frost | No. |
| Special quality | Fast drying mortar. |

APPLICATION

Mortar for:

- smoothening away irregularities and differences of height in levelling and stony floors
- filling of joints of water-resistant sheet material, bitumen and tile floors
- repairing damaged concrete

PROCESSING

| | |
|-----------------|---|
| Storage | Store cool and dry. |
| Tools | Trowel or putty-knife. |
| Mixing ratio | Add 4 parts 905 Europlan Fill to 1 part of water or mix a small quantity of powder with water to a flexible mortar. |
| Processing time | Use within 5 minutes after mixing. * |
| Waiting time | None. |
| Drying | 15-30 minutes. * |

905 EUROPLAN FILL

| | |
|------------|-----------------------------------|
| Shelf Life | 12 Months, in unopened packaging. |
| Cleaner | Water. |

* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- 905 Europlan Fill can be applied on any stony subfloor that is rigid and has a good tensile and compression strength. The subfloor should also be clean, free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.
- Apply 044 Europrimer Multi thinly and evenly on smooth and impervious subfloors (tile floors, granito, terrazzo etc.).
- Porous cement screeds should first be damped with water or primed with 044 Europrimer Multi or 049 Europrimer ABS.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Instruction manual:

- Add 4 parts of 905 Europlan Fill to 1 part of water and stir thoroughly to a homogeneous mixture.
- Apply the mortar immediately with a trowel or putty-knife.
- Until approx. 1 hour after hardening, the applied 905 Europlan Fill can still be polished by sprinkling the mortar with a little water and polishing it with a trowel.

ENVIRONMENT AND HEALTH

| | |
|------------------------|--|
| Hazard Class | Observe notes in the safety data sheet/label! |
| Safety and environment | Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Wear protective gloves and safety glasses! Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste. |
| MSDS | For extensive information about safety and environment we refer to our website www.eurocol.nl . |

ITEM DATA

| Article Definition | Packaging | EAN-code |
|--------------------|----------------------|-----------------|
| 905 Europlan Fill | Bucket with 4 kg box | 8 710345 905107 |

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturer's liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturer's influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

905 EUROPLAN FILL