

eurocol 063

the strong connection



EUROTAPE

Reinforcing tape for sealing horizontal and vertical tile connections in "wet areas", such as shower cubicles, bathrooms, utility rooms, etc. Also suitable for sealing connections of sheet material under tiling. To be used in combination with 685 Eurocoat or 683 Fibrecoat

PRODUCT TYPING

Base	Fabric made of polyester and polypropylene fibres.
Color	White.

- Flexible
- Elastic
- Seam sealing

PROPERTIES

Alkali resistance	Resistant against alkaline moisture.
Elasticity	In combination with 685 Eurocoat sufficiently elastic to intercept movement in the construction in practice.
Sensitive to frost	No.
Humidity resistance	Insensitive to moisture.

APPLICATION

For sealing horizontal and vertical corner connections of tile work in "wet areas", e.g. shower cabins, bathrooms, professional kitchens etc. Also suitable for sealing connections between board materials under tile work. Use in combination with 685 Eurocoat or 683 Fibrecoat.

PROCESSING

Storage	Store dry.
Moisture resistance	Insensitive to moisture.
Shelf Life	Unlimited.

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Substrate:

- 063 Eurotape can be applied on almost any type of subfloor that is clean and free from grease and dirt.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Instruction manual:

See directions for use of 685 Eurocoat.

063 EUROBAND

ENVIRONMENT AND HEALTH

MSDS For extensive information about safety and environment we refer to our website www.eurocol.nl.

ITEM DATA

Article	Definition	Packaging	EAN-code
063	Eurotape	Box of 100 m ¹	8 710345 057301
063	Eurotape	Box of 4x25 m ¹	8 710345 001038
685/063	Eurocoat/Eurotape	Do-it-yourself packaging of 4 kg 685 Eurocoat/12 m ¹ 063 Eurotape	8 710345 003612

BG172063, Version 01, Stand 2022-08-30,

063 EUROBAND

