

Product quick info

**CD40+ 1R U30 NP-NA-HACCP
BL FDA**


Sketch of cross-section (not actual size)

Applications

- Dough conveying
- Meat processing
- Poultry conveying
- Seafood processing
- Fruit & vegetable processing

Properties/Advantages

- Cord reinforced homogenous belt with increased belt strength for higher load and long-distance transportation (cord spacing = 12.5 mm (0.49 in))
- Easy to clean
- Form-fit power transmission via sprockets with self-tracking properties
- Smooth running
- Reduced product contact area and improved product release
- Complies to the regulation for direct contact to foodstuffs accord. to FDA, EU and MHLW

**Basic technical data**

Top face	Polyurethane, inverted pyramid
Underside	Polyurethane, Center Drive
Article no.	640031
d _{min} [mm]	76
Total thickness [mm]	3.4/10.9
C3 value [N/mm]	6.0
Weight [kg/m ²]	3.5
Permitted operating temperature [°C]	-10 to +70

Product Quick Info | EN | 02.2026
FMS · Reproduction of text or parts thereof only
with our approval. Modifications reserved.

Forbo Siegling GmbH
Lilienthalstrasse 6/8, D-30179 Hannover
Phone +49 511 67 04 0
www.forbo-siegling.com, siegling@forbo.com