

ADHESIVE

MANDATORY

Tackifier 541 Eurofix Anti Slip

Ref. : 541

541 eurofix tack plus is a non-slip, solvent-free fixative with very low VOC emissions (EMICODE EC1) and very low consumption. It is recommended for the new-build and renovation of removable lead tiles with bituminous felt backing, such as Tessera.

Technical characteristics :

Waiting time : 60 minutes depending of the ambient temperature and subfloor porosity.

Consumption : 100 to 150 g/m² (foam roller).

Bucket of 10 kg



FOR A DISSIPATIVE INSTALLATION

MANDATORY

1 Additive 841 Europrimer ec Ref. : 841

841 europrimer ec is a conductive agent which has to be mix with the tackifier 541 eurofix anti slip to improve ESD properties. In association with a copper tape linked to the ground. This installation will improve the ESD properties to a dissipative installation.

Technical characteristics :

Consumption : 1 bucket of 3.5 liters of 841 in one bucket of 10 kg of 541 eurofix anti slip.

Bucket of 3.5 liters



2 Self-adhesived copper tape Ref. : 801

For rooms requiring the use of conductive or dissipative flooring. It is installed under conductive or dissipative tiles and allows electrostatic charges to be discharged to earth (connection is made by the electrician).

Bonding is carried out using 541 eurofix anti-slip conductive adhesive.

Roll of 20 m

