

150 Parquet Doctor

1-K-PU PARQUET REPAIR ADHESIVE

PRODUCT DESCRIPTION

Low-viscosity, moisture-curing PUR adhesive for the small-surface repair of hollow areas under parquet flooring. Cavity filling through slight foaming..



PARQUET

PRODUCT FEATURES

Repair of hollow areas under parquet flooring.

TECHNICAL DATA

Base	PUR
Colour	brown
Consistency	low viscous
Cleaning agent	358 ToolCleaner
Processing conditions	not below 15 °C on the subfloor, minimum 18°C material- and room temperature 35-75% relative air moisture, recommended <65%
Mode of application	directly from the bottle
Consumption	depending on the cavity
Curing time	approx 3 hours
Permitted shelf-life	within approx. 12 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C
Frost sensitivity	no
Moisture sensitive	yes
Code acc. to GHS	yes, note safety data sheet
Environment/Work safety	Contains isocyanates. May produce an allergic reaction. Restricted to professional users.

SUBFLOOR

After fine sanding, the wood surfaces to be treated must be clean and dry without residues of old coatings, oil, wax, silicone and other adhesion-reducing layers. Joints are closed with suitable Eurocol joint sealant.

APPLICATION

Isolate the hollow area, secure the drilling point with adhesive tape against chipping and soiling. Drill the hole and inject adhesive. Use disposable syringes if necessary. Remove excess adhesive. Remove adhesive tape and weigh down for several hours until the adhesive has set. Close drill hole with wooden dowel in matching colour.
Suitable for all types of installed parquet, wood and all permanently dry substrates.

NOTE

Please pay attention to the technical data sheet and safety data sheet issued by the parquet manufacturer.

PACKAGING

0,75 kg nonreturnable package netto, (6/carton)

SAFETY NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.

The manufacturer's terms and conditions are binding

Stand 2018-09-04
ersetzt Ausgabe vom 11. März 2008

Version Nr.:02
BG146580_150-HW 001