eurocol

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

 Printing date 01.04.2021
 Version number 5.1
 Revision: 01.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 154 Eurowood SF Ultra
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Forbo Eurocol Deutschland GmbH August-Röbling-Straße 2 99091 Erfurt GERMANY

Tel.: +49 361 730 41 0 Fax: +49 (0)361 73041-92

E-Mail: Elisabeth.Reinhardt@forbo.com

www.forbo-eurocol.de

· Further information obtainable from:

Laboratory

Elisabeth Reinhardt

Elisabeth.Reinhardt@forbo.com

· 1.4 Emergency telephone number:

Poison information center for the states of Mecklenburg-Western Pomerania, Saxony, Saxony-Anhalt and Thuringia:

+49-361-730730

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Warning

(Contd. on page 2)

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

(Contd. of page 1)

· Hazard-determining components of labelling:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

· Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous componer	nts:	
	trimethoxyvinylsilane	≤2.5%
	🏇 Flam. Liq. 3, H226; 🗘 Acute Tox. 4, H332	
 - -	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate \textcircled{A} Aquatic Acute 1, H400; Aquatic Chronic 1, H410; \textcircled{A} Skin Sens. 1A, H317	≥0.25-<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class (TRGS): 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
2768-02-	7 trimethoxyvinylsilane	
Oral	DNEL Long-term - oral, systemic effects	0.3 mg/kg_bw/day (general public)
Dermal	DNEL Long-term – dermal, systemic effects	3.9 mg/kg_bw/day (Worker)
		7.8 mg/kg_bw/day (general public)
	•	(Contd. on page

(Contd. on page 4)

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

			(Contd. of page
Inhalative	DNEL Long-term – inhalati	on, systemic effects	27.6 mg/m³/day (Worker)
			6.7 mg/m³/day (general public)
1065336-9	11-5 Reaction mass of bis(1 pentamethyl-4-piperidyl		hyl-4-piperidyl) sebacate and methyl 1,2,2,6,6
Oral	DNEL Long-term - oral, sys	temic effects	0.05 mg/kg_bw/day (general public)
Dermal	DNEL Long-term – dermal,	systemic effects	0.5 mg/kg_bw/day (Worker)
			0.25 mg/kg_bw/day (general public)
Inhalative	DNEL Long-term – inhalati	on, systemic effects	0.68 mg/m³/day (Worker)
			0.17 mg/m³/day (general public)
PNECs			
2768-02-7	trimethoxyvinylsilane		
PNEC sho	rt term, fresh water	0.4 mg/l (Aquatic organisms)	
PNEC sho	rt term, sea water	0.04 mg/l (Aquatic organisms)	
PNEC sho	rt term, sewage plant	6.6 mg/l (Aquatic organisms)	
PNEC sho	rt term fresh water sediment	1.5 mg/kg (Aquatic organisms)	
PNEC sho	rt term soil	0.06 mg/kg (Aquatic organisms)	
PNEC sho	rt term sea water sediment	0.15 mg/kg (Aquat	ic organisms)
PNEC sho	rt term, intermittent releases	2.4 mg/l (Aquatic o	organisms)
1065336-9	11-5 Reaction mass of bis(1	,2,2,6,6-pentameti	hyl-4-piperidyl) sebacate and methyl 1,2,2,6,6
	pentamethyl-4-piperidyl	sebacate	
PNEC short term, fresh water		0.002 mg/l (Aquatic organisms)	
PNEC short term, sea water		0 mg/l (Aquatic organisms)	
PNEC short term, sewage plant 1 mg/l (A		1 mg/l (Aquatic org	ganisms)
PNEC short term fresh water sediment 1.05 mg/kg (Aquati		ic organisms)	
PNEC sho	ort term soil 0.21 mg/kg (teresstric organismens)		tric organismens)
PNEC short term sea water sediment 0.11 mg/kg (Aquatic organisms)		ic organisms)	
PNEC sho	rt term, intermittent releases	0.009 mg/l (Aquati	ic organisms)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 5)

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

(Contd. of page 4)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chem	nical properties
9.1 Information on basic physical and	l chemical properties
General Information	
Appearance:	
Form:	Viscous
Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	ge: Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.6 \mathrm{g/cm^3}$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	< 0.2 %
VÕC (EC)	0.19 %
9.2 Other information	No further relevant information available.

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:	
ATE (Acute Toxicity Estimates)	
Inhalative $ LC50 (4h) > 712 \text{ mg/l (rat)}$	

276	8-02-7	trimethoxy	vinylsilane
_	1	T D = 0	-100 -006

Oral	LD50	7120-7236 mg/kg (rat)
Dermal	LD50	3200 mg/kg (rabbit)
Inhalative	LC50 (4h)	16.8 mg/l (rat)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Oral	LD50	3230 mg/kg (rat)
Dermal	LD50	3170 mg/kg (rat) (OECD 402)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation
 - May cause an allergic skin reaction.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

LC50 (96h) mg/ltr. 0.9 mg/ltr (Fish) EC50 (72h) 0.42 mg/l (algae)

(Contd. on page 7)

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

		(Contd. of page 6)
	ce and degradability	
125643-61-0	A mixture of isomers of: C7-9-alkyl-3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate	4 (28d) %
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	38 %

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	not regulated
14.2 UN proper shipping name ADR, IMDG, IATA	not regulated
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	not regulated
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Ann Marpol and the IBC Code	vex II of Not applicable.
UN "Model Regulation":	not regulated

Printing date 01.04.2021 Version number 5.1 Revision: 01.04.2021

Trade name: 154 Eurowood SF Ultra

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · VOC (EU) 3.2 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS: Environmental Protection Department

· Contact:

Laboratory

Elisabeth Reinhardt

Elisabeth.Reinhardt@forbo.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category I

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.