

DSDC ACCREDITED PRODUCTS

Age inclusive design

NUWAY
& CORAL
ENTRANCE
FLOORING

MARMOLEUM
NATURAL
LINOLEUM

MARMOLEUM
MODULAR
NATURAL
LINOLEUM TILES

OFF THE
FLOOR
LINOLEUM

ALLURA
LUXURY
VINYL TILES

ETERNAL
GENERAL
PURPOSE
VINYL

STEP
SAFETY
VINYL

SPHERA
HOMOGENEOUS
VINYL

ACOUSTIC
FLOORING
SOLUTIONS

ESD &
CLEANROOM
FLOORING

FAST FIT
ADHESIVE FREE
FLOORING

TESSERA
CARPET TILES

FLOTEX
FLOCKED
FLOORING

FURTHER
INFORMATION

creating better environments



FLOORING SYSTEMS

EXPERTISE IN AGED CARE

At Forbo, we understand how complex the design of care facilities can be. Often these buildings will provide a range of services to support residents, which means the flooring requirements will vary from area to area. Therefore, when it comes to choosing floor coverings the decision should be about more than just function. The aim should be to create an environment that helps residents to feel comfortable and relaxed, while ensuring that the chosen products can meet the day to day demands of footfall, cleaning and infection control.

Since 2017, we have been partnered with the Dementia Services Development Centre (DSDC), to develop a portfolio of products suitable for use in dementia friendly environments. In that time more than 1,000 of our floor finishes and products have been accredited by the leading research centre.



CONTENTS

ENTRANCE FLOORING

Entrance Flooring Systems at a glance	14
Nuway	16
Coral	17

MARMOLEUM

Marmoleum at a glance	20
-----------------------	----

MARbled

Marmoleum Fresco/Real/Terra/Vivace/Splash	22
---	----

SOLID

Marmoleum Walton	26
Marmoleum Concrete	26
Marmoleum Slate	28

MARMOLEUM LINEAR

Marmoleum Linear	29
Marmoleum Ohmex	30
Marmoleum Acoustic	31
Marmoleum Decibel	32

MODULAR

Marmoleum Modular Lines	34
Marmoleum Modular Textura	35
Marmoleum Modular Shade / Slate	36
Marmoleum Modular Colour / Marbled	37

OFF THE FLOOR

Bulletin Board	38
Furniture Linoleum Desktop	39

ALLURA LUXURY VINYL TILES

Allura at a glance	40
Allura dryback	44
Allura Flex	51
Fast Fit by Allura	54
Allura Click pro	55
Allura Puzzle	58
Allura Ease	59
Allura Decibel	60

ETERNAL GENERAL PURPOSE VINYL

Eternal at a glance	62
Eternal Wood	64
Eternal Material	68
Eternal Colour	69
Eternal de Luxe	70

STEP SAFETY VINYL

Step at a glance	72
Surestep Material	74
Surestep Wood	75
Surestep Laguna	76
Safestep Aqua	77
Surestep Decibel	78

SPHERA HOMOGENEOUS VINYL

Sphera at a glance	80
Sphera Element	82
Sphera SD	84

ACOUSTIC VINYL

The Acoustic collection at a glance	86
Sarlon & Modul'up	88
Marmoleum Acoustic 14 dB	94
Marmoleum Decibel 18 dB	95
Eternal de Luxe decibel 17 dB	96
Surestep Decibel 17 dB	98
Allura Decibel 19 dB	100
Novilon Viva	102

COLOREX ESD & CLEANROOM FLOORING

ESD flooring at a glance	104
Sphera SD	105

FAST FIT ADHESIVE FREE FLOORING

Fast Fit at a glance	106
Coral Click entrance matting	108
Modul'up	110
Modul'up T.E.	116
Allura Click Pro	119
Allura Puzzle	122
Allura Ease	123

TESSERA CARPET TILES

Carpet Tiles at a glance	124
Tessera Chroma	126
Tessera Create Space 1	127
Tessera Struktur 1	128
Tessera Layout	130
Tessera Arran	132
Tessera Contour	134
Tessera Perspective	135

TESSERA PLANKS

Tessera Seagrass Planks	136
Tessera Layout Planks	138

FLOTEX FLOCKED FLOORING

The Flotex collection at a glance	140
-----------------------------------	-----

COLOUR

Flotex Colour	142
---------------	-----

COLOUR PLANKS

Colour Planks	146
---------------	-----

NATURALS

Flotex Naturals	148
-----------------	-----

PLANKS

Flotex Ombré	150
Flotex Seagrass	151
Flotex Wood	152
Case studies	154

FURTHER INFORMATION

Bespoke Design Service	158
Dementia Resources	158
BIM	158
Further reading	158

Within this brochure, Forbo has endeavoured to be positive and inclusive with the language used and product imagery shown. However, please be aware that some images may not reflect the correct dementia guidelines and are used purely as a product reference. When creating your own 'dementia-inclusive' or 'dementia-friendly' designs, please always refer to the dementia guidelines. For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring. For further guidance and information please visit www.dementia.stir.ac.uk

OUR COMMITMENT TO DESIGNING FOR INCLUSIVE ENVIRONMENTS



The number of people diagnosed with dementia in the UK continues to rise. The Alzheimer's Society estimates that there are currently around 850,000 people living with dementia in the UK and predicts that this will rise to 1.6 million by 2040. Currently 1 in 6 people over the age of 80 have dementia and 70 per cent of people in care homes have dementia or severe memory problems.

Therefore, it is essential that we start to design more inclusive environments for those with dementia, to help make their lives easier. At Forbo, we are committed to helping you achieve a safe and comfortable environment, which provides a sense of well-being, for residents of special care and dementia facilities. As a global provider of complete flooring solutions, many of which have been accredited for dementia-friendly schemes, we are in a position to offer the benefits of our unique expertise in this area.



DSDC partnership

Our work with the Dementia Services Development Centre (DSDC) is an essential part of this commitment. Based on the Centre's 25 years of global research and best practice, more than 1,000 of our products have been DSDC accredited. These flooring solutions have since been used to provide safe, comfortable, healthy and attractive spaces for a diverse range of sectors – including healthcare facilities and care environments.

Each one of our account managers have also been through the 'DSDC Intersections of Dementia & Design' training – a two-day intensive course on all aspects of dementia friendly, built environment design. As a result, our team has the knowledge to advise on which products can contribute to a dementia-friendly scheme.

Dementia CPD

We have developed a new RIBA-certified CPD, which examines the role of flooring in dementia-inclusive buildings. Developed with guidance from the DSDC, the CPD is designed for anyone who specifies flooring or is looking to create truly inclusive environments. Delivered as a live webinar by one of our expert, DSDC trained team, the CPD equips participants with the knowledge they need to create an environment that improves the lives of people with dementia.

Design for the Mind

As well as partnering with the DSDC, we have also partnered with the British Standards Institution (BSI) to develop a new inclusive-design Publicly Available Specification (PAS) for the built environment. PAS 6463 'Design for the mind – Neurodiversity and the built environment – Guide' has an expected publication date of early 2022.

This new PAS will provide guidance on the design of the built environment so that it is inclusive of people with a wide range of neurological conditions, which includes, but is not limited to, dementia and autism.

The ultimate goal is to strive to make buildings more inclusive for everyone. We are also hoping that in the future, these guidelines will be incorporated into national and international formal standards.



Request our free RIBA approved CPD: **The Role of Flooring in Dementia-Inclusive Design.**

The CPD can be delivered in person, or remotely, and is ideal for anyone working on a project where dementia design principles are important.

DESIGNING DEMENTIA FRIENDLY ENVIRONMENTS



Request our free RIBA approved CPD: **The Role of Flooring in Dementia-Inclusive Design.**

The CPD can be delivered in person, or remotely, and is ideal for anyone working on a project where dementia design principles are important.

Holistic dementia design


Dementia and other age-related changes and impairments can often make it more difficult for people to understand and navigate a building. In a dementia environment no single design element stands alone and should be viewed as a whole. As one of the largest surfaces within a building, the flooring is an integral part of the design, together with the wall colourings, doors, furniture, sanitary fittings and lighting schemes. Factoring in the contrast between colour and materials is essential to be able to create visually continuous surfaces, as well as clear visual contrast when necessary.

Design and colour combinations

The colours and designs found within our care portfolio have been carefully coordinated and muted, so that residents do not get confused by the patterns or are tempted to try and 'pick up' design elements from the floor. We closely analysed the contrast and harmony of our colours to ensure complementing designs can be created, and where necessary contrast with the colours of other interior elements such as walls and furniture. What's more, the solutions within our care portfolio also have a matt finish to avoid any disturbing reflection and, by their nature, provide a more homely atmosphere.

Light reflectance values (LRV)

Light Reflectance Values (LRV) are a measure of the percentage of visible and usable light that is reflected from a surface when illuminated by a light source. The numerical value in LRVs represents tone and does not represent hue or saturation values of a colour. Therefore, when considering contrast, it is the tone that is relevant.



DESIGN PRINCIPLES FOR DEMENTIA-FRIENDLY ENVIRONMENTS

Guidelines for product selection

There is no one way to design for dementia. The key is to make holistic decisions based on the demands of the specific project and follow the key design principles outlined in the following pages.




Careful use of tonal contrast

A recommended **difference of 30 degrees of LRV** should be achieved between critical surfaces, such as floors to walls and doors to walls. This will help people with dementia to see spaces three-dimensionally and enable them to easily navigate through the building.



Develop one continuous surface

In adjacent areas, floor finishes should be tonally similar to prevent the perception of a change in level that is not really there in order to reduce the risk of falls. The LRVs of the **adjoining floors should ideally be within eight degrees** of each other (less is better) and no more than 10 degrees.



Reduce impact sound

Minimising excess noise, echo and reverberation is important to make the environment as comfortable as possible for those with dementia. It also makes speech easier to understand to aid communication. There are a range of flooring options available with sound absorbing properties, which also meet other practical requirements.



Avoid sparkle and pattern and 'false steps'

For dementia-inclusive environments it is recommended that flecked, striped or patterned effects are avoided. These types of designs can create false steps, increase visual stimulus and could also cause illusions or hallucinations.




Avoid sensory overload

Dementia affects how the brain interprets the information it receives and so over-stimulation of the senses, especially at the same time, is a significant concern. It is important to make the environment as simple as possible by choosing the right colours and patterns for flooring and walls.




Opt for matt finishes

Excessively sparkly or shiny finishes need to be avoided. Highly reflective or glossy surfaces might be perceived as a wet floor and will therefore suggest a slip risk that is not there and in fact, increase the chances of a real fall.



Careful transitions between flooring

It is recommended that different floorings of the same thickness are abutted without the use of a transitional strip, avoiding a potential trip hazard. However, if transition strips are used, they should match the tones of both flooring surfaces, with an ideal difference of **no more than three degrees of LRV between the transition strip and the adjoining floor** to avoid creating the impression of a step that is not there.



Mindful of installation methods

Selecting products that can be fitted quickly and minimise disruption both during and after is an important consideration. Low Volatile Organic Compound (VOC) and adhesive-free products can help specifiers achieve this. **Consideration should also be given to the installation methods** of some products.



DSDC accredited

To ensure a truly dementia friendly environment is created, it is recommended that only products that have been accredited by the DSDC are used.



Scheme – not just a product

It is important to look at the flooring in the context of the whole design to ensure it works as a holistic scheme.

DEMENTIA-FRIENDLY FLOORING CHECK LIST

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme

DO'S AND DON'TS

Here are some examples of these principles in practice, as well as what to avoid when designing a scheme.

DO – DARK FLOORS

0-10 LRV



It is not always possible to achieve 30 degrees of contrast between walls, skirting and floors. When this is the case, it is essential that optimum contrast is achieved between the two critical planes; the floor and wall.

DO – DARK FLOORS

0-10 LRV



Where it is possible to abut flooring without a transitional strip, this is preferred, as this will reduce the number of interfaces to be coordinated. However, ensure the flooring is level; floor thicknesses can vary.

DON'T

FLOOR CONTRAST TOO HIGH



The contrast between the adjoining flooring is too great and the dark strip also contrasts too much. This could be perceived as a step and result in high-stepping.

DON'T

SHINY TRIM, FLOOR & WALL



Highly reflective trims create glare. The ageing eye is more sensitive to glare and often, the glare from the strip can be perceived as a step, resulting in high-stepping. For some people with dementia, the highly reflective strip can deter the person from passing.

DO – MID TONE FLOORS

11-40 LRV



Adjoining flooring should not contrast more than 10 degrees of light reflectance value. In this example there are 9 degrees of contrast between the two floors.

DO – LIGHT FLOORS

41-60 LRV



DON'T (WITH ALUMINIUM TRIM) DO (WITHOUT TRIM)



DON'T FLOOR CONTRAST TOO HIGH



DSDC ACCREDITED PRODUCTS

The Dementia Services Development Centre (DSDC) reviews products to evaluate their suitability for use in dementia-inclusive environments. For easy identification, the DSDC's accreditation scheme classifies products and assigns them a number based on the tonal contrast and pattern:

Category 1a – has a plain aesthetic and can be used widely as part of a holistic scheme.

Category 1b – has a semi-plain design, which means it can also be used throughout as long as it is coordinated with other elements.

Category 2 – has a patterned surface and as such should be used with caution.

It is important to note that the DSDC Accreditation is awarded based on the merits of the individual product and colourway, and not the final application. This means the product's interaction with other products or finishes must be evaluated.

RATING	RATING DESCRIPTION
Class 1a	<p>Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors/frames, furniture and sanitary ware.</p> <p>Contrast is the key word.</p> <p>We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>
Class 1b	<p>Flooring within this rating is semi-plain (minimal texture or fleck/pattern, wood effect with no knots) and in general, can be used throughout.</p> <p>Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>
Class 2	<p>Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured/patinated and although still familiar they need to be used with more caution than the above range.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>



Request our free RIBA approved CPD: **The Role of Flooring in Dementia-Inclusive Design.**

The CPD can be delivered in person, or remotely, and is ideal for anyone working on a project where dementia design principles are important.

FORBO PRODUCTS

When designing a dementia friendly environment, it is essential to find a suitable floor covering, as not only can the floor have a positive impact on the safety and orientation of a space but, when used correctly, they can help provide confidence, security and independence.

At Forbo, we have developed a care portfolio to help in your decision making, which comprises a large selection of DSDC accredited solutions for each and every area of a dementia-friendly building.

Within this brochure, Forbo has endeavoured to be positive and inclusive with the language used and product imagery shown. However, please be aware that some images may not reflect the correct dementia guidelines and are used purely as a product reference.

When creating your own 'dementia-inclusive' or 'dementia-friendly' designs, please always refer to the dementia guidelines.

Please note: For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring.

For further guidance and information please visit www.dementia.stir.ac.uk

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Surestep Decibel safety vinyl

ENTRANCES

Coral and Nuway entrance flooring systems will help minimise the amount of dirt and moisture that is transported into the care facility, making the building safer by reducing the risk of slips and falls.

The Nuway range of single and double sided rigid entrance floor systems offers an outstanding first line of protection against dirt and moisture, with guarantees of up to 15 years. Our Coral range has been the international market leading textile entrance flooring for more than 40 years. Each m² of Coral removes up to 6 litres of water or 5kg of dirt for a cleaner, safer environment.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Coral Brush 5764 | petrified grey + Tessera Layout 2124 | pina colada

nuway® tuftiguard

The original and most widely used rigid entrance mat in the UK. Reversible, effectively doubling its lifespan and guaranteed for up to 15 years. Available in open or closed format with single or double wiper strips for increased moisture removal.



coral® click

Coral Click is an exceptionally versatile 'off the shelf' modular matting system that can be assembled on site.



coral® brush

Coral Brush is suitable for all types of entrance areas, absorbing moisture and removing dry soiling as the weather demands. Available in sheet and tile.



coral® classic

Coral Classic's moisture absorbing yarns is enough to absorb half of the foot-borne moisture that would otherwise be carried inside on the soles of people's shoes.





Tuftiguard Bamboo – the sustainable choice

Nuway entrance systems provide an outstanding first line of defence against soil and moisture entering a building and is a perfect solution for high footfall areas.

As the name suggests, Nuway Bamboo scraper bars are made from bamboo, which is a sustainable species of grass providing a matt look and ideal for use alongside timber finishes

Nuway Bamboo has been accredited as 1B when used alongside using buffed wiper strips.



Nuway Bamboo has been accredited as 1B when used alongside using buffed wiper strips.





coral® click

The first steps in protecting your building.


Coral Click is an exceptionally versatile 'off the shelf' modular matting system that can be assembled on site. Coral Click can be used on its own or in conjunction with our Coral clean-off textile ranges to provide an integrated entrance system.

This versatile PVC tile with Coral Brush inserts can be used in all types of buildings and, because it contains no metal components, Coral Click entrance products are particularly suitable for installation in retail environments as they do not interfere with electronic-tagging systems.

- 'Off the shelf' modular matting system
- Exceptionally easy to fit, handle and store
- Available in 12mm & 17mm depths
- Textile inserts from the award winning Coral Brush collection
- Coral Brush insert is produced using 100% Econyl® regenerated yarn
- Coral Entrance flooring systems remove up to 95% of dirt and moisture from shoes and wheeled traffic
- 5 year guarantee



7833 (12mm) | 7883 (17mm)



7837 (12mm) | 7887 (17mm)

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

Description	Modular matting system	
Dimensions	24 x 24cm	
Total thickness	ISO 1765	11/16mm (without textile insert) 14/19mm (with Coral Brush insert)
Pile material	100% regenerated Econyl® Nylon	
Collection size	6	
Application	EN 1307	Class 33
CE	EN 14041	

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.




The great all-rounder

Coral Brush is suitable for all types of entrance areas, absorbing moisture and removing dry soiling as the weather demands.

- Functional all-rounder that removes both moisture and dirt
- 100% of the yarn in Coral Brush is Econyl® regenerated solution dyed polyamide
- Appealing solid and linear designs
- Complies with the highest fire class standard for a textile product: B_{fl}-s1
- Suitable for heavy contract use: wear class 33
- Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50cm x 50cm tiles
- Adhesive-free options available

Description	Tufted cut pile	
Dimensions	Roll width 105 / 155 / 205cm* Roll length ≤ 27.5m Tiles 50 x 50cm	
Mat dimensions	55 x 90cm / 90 x 155cm / 135 x 205cm / 205 x 300cm	
Total thickness	ISO 1765	Approx 9.0mm
Backing	EVERFORT® vinyl	
Yarn	100% regenerated ECONYL® Nylon	
Collection size	18 (12 tiles in a box, 3m ²)	
Application	EN 1307	Class 33
CE	EN 14041	<i>Note: The requirements of EN14041 do not apply to loose laid mats and rugs</i>
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS
Personal charging	ISO 6356	<2 kV

**NOTE: Roll sizes include 2.5cm salve edge on each side.*
Our recommended adhesive for Coral Sheet products is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



5721 | hurricane grey LRV 3



5710 | asphalt grey LRV 2




5730 | vulcan black LRV 1



5715 | charcoal grey LRV 2



5727 | stratos blue LRV 2



5723 | cardinal red LRV 2

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.

The ultimate moisture absorber

Research shows that taking just two steps on Coral Classic's moisture absorbing yarns is enough to absorb half of the foot-borne moisture that would otherwise be carried inside on the soles of people's shoes.

- Maximum moisture absorption and effective dirt removal
- Choice of practical colourways
- Complies with the highest fire class standard for a textile product: B_{fl}-s1
- Suitable for heavy contract use: wear class 33
- Ideal for interior entrances and circulation areas
- Available in sheet, mats and 50cm x 50cm tiles
- Adhesive-free options available

Description	Tufted cut pile	
Dimensions	Roll width 105 / 155 / 205cm* Roll length ≤ 27.5m Tiles 50 x 50cm	
Mat dimensions	55 x 90cm / 90 x 155cm / 135 x 205cm / 205 x 300cm	
Total thickness	ISO 1765	Approx 9.0mm
Backing	EVERFORT® vinyl	
Yarn	100% polyamide – BCF solution dyed	
Collection size	13 (12 tiles in a box, 3m ²)	
Application	EN 1307	Class 33
CE	EN 14041	<i>Note: The requirements of EN14041 do not apply to loose laid mats and rugs</i>
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS
Personal charging	ISO 6356	<2 kV


**NOTE: Roll sizes include 2.5cm salve edge on each side.*
Our recommended adhesive for Coral Sheet products is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



4751 | silver grey LRV 9




4721 | mouse grey LRV 4



4730 | raven black LRV 2



4756 | bronzetone LRV 2



4750 | warm black LRV 4

Forbo's linoleum brand

Our Marmoleum linoleum is a flooring renowned for its durability, versatility, sustainability, quality and design choice.


Marmoleum is ideal for care environments as it is proven to inhibit the growth and spread of infections like MRSA, C Difficile and Norovirus and has the Allergy UK Seal of Approval – contributing to a healthier and more hygienic space.

Marmoleum is available in a wide range of tranquil all-over designs and the smooth surface makes movement easy even when walking has become a 'shuffle'.

The unique Topshield finish of Marmoleum resists staining and makes cleaning simple. It is also made from 97% natural raw materials and is CO₂ neutral (cradle to gate) without the need to offset.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme




marmoleum® marbled

Taking inspiration from the natural world, and offering a spectrum of over 90 colours across the Fresco, Real, Terra, Vivace and Splash ranges, the Marmoleum Marbled collection combines both subtle and striking marbled effects to create a range that provides the perfect backdrop for any commercial interior.



marmoleum® solid

The five individual finishes provide the foundation for creating pure, distinctive and modern spaces. The Solid collection combines contemporary styling with a versatility that enables designers to design an elegant, natural backdrop to any interior.



marmoleum® linear

Marmoleum Linear is known for its subtle yet distinctive directional design which is complemented by a natural colour palette comprising both cool and warm tones.



MARMOLEUM COLLECTION AT A GLANCE

marmoleum® ohmex | decibel | acoustic

(special acoustic and static dissipative varieties)

In addition to our standard ranges, we also offer a number of linoleum floor coverings developed to meet specific technical or comfort requirements, including static control and impact sound reduction.



marmoleum® modular

Comprising 6 distinct design ranges – Lines, Textura, Slate, Shade, Marble and Colour, the Marmoleum Modular collection offers 100 x 25cm planks and 50 x 25cm and 50 x 50cm tiles to allow complete design freedom.



bulletin board®

Pinboard linoleum, or Bulletin Board, offers a practical, simple solution to collect and exchange thoughts and ideas wherever people plan, create and meet. Simply share your thoughts by pinning your idea onto the wall.



furniture linoleum

Furniture Linoleum is a decorative surfacing material that can be applied to vertical, horizontal and curved surfaces, providing interior furniture with a truly distinctive and individual look.



Visit the Marmoleum section on our website.



See all available technical downloads for Marmoleum.

marmoleum® marbled

fresco | real | terra | vivace | splash

Marmoleum

Taking inspiration from the natural world, and offering a spectrum of over 90 colours across the Fresco, Real, Terra, Vivace and Splash ranges, the Marmoleum Marbled collection combines both subtle and striking marbled effects to create a range that provides the perfect backdrop for any commercial interior.






	<table border="1"> <tr> <td>Description</td> <td>Linoleum sheet</td> </tr> <tr> <td>Dimensions</td> <td>EN-ISO 24341 Roll width 2.0m Roll length ≤ 32m</td> </tr> <tr> <td>Total thickness</td> <td>EN-ISO 24346 2/2.5/3.2mm</td> </tr> <tr> <td>Collection size</td> <td>83</td> </tr> <tr> <td>Application</td> <td>EN-ISO 10874 Class 23/34/43</td> </tr> <tr> <td>CE</td> <td>EN 14041</td> </tr> <tr> <td>Reaction to fire</td> <td>EN 13501-1 C_{s1}-s1</td> </tr> <tr> <td>Slip resistance</td> <td>EN 13893 DS: ≥0.30</td> </tr> </table> <p>Our recommended adhesive is 414 Euroflex Lino Plus or 611 Eurostar Lino Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk</p>		Description	Linoleum sheet	Dimensions	EN-ISO 24341 Roll width 2.0m Roll length ≤ 32m	Total thickness	EN-ISO 24346 2/2.5/3.2mm	Collection size	83	Application	EN-ISO 10874 Class 23/34/43	CE	EN 14041	Reaction to fire	EN 13501-1 C _{s1} -s1	Slip resistance	EN 13893 DS: ≥0.30
Description	Linoleum sheet																	
Dimensions	EN-ISO 24341 Roll width 2.0m Roll length ≤ 32m																	
Total thickness	EN-ISO 24346 2/2.5/3.2mm																	
Collection size	83																	
Application	EN-ISO 10874 Class 23/34/43																	
CE	EN 14041																	
Reaction to fire	EN 13501-1 C _{s1} -s1																	
Slip resistance	EN 13893 DS: ≥0.30																	

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

marmoleum® marbled

fresco | real | terra | vivace | splash







Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 32m
Total thickness	EN-ISO 24346	2/2.5/3.2mm
Collection size	83	
Application	EN-ISO 10874	Class 23/34/43
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 414 Euroflex Lino Plus or 611 Eurostar Lino Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.




marmoleum® solid

concrete | slate | walton

Marmoleum Solid is a contemporary collection that fits perfectly with the desire for more solid visuals and raw tactility. With its variety of plain to semi-plain aesthetics, it provides a large choice of honest designs that give the collection a strong, modern, identity. Solid has been designed to combine beautifully with other natural materials such as wood, glass and metal.



marmoleum® walton



Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 33 lm
Total thickness	EN-ISO 24346	2.5mm
Collection size	78	
Application	EN-ISO 10874	Class 23/34/43
CE	EN 14041	
Reaction to fire	EN 13501-1	C _{s1} -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 414 Euroflex Lino Plus or 611 Eurostar Lino Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

marmoleum® concrete



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.


marmoleum® slate



Inspired by the natural texture of stone, Marmoleum Slate introduces a unique embossed texture that adds a new dimension to our Marmoleum flooring. The result is a surface that has the timeless aesthetic of stone with the warmth and purity of linoleum.




Marmoleum Slate e3725 | Welsh slate




e3747 | Lakeland shale LRV 21



e3745 | Cornish grey LRV 15



e3746 | Newfoundland slate LRV 11



e3725 | Welsh slate LRV 9



e3707 | Highland black LRV 7

Description		Linoleum sheet
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 33 lm
Total thickness	EN-ISO 24346	2.5mm
Collection size		78
Application	EN-ISO 10874	Class 23/34/43
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 414 Euroflex Lino Plus or 611 Eurostar Lino Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

marmoleum® linear

Marmoleum Solid / Linear



Marmoleum Linear is known for its subtle yet distinctive directional design which is complemented by a natural colour palette comprising both cool and warm tones.




Marmoleum Linear 5232 | rocky ice + 5225 | compressed time



Marmoleum Linear 3573 | trace of nature



5225 | compressed time



5218 | Welsh moor LRV 8




5217 | withered prairie



5232 | rocky ice



3573 | trace of nature LRV 27



LRV 34



Description		Linoleum sheet
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 33m
Total thickness	EN-ISO 24346	2.5mm
Collection size		27
Application	EN-ISO 10874	Class 23/34/43
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 414 Euroflex Lino Plus or 611 Eurostar Lino Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

Ohmex Static Dissipative Linoleum meets the higher requirements for electrical conductivity.

Electrical resistance is improved to $< 1 \cdot 10^8$ (EN1081), ensuring personal safety and protecting equipment that is sensitive to static electricity. Marmoleum Ohmex, which is 2.5mm thick, is available in six colours. Typical areas of use are computer/server rooms and areas with sensitive electrical equipment.






Description	Linoleum sheet
Dimensions	EN-ISO 24341 Roll width 2.0m Roll length \leq 32 lm
Total thickness	ISO 1765 2.5mm
Collection size	6
Application	EN 1307 Class 23/34/42
Electrical resistance	EN 1081 $1 \cdot 10^8 < R_1 < 1 \cdot 10^9 \Omega$ static dissipative
CE	EN 14041
Reaction to fire	EN 13501-1 C _s -s1
Slip resistance	EN 13893 DS: \geq 0.30

Our recommended adhesive is 615 Eurostar Lino EL. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk.



Marmoleum Acoustic has a total thickness of 4mm and reduces impact sound by 14 dB (ISO 717-2).

It is a twinlayer linoleum built up from 2mm of Marmoleum and 2mm Corkment backing. Using Marmoleum Acoustic reduces installation costs as it can be installed in one go, avoiding the need to first lay Corkment and then Marmoleum. Marmoleum Acoustic is available in six colours.



Description	Linoleum sheet
Dimensions	EN-ISO 24341 Roll width 2.0m Roll length \leq 32m
Total thickness	ISO 1765 4.0mm
Collection size	6
Application	EN 1307 Class 23/34/41
Acoustical impact noise reduction	\leq 14 dB
CE	EN 14041
Reaction to fire	EN 13501-1 C _s -s1
Slip resistance	EN 13893 DS: \geq 0.30

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

marmoleum® decibel 18 dB




Marmoleum Decibel is 3.5mm thick and provides an impact sound reduction of 18 dB. The acoustic performance is achieved by laminating 2.5mm Marmoleum onto a 1mm thick layer of polyolefin foam.

Marmoleum Decibel is also available in all Marmoleum colours as a made-to-order item with an 18 dB impact sound rating. Please note that minimum order quantities and lead times will apply. Please contact Forbo Customer Service for more details.

Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 32m
Total thickness	ISO 1765	3.5mm
Collection size	27	
Application	EN 1307	Class 23/34/41
Acoustical impact noise reduction	≤ 18 dB	
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.



marmoleum® modular | lines

Marmoleum Modular is a collection with a twist, offering over 50 colours and 3 different tile and plank sizes, that enable individual and sustainable flooring designs to be created.

Similarly to Marmoleum Sheet, the Marmoleum Modular collection is split into six design styles – Lines, Textura, Shade, Slate, Colour and Marbled.

Lines: Bringing the linearity trend into the colour spectrum of the 21st Century, the Marmoleum Modular Lines range features a palette of 11 striated colours – from cool whites and greys to warm and softer wood tones.



Plank size
100 x 25 cm

Please note that ratings only apply when installed broadloom/brick bond in one colour.



Marmoleum Modular Lines **t3573** | trace of nature + **t5231** | Cliffs of Moher + **t5232** | rocky ice



t3575 | white cliffs LRV 57



t5232 | rocky ice LRV 44



t5226 | grey granite LRV 29



t3573 | trace of nature LRV 27



t5230 | white wash LRV 49



t5235 | North Sea coast LRV 32



t5225 | compressed time LRV 34



t5237 | black sheep LRV 18



t5231 | Cliffs of Moher LRV 17



t5218 | welsh moor LRV 8



t5217 | withered prairie LRV 23

Description	Linoleum tile
Dimensions (length x width)	EN-ISO 24342 100 x 25cm
Packaging per carton	3m ² (12 tiles)
Total thickness	EN-ISO 24346 2.5mm
Collection size	11
Application	EN-ISO 10874 Class 23/34/43
CE	EN 14041
Reaction to fire	EN 13501-1 C _s -s1
Slip resistance	EN 13893 DS: ≥0.30

Our recommended adhesives are 414 Euroflex Lino Plus and 646 Eurostar Premium. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

marmoleum® modular | textura



Textura: A succinct collection of 7 tones, each featuring either a wood grain or saw cut embossed finish to complement the design, Marmoleum Modular Textura can be used on it's own or alongside its Lines counterparts to add depth and texture to flooring concepts.


Plank size
100 x 25 cm




Marmoleum Modular Textura **te3573** | trace of nature

Description	Linoleum tile
Dimensions (length x width)	EN-ISO 24342 100 x 25cm
Packaging per carton	3m ² (12 tiles)
Total thickness	EN-ISO 24346 2.5mm
Collection size	7
Application	EN-ISO 10874 Class 23/34/43
CE	EN 14041
Reaction to fire	EN 13501-1 C _s -s1
Slip resistance	EN 13893 DS: ≥0.30

Our recommended adhesives are 414 Euroflex Lino Plus and 646 Eurostar Premium. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



te3573 | trace of nature



LRV 27 te5231 | Cliffs of Moher LRV 17



te5230 | white wash LRV 49



te5235 | North Sea coast LRV 32



te5217 | withered prairie LRV 23



te5229 | fresh walnut LRV 15



te5218 | Welsh moor LRV 8



Marmoleum Modular Textura **te5218** | Welsh moor

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.




Shade offers a collection of concrete structures in cool and warm greys as well as classic black and white, all designed to complement each other, while the embossed finish on Slate brings a contemporary finish to the design.



Marmoleum Modular Shade t3717 | Neptune

Tile sizes
50 x 25 cm
50 x 50 cm



t3722 | stardust LRV 59




t3711 | cloudy sand LRV 49



te3747 | Lakeland shale LRV 21



te3745 | Cornish grey LRV 15



te3725 | Welsh slate LRV 9



te3746 | Newfoundland slate LRV 11



Marmoleum Modular Slate te3745 | Cornish grey + te3725 | Welsh slate + te3747 | Lakeland shale

Description	Linoleum tile
Dimensions (length x width)	EN-ISO 24342 50 x 25cm / 50 x 50cm
Packaging per carton	5m ² (40 tiles) / 5m ² (20 tiles)
Total thickness	EN-ISO 24346 2.5mm
Collection size	10/4/8/11
Application	EN-ISO 10874 Class 23/34/43
CE	EN 14041
Reaction to fire	EN 13501-1 C ₁ -s1
Slip resistance	EN 13893 DS: ≥0.30

Our recommended adhesives are 414 Euroflex Lino Plus and 646 Eurostar Premium. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

OFF THE FLOOR MARMOLEUM COLLECTION




In addition to our standard ranges, we also offer a number of linoleum products developed for 'off the floor' functions.


bulletin board®

Pinboard linoleum, or Bulletin Board, offers a practical, simple solution to collect and exchange thoughts and ideas wherever people plan, create and meet. Simply share your thoughts by pinning your idea onto the wall.

Bulletin Board is an all natural material that can be applied in framed pin boards or directly onto the wall. Its surface is tactile and colourful, creating a decorative element in your space, in addition to being a practical aid in your day to day activity.



Bulletin Board 2162 | duck egg + 2166 | nutmeg spice + 2186 | blanched almond + 2210 | hot salsa



2206 | oyster shell LRV 43




2182 | potato skin* LRV 28



2187 | brown rice LRV 34



2212 | fresh pineapple LRV 40



2211 | tangerine zest LRV 20




2162 | duck egg LRV 25



2186 | blanched almond* LRV 34



2166 | nutmeg spice* LRV 22



2210 | hot salsa LRV 11



2213 | baby lettuce LRV 23



2204 | poppy seed LRV 16



2207 | cinnamon bark LRV 18




2202 | blue berry LRV 6



2209 | black olive LRV 5



2208 | mushroom medley LRV 21



2214 | blue berry LRV 6

Description	Bulletin Board
Dimensions	EN-ISO 24341 Roll width 1.22m *(3 items available in 1.83m) Roll length ≤ 28m
Total thickness	ISO 1765 6.0mm
Collection size	15
Force on pins - Perpendicular to pin direct LH000421	25 N (typical)
Force on pins - Perpendicular to pin at 7mm LH000421	10 N (typical)
Force on pins - Parallel to pin (pulling the pin out) LH000421	15 N (typical)

Our recommended adhesives are 414 Euroflex Lino plus and 530 Eurosafe Cork. Full technical specifications are available at www.forbo-flooring.co.uk/downloads Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

furniture linoleum | desktop




Forbo's Furniture Linoleum Desktop is a natural surfacing material that delivers the finishing touch for all high end 3D furniture designs such as desks, chairs, stools, cabinets, doors and displays. The material is flexible and can be applied as a surface on all kinds of constructions. Furniture Linoleum is renowned for its elegance and durability, radiating high quality and finesse.



Bulletin Board 4184 | olive

Furniture Linoleum doesn't show finger marks




4176 | mushroom LRV 54



4132 | ash LRV 23



4157 | pearl LRV 67



4183 | pistachio LRV 47



4182 | spring green LRV 47



4177 | vapour LRV 50



4185 | powder LRV 54




4155 | pewter LRV 12

Description	Linoleum sheet
Dimensions	EN-ISO 24341 Roll width 1.83m (2.0m - Nero only) Roll length ≤ 30m
Total thickness	ISO 1765 2.0mm
Collection size	21



4175 | pebble LRV 35



4184 | olive LRV 18



4164 | salsa LRV 9



4166 | charcoal LRV 6



4172 | mauve LRV 11



4174 | conifer LRV 7



4186 | orange blast LRV 22



4023 | nero LRV 5




4178 | iron LRV 8



4179 | smokey blue LRV 8



4154 | burgundy LRV 9



4181 | midnight blue LRV 9

LUXURY VINYL TILES

allura

Our Allura collection of luxury vinyl tiles (LVT) create realistic, natural looking floors (such as wood or stone) without the hazard of tripping or seams opening up, while offering the high-performing benefits of vinyl. It is also durable and easy to clean making it an ideal choice to combine the beauty of natural materials with the practicality required for a care environment.

Allura tiles are available in a wide range of designs and sizes as well as different formats and structures, including Allura Decibel acoustic LVT and the adhesive free Allura Click Pro, Allura Ease and Allura Puzzle products.

Dementia-friendly flooring check list



- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Allura 60305 | light honey oak + 62485 | taupe sand

ALLURA COLLECTION AT A GLANCE


allura dryback



The fully adhered version of our Allura luxury vinyl tiles portfolio, Allura Dryback offers the largest choice in colour, size, shape and design.




allura flex



With tackified installation and high quality dimensionally stable tiles, Forbo Allura Flex LVT delivers answers to many of today's key issues, such as limiting downtime, re-using floors and minimising environmental impact.



allura click pro



Allura Click Pro is a superb clickable design solution for areas up to 1000m².




allura puzzle



Forbo's Allura Puzzle vinyl tiles come in a unique puzzle-shaped 96 x 96cm size and are designed specially for adhesive free installation.




allura ease



Ideal for use across a wide range of applications and completely adhesive free, new Allura Ease is easy to install. It's also simple to remove, re-use and recycle.



allura decibel



Allura Decibel delivers excellent performance in dimensional stability and impact sound reduction (19 dB).



FIND THE RIGHT ALLURA COLLECTION FOR YOUR PROJECT

Every project is different and has its own specific demands. This can be in relation to the subfloor, the volume of traffic that passes through, or the size of the project. One thing is certain, we have the right solution in our Allura portfolio.

	SIZE OF AREA WITHOUT TRANSITION	IMPACT SOUND REDUCTION EN ISO 717-2	ADHESION	REMOVABILITY	SPEED OF INSTALL	PROPOSITION
Dryback	Unlimited	6 dB	Fully stuck	Low – fully bonded	Traditional speed	Widest choice of design
Flex	Unlimited	14 dB	Tackified	Removable	Fast	Perfect complement to carpet tiles and planks, no transition needed
Click Pro	<1000m ²	7 dB/15 dB in combination with Forbo underlay	None	Reusable	Fastest	No adhesive, ease of installation, DIY solution
Ease	<250m ²	7 dB	None	Reusable	Fastest	No adhesive, ease of installation, ultra fast refurbishment
Puzzle	<500m ²	7 dB	None	Reusable	Fastest	Simple no adhesive solution, ultra fast refurbishment in high traffic areas
Decibel	Unlimited	19 dB	Tackified	Removable	Fast	Removable acoustic solution without the need for 2 part installation process

HOW TO SPECIFY YOUR ORDER

The project requirements dictate which product is most suitable.

- DR7** – Allura dryback wear layer 0.70mm
- DR5** – Allura dryback wear layer 0.55mm
- DR4** – Allura dryback wear layer 0.40mm
- FL1** – Allura flex wear layer 1.0mm
- FL5** – Allura flex wear layer 0.55mm
- CL5** – Allura click pro wear layer 0.55mm
- EA7** – Allura ease wear layer 0.70mm
- PZ7** – Allura puzzle wear layer 0.70mm


The colourway numbers are mentioned below the sample. Add the code above as a suffix after the colourway number to specify your required format of the product. Items with multiple executions (size or shape) each have a different colourway number.

Please note that not all designs are available in every product construction.

Example:

When you want the grey waxed oak in Allura Flex with wear layer thickness 0.55 mm. Take the colourway number of grey waxed oak which is 63496 and add FL5 to the number.

This is how you would specify this example order:



UNDERSTANDING ALLURA

Throughout the Allura section you will see several letters and icons below each colourway, here we explain what these letters and icons mean.



bleached rustic pine **DR | FL | CL**
60084 | 120 x 20 cm |

EXAMPLE 1

(Taken from the Dryback section)

Bleached rustic pine is the colourway name

- 60084 is the colourway number
- This colourway is available in **Dryback** (DR), **Flex** (FL) and **Click Pro** (CL)
- The Dryback plank size is 120 x 20cm
- It has a 4 sided bevel
- It has in register embossing

THE SYMBOLS AND ABBREVIATIONS UNDER THE SAMPLES EXPLAINED:

2 or 4 sides bevelled

in register embossing

hungarian point size

natural colour variation

Circle Ø 40cm cut in 50 x 50cm tile to work with other colours. Only available in DR7.




grey waxed oak **DR | FL | CL | EA | PZ**
63496 | 100 x 15 cm |
63497 | HP 90 x 15 cm |
DR | FL

EXAMPLE 2

(Taken from the Dryback section)

Grey waxed oak is the colourway name

- 63496 is the colourway number
- This colourway is available in **Dryback** (DR), **Flex** (FL), **Click Pro** (CL), **Ease** (EA) and **Puzzle** (PZ) the Dryback plank size is 100 x 15cm with a 4 sided bevel
- 63497 is the same colourway but in **Hungarian Point**. The Dryback plank size is 90 x 15cm (The Flex plank size can be found in the Flex section)
- It has a 2 sided bevel




CORE COLLECTION SIZES

- New "slimmer" wood sizes in line with trend
- More combination/herringbone possibilities
- Large sizes possible thanks to product features
- Unique circle shape



allura wood

The Allura collection contains our largest range of wood designs including classic, contemporary and modern. The varieties offer excellent realism as they reflect the style and format of their natural inspiration, including the size and shape of the grain and plank.



white giant oak **60286** | 180 x 32 cm | **DR**
 natural giant oak **60284** | 180 x 32 cm | **DR | FL | CL | EA | PZ**
 grey giant oak **60280** | 180 x 32 cm | **DR | FL | CL | EA | PZ**



Tessera Cloudscape **3407** | april shower + Allura **60300** | central oak + Flotex planks **145009** | lava trident

DSDC Ratings:


- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.



whitened oak **60301** | 150 x 28 cm | **DR | FL | CL**
 light honey oak **60305** | 150 x 28 cm | **DR | FL | CL | EA**
 rustic anthracite oak **60306** | 150 x 28 cm | **DR | FL | CL | EA**



63402 | brown ash **63400** | light ash **63404** | smoked ash



light ash **63400** | 150 x 15 cm | **DR**
 smoked ash **63404** | 150 x 15 cm | **DR**
 brown ash **63402** | 150 x 15 cm | **DR**



classic timber **63416** | 150 x 15 cm | **DR**
 light timber **63414** | 150 x 15 cm | **DR**
 blond timber **63412** | 120 x 20 cm | **DR | FL | CL | EA**
63413 | 50 x 15 cm | **DR**
 bleached timber **63406** | 120 x 20 cm | **DR | FL | CL | EA**
63407 | 50 x 15 cm | **DR**
 greywashed timber **63408** | 120 x 20 cm | **DR | FL | CL | EA**
63409 | 50 x 15 cm | **DR**
 hazelnut timber **63410** | 120 x 20 cm | **DR | FL | CL**
63411 | 50 x 15 cm | **DR**



63414 | classic timber **63476** | burgundy **5754** Coral Brush straw brown

Description	Luxury vinyl tiles
Dimensions	50 x 15cm / HP 90 x 15cm 100 x 15cm / 120 x 20cm 150 x 28cm / 180 x 32cm
Packaging per carton (planks)	3.0m ² (40 pcs) / 4.5m ² (40 pcs) 3.0m ² (20 pcs) / 2.9m ² (12 pcs) 4.2m ² (10 pcs) / 4.6m ² (8 pcs)
Total thickness	ISO 1765 2.5mm
Thickness wear layer	ISO 24340/ EN 428 0.55mm / 0.7mm
Collection size	63
Application	EN 10874 0.55mm Class 33/42 0.7mm Class 34/43
CE	EN 14041
Reaction to fire	EN 13501-1 B _s -s1
Slip resistance	EN 13893 DS: ≥0.30

Key:
 = 4 sided bevelled = in-register embossing

Our recommended adhesives are 640 Eurostar Special, 543 Eurosafe Deco or 646 Eurostar Premium. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



63427 | light cement 63418 | petrified oak 63420 | burned oak



Scan here to view the full Allura technical specification

Only DSDC accredited products shown.
To see the full range, please visit www.forbo-flooring.co.uk

		
natural collage oak DR FL CL 60374 120 x 20 cm ↘	chocolate collage oak DR 60376 120 x 20 cm ↘	grey collage oak DR FL CL 60375 120 x 20 cm ↘



60085 | weathered rustic pine 60084 | bleached rustic pine

				
petrified oak DR FL CL 63418 120 x 20 cm ↘	burned oak DR FL CL 63420 120 x 20 cm ↘	bronzed oak DR 63422 120 x 20 cm ↘	natural seagrass DR FL CL 61255 100 x 15 cm ↘	oyster seagrass DR FL CL PZ 61253 100 x 15 cm ↘

				
bleached rustic pine DR FL CL 60084 120 x 20 cm ↘	natural rustic pine DR FL CL 60082 120 x 20 cm ↘	weathered rustic pine DR FL CL 60085 120 x 20 cm ↘	natural weathered oak DR 60187 150 x 28 cm ↘	anthracite weathered oak DR 60185 150 x 28 cm ↘

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

			
brown raw timber DR FL CL 60150 120 x 20 cm ↘	classic autumn oak DR FL CL 60353 100 x 15 cm ↘ 60354 HP 90 x 15 cm ↘ DR FL	white autumn oak DR FL CL 60350 100 x 15 cm ↘ 60351 HP 90 x 15 cm ↘ DR FL	grey autumn oak DR FL CL 60356 100 x 15 cm ↘ 60357 HP 90 x 15 cm ↘ DR FL

					
whitewash elegant oak DR FL 60064 120 x 20 cm ↘	honey elegant oak DR FL CL 60065 120 x 20 cm ↘	steamed oak DR FL CL 60293 120 x 20 cm ↘	pure oak DR FL CL 60295 120 x 20 cm ↘	light rustic oak DR 60078 120 x 20 cm ↘	black rustic oak DR FL CL 60074 120 x 20 cm ↘



60387 | charcoal solid oak



charcoal solid oak **DR**
60387 | 100 x 15 cm | 
60389 | HP 90 x 15 cm | 
grey waxed oak **DR | FL | CL | EA | PZ**
63496 | 100 x 15 cm | 
63497 | HP 90 x 15 cm | 
waxed oak **DR | FL | CL**
60063 | 100 x 15 cm | 
60055 | HP 90 x 15 cm | 
DR | FL


Key:  = 4 sided bevelled  = in-register embossing



60063 | waxed oak




63429 | iron cement 63427 | light cement 60375 | grey collage oak



light cement **DR | FL | CL**
63426 | 50 x 50 cm
63427 | 100 x 100 cm **DR | FL**
grey cement **DR | FL | CL | EA | PZ**
63430 | 50 x 50 cm
63431 | 100 x 100 cm **DR | FL**
iron cement **DR | FL | CL | EA | PZ**
63428 | 50 x 50 cm
63429 | 100 x 100 cm **DR | FL**
smoke cement **DR | FL | CL**
63432 | 50 x 50 cm
63433 | 100 x 100 cm **DR | FL**



Only DSDC accredited products shown.
To see the full range, please visit www.forbo-flooring.co.uk




mist texture **DR | FL | CL**
62534 | 50 x 50 cm
taupe texture **DR | FL | CL**
63438 | 50 x 50 cm
white sand **DR | FL | CL**
62488 | 50 x 50 cm | 
taupe sand **DR | FL | CL**
62485 | 50 x 50 cm | 
charcoal concrete **DR | FL | CL | EA | PZ**
62418 | 50 x 50 cm
62518 | 100 x 100 cm **DR | FL**
nero concrete **DR | FL | CL | EA | PZ**
62419 | 50 x 50 cm
62519 | 100 x 100 cm **DR | FL**



63427 | light cement


DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
For more information please see page 12.




silver stream **DR | FL | CL**
63776 | 50 x 50 cm
grey slate **DR**
62408 | 50 x 50 cm



63468 | grey stone





DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.



60293 | steamed oak

With tackified installation and high quality dimensionally stable tiles, Forbo Allura Flex LVT delivers answers to many of today's key issues, such as limiting downtime, re-using floors and minimising environmental impact. Allura Flex offers Allura Flex Wood, with a range of natural wood designs and Allura Flex Material, which delivers a selection of robust concretes and modern stones.



Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



grey autumn oak **60356** | 100 x 20 cm | 4-sided bevelled | DR | CL
60357 | HP 120 x 20 cm | DR
 classic autumn oak **60353** | 100 x 20 cm | 4-sided bevelled | DR | CL
60354 | HP 120 x 20 cm | DR
 white autumn oak **60350** | 100 x 20 cm | 4-sided bevelled | DR | CL
60351 | HP 120 x 20 cm | DR | FL
 bleached rustic pine **60084** | 120 x 20 cm | 4-sided bevelled | DR | CL
 natural rustic pine **60082** | 120 x 20 cm | 4-sided bevelled | DR | CL
 weathered rustic pine **60085** | 120 x 20 cm | 4-sided bevelled | DR | CL



oyster seagrass **61253** | 100 x 20 cm | DR | CL | PZ
 natural seagrass **61255** | 100 x 20 cm | 4-sided bevelled | DR | CL
 honey elegant oak **60065** | 120 x 20 cm | DR | CL | EA | PZ
 waxed oak **60063** | 100 x 20 cm | 4-sided bevelled | DR | CL
60055 | HP 120 x 20 cm | 2-sided bevelled | DR
 whitewash elegant oak **60064** | 120 x 20 cm | DR | CL | EA | PZ



brown raw timber **60150** | 120 x 20 cm | 4-sided bevelled | DR | CL
 grey waxed oak **63496** | 100 x 20 cm | 4-sided bevelled | DR | CL | EA | PZ
63497 | HP 120 x 20 cm | 2-sided bevelled | DR

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.


Key:
 4-sided bevelled
 in-register embossing

Description	Luxury vinyl tiles
Dimensions (tiles)	50 x 50cm / 100 x 100cm
Dimensions (planks)	100 x 20cm / 120 x 20cm HP 120 x 20cm / 150 x 28cm
Packaging per carton (tiles)	2.5m ² (10 pcs) 1.0m ² (1 pc)
Packaging per carton (planks)	2.0m ² (10 pcs) / 2.4m ² (10 pcs) 2.4m ² (12 pcs) / 2.52m ² (6 pcs)
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/ EN 428 1mm
Collection size	26
Application	EN 651 Class 34/42
CE	EN 14041
Reaction to fire	EN 13501-1 B _s -s1
Slip resistance	EN 13893 DS: ≥0.30


Our recommended adhesives are 640 Eurostar Special, 543 Eurosafe Deco or 646 Eurostar Premium. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk




63427 | light cement 63418 | petrified oak 63420 | burned oak




petrified oak **63418** | 120 x 20 cm | 4-sided bevelled | DR | CL
 burned oak **63420** | 120 x 20 cm | 4-sided bevelled | DR | CL
 black rustic oak **60074** | 120 x 20 cm | 4-sided bevelled | DR | CL



light cement **63426** | 50 x 50 cm | DR | CL
63427 | 100 x 100 cm | DR
 grey cement **63430** | 50 x 50 cm | DR | CL | EA | PZ
63431 | 100 x 100 cm | DR
 iron cement **63428** | 50 x 50 cm | DR | CL | EA | PZ
63429 | 100 x 100 cm | DR
 smoke cement **63432** | 50 x 50 cm | DR | CL
63433 | 100 x 100 cm | DR
 mist texture **62534** | 50 x 50 cm | DR | CL
 taupe texture **63438** | 50 x 50 cm | DR | CL



grigio concrete **62523** | 50 x 50 cm | DR | CL | EA | PZ
62513 | 100 x 100 cm | DR
 natural concrete **62522** | 50 x 50 cm | DR | CL | EA | PZ
62512 | 100 x 100 cm | DR
 charcoal concrete **62418** | 50 x 50 cm | DR | CL | EA | PZ
62518 | 100 x 100 cm | DR
 nero concrete **62419** | 50 x 50 cm | DR | CL | EA | PZ
62519 | 100 x 100 cm | DR
 taupe sand **62485** | 50 x 50 cm | 4-sided bevelled | DR | CL
 white sand **62488** | 50 x 50 cm | 4-sided bevelled | DR | CL




grey stone **63468** | 50 x 50 cm | DR | CL | EA | PZ



63776 | silver stream



silver stream **63776** | 50 x 50 cm | DR | CL



nickel metal brush **63625** | 50 x 50 cm | DR | CL | PZ

FAST FIT BY ALLURA

Part of our new Fast Fit collection, these adhesive free products are ideal for projects where reduced installation and downtime are essential.

For more information on the Fast Fit collection, please see page 100 or visit www.forbo-flooring.co.uk/fastfit

FASTFIT

Rapid, reusable flooring

allura click pro

CL

CLICK CONNECTED ADHESIVE FREE

- Clickable design solution for any single area without transition up to 1000m²
- Suitable for use with uneven subfloors and is genuinely adhesive free
- As part of Forbo's Fast Fit collection, it can reduce installation time by over 50%

allura puzzle

PZ

PUZZLE CONNECTED ADHESIVE FREE


- Puzzle solution for any single area without transition up to 500m²
- High traffic solution with strong puzzle connection
- Minimal subfloor preparation and quick to install
- Large tile format in Wood/Materials colourways that is ready to use immediately
- As part of Forbo's Fast Fit collection, it can reduce installation time by over 50%

allura ease

EA

ADHESIVE FREE

- Suitable for use across a wide variety of applications
- Easy to install but also to remove, re-use and recycle
- Adhesive free installation in any single area without transition up to 250m²
- As part of Forbo's Fast Fit collection, it can reduce installation time by over 50%




Description	Luxury vinyl tiles
Dimensions (tiles)	60 x 31.7cm
Dimensions (planks)	121.2 x 18.7cm / 150.5 x 23.7cm
Packaging per carton (tiles)	1.9m ² (10 pcs)
Packaging per carton (planks)	1.81m ² (8 pcs) / 2.14m ² (6 pcs)
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/ EN 428 0.55mm
Collection size	51
Application	EN 651 Class 33 / 42
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1, L, CS
Slip resistance	EN 13893 μ > 0.30

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk
 Key:
 = 4 sided bevelled
 = in-register embossing





Key:
 = 4 sided bevelled
 = in-register embossing
 = natural colour variation



Description	Luxury vinyl tiles
Dimensions (tiles)	60 x 31.7cm
Dimensions (planks)	121.2 x 18.7cm / 150.5 x 23.7cm
Packaging per carton (tiles)	1.9m ² (10 pcs)
Packaging per carton (planks)	1.81m ² (8 pcs) / 2.14m ² (6 pcs)
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/ EN 428 0.55mm
Collection size	51
Application	EN 651 Class 33 / 42
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, CS
Slip resistance	EN 13893 μ > 0.30


Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.



Description	Luxury vinyl tiles	
Dimensions	96 x 96cm	
Packaging per carton (tiles)	Tiles are delivered palletised	
Total thickness	ISO 1765	5mm
Thickness wear layer	ISO 24340/ EN 428	0.70mm
Collection size	18	
Application	EN 10874	Class 34 / 43
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1, L, NCS
Slip resistance	EN 13893	μ >0.30

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Description	Luxury vinyl tiles	
Dimensions	48 x 48cm / 120 x 19cm / 150 x 24cm	
Packaging per carton (tiles)	See page 95 for packaging information	
Total thickness	ISO 1765	5mm
Thickness wear layer	ISO 24340/ EN 428	0.70mm
Collection size	18	
Application	EN 10874	Class 34 / 43
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	μ >0.30

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Allura Decibel luxury acoustic vinyl tiles are made with passion for innovation, design and the environment. The balanced palette of 30 Wood and Material designs combines beautiful floor design with high performance and excellent acoustic properties of 19 dB.

The D3S core technology makes this the best dimensional stable flooring possible for this type of floor covering.

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.




8SL04 | silt slabstone

Description	Luxury vinyl tiles
Dimensions (tiles)	50 x 50cm, (1 x 1m on request)
Dimensions (planks)	100 x 16.6cm, 100 x 20cm, 120 x 20cm
Total thickness	ISO 1765 3.15mm, 4.00mm
Thickness wear layer	ISO 24340 EN 428 0.35mm, 0.80mm
Collection size	30
Acoustical Impact sound reduction	EN-ISO 717-2 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 C _f -s1, L, CS
Slip resistance	EN 13893 DS: ≥0.25

Our recommended adhesives are 640 Eurostar Special, 543 Eurosafe Deco or 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



8SL04 | silt slabstone 8IM03 | mortar imprint concrete 8MIM02 | iron imprint concrete



* metallic effect

GENERAL PURPOSE VINYL

As an excellent general purpose vinyl sheet, our Eternal range can help you transform your community spaces by delivering the natural look of a home with an easy to clean, highly practical surface.

Available in both muted realistic wood and stone designs, the Eternal collection creates a warm, welcoming space where residents will feel comfortable. Its high tech PVC wear layer and PUR Pearl finish also means it will keep its as-new appearance, even after many years of intensive use.

PUR Pearl & PUR wood Pearl

The majority of our Eternal designs feature Forbo's proven PUR Pearl lacquering protection technique. The technique for applying the lacquering layer ensures an even distribution of PUR Pearl on both the surface and in the deeper areas of the embossing. This helps to prevent the surface of Eternal becoming soiled and reduces maintenance costs.

Five items in the Eternal Wood range and seven items in the Eternal Material Concrete range are finished with a specific PUR Wood/Concrete embossing, offering the best possible performance on an all over wood/concrete design with integrated Pearl effect. The matt embossed lacquer layer ensures the highest level of both chemical and scuff resistance. Our Eternal de Luxe range delivers high design and exceptional embossing with the convenience of a sheet vinyl product.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



ETERNAL COLLECTION AT A GLANCE

eternal wood



The Eternal Wood collection contains a large variety of realistic wood designs and plank sizes, including some multi-width plank designs.



eternal material



A modern collection of metals and stones which create a soft, elegant look and feel.



eternal colour



From bold solid colours, to subtle colour gradients that run along the full width of a roll, Eternal Colour offers an inspiring choice of colour and design.



eternal de luxe



Offering the highest diversity in design and embossing on the market, Eternal de Luxe creates a inviting, comfortable atmosphere in any application area and is available in compact and 17 dB formats.



Visit the Eternal section on our website.




See all available technical downloads for Eternal.



The Eternal Wood collection contains a large variety of realistic wood designs and plank sizes, including some multi-width plank designs.

Please note: The measurement stated on each colourway is the size of the plank within the sheet.



Eternal Wood 11912 | whitewash oak



11912 | whitewashed oak 12.5 x 150cm

LRV 30



11952 | steamed oak 12.5 x 150cm

LRV 22



11932 | rustic oak* 12.5 x 150cm

LRV 20



11942 | dark grey oak* 12.5 x 150cm

LRV 12



Eternal Wood 12802 | elegant oak + Eternal Colour 40672 | ocean



12802 | elegant oak* 20 x 150cm

LRV 32



12832 | natural oak 20 x 150cm

LRV 27



12862 | grey oak* 20 x 150cm

LRV 25



13442 | light oak 16 x 150cm

LRV 33



13412 | shadow oak 16 x 150cm

LRV 20

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

Only DSDC accredited products shown.
To see the full range, please visit www.forbo-flooring.co.uk

*Also available in Step Safety vinyl



13932 | pale timber 20 x 150cm LRV 31



13802 | blond timber 20 x 150cm LRV 26



13942 | classic timber 20 x 150cm LRV 22



13922 | bleached timber 20 x 150cm LRV 36



13952 | greywashed timber 20 x 150cm LRV 23



Eternal Wood 13002 | silver concrete + 13952 | greywashed timber




11632 | light oak 16.7 x 75cm LRV 31



11652 | vintage oak 16.7 x 75cm LRV 26



10842 | cream oak 20 x 150cm LRV 44



10832 | hazelnut oak 20 x 150cm LRV 21



10852 | chocolate oak 20 x 150cm LRV 17

Please note: The measurement stated on each colourway is the size of the plank within the sheet.

*Also available in Step Safety vinyl



Eternal Wood 10232 | dark walnut



10322 | white chestnut* 25 x 150cm LRV 34



10362 | warm chestnut 25 x 150cm LRV 17



10342 | dark chestnut 25 x 150cm LRV 12

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

Description	Sheet vinyl
Dimensions	Roll width 2m Roll length 24-30 Im
Total thickness	EN ISO 24346 2.0mm
Thickness wear layer	EN ISO 24340 0.7mm
Collection size	31
Application	EN 10874 Class 34/43
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, NCS
Slip resistance	EN 13893 $\mu \geq 0.30$

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



11542 | traditional oak 25 x 150cm LRV 22



10232 | dark walnut 10 x 150cm LRV 18



11162 | tropical beech 6.7cm x variable LRV 28




11442 | washed beech 8 x 37.5cm LRV 28

eternal material



A modern collection of textiles, metals and stones which create a soft, elegant look and feel.



Description	Sheet vinyl
Dimensions	Roll width 2m Roll length 24-30 Im
Total thickness	EN ISO 24346 2.0mm
Thickness wear layer	EN ISO 24340 0.7mm
Collection size	30
Application	EN 10874 Class 34/43
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1, L, NCS
Slip resistance	EN 13893 $\mu \geq 0.30$


Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

*Available in Step Safety Vinyl

eternal colour



From bold solid colours, to subtle colour gradients that run along the full width of a roll, Eternal Colour offers an inspiring choice of colour and design.



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Description	Sheet vinyl
Dimensions	Roll width 2m Roll length 24-30 Im
Total thickness	EN ISO 24346 2.0mm
Thickness wear layer	EN ISO 24340 0.7mm
Collection size	35
Application	EN 10874 Class 34/43
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1, L, NCS
Slip resistance	EN 13893 $\mu \geq 0.30$

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

*Available in Step Safety Vinyl

eternal de luxe compact & 17 dB



The Eternal de Luxe range features fresh wood and stone designs, enhanced by authentic embossing structures that add even more realism to the designs. All the designs are available in a compact version and a decibel (17 dB impact sound reduction) format.



Eternal de Luxe 3047 decibel | 2867 compact | anthracite oak



3024 Decibel | grey pine
2894 Compact LRV 30



3026 Decibel | aged pine
2895 Compact LRV 21



Eternal de Luxe 2841 compact | 3051 decibel | dark wild oak



3142 Decibel | grey washed oak
2742 Compact LRV 31



3143 Decibel | coal oak
2743 Compact LRV 13



3141 Decibel | traditional oak
2741 Compact LRV 21



Eternal de Luxe 2856 compact | 3016 decibel | light honey oak



3016 Decibel | light honey oak
2856 Compact LRV 36



3018 Decibel | whitewashed oak
2858 Compact LRV 37



3019 Decibel | shadow oak
2859 Compact LRV 17

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

In-register embossing




3153 decibel | 2733 compact | light concrete tile

In-register embossing



3111 Decibel | light neutral grey
2781 Compact LRV 25



3112 Decibel | mid neutral grey
2782 Compact LRV 14



3174 Decibel | iced stream
2764 Compact LRV 36



3153 Decibel | light concrete tile
2733 Compact LRV 25



3194 Decibel | black metal
2724 Compact LRV 12




3113 Decibel | dark neutral grey
2783 Compact LRV 9



3176 Decibel | silver stream
2766 Compact LRV 22



3155 Decibel | dark concrete tile
2735 Compact LRV 17



3299 Decibel | charcoal tile
2799 Compact LRV 5

Description	Sheet vinyl
Dimensions	Roll width 2/4m Roll length ±25m
Total thickness	EN ISO 24346 2.0mm (Compact) 3.0mm (Decibel)
Thickness wear layer	EN ISO 24340 0.7mm
Collection size	22
Impact sound reduction	EN ISO 717-2 Eternal de Luxe: ΔLw = 5dB Eternal de Luxe Decibel: ΔLw = 17dB
Application	EN 10874 34/43 (Compact), 33/42 (Decibel)
CE	EN 14041
Reaction to fire	EN 13501-1 B _f -s1, L, NCS
Slip resistance	EN 13893 μ ≥ 0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

SAFETY VINYL

In care facilities, slip resistance is of prime consideration in areas where water or spillages could affect underfoot safety. For residents, being able to use bathroom facilities without fear of slipping provides peace of mind.

Our safety flooring collection Step can reduce the risk of slip hazards in bathrooms, walk-in showers and wet rooms. With R10, R11, R12 and barefoot options, the Step collection offers guaranteed lifetime slip resistance across a variety of designs to create a safe and modern, yet homely aesthetic.

Step safety vinyl is available in natural wood and stone designs as well as various muted colours. The traditional shiny non-slip particles have also been replaced by matt crystals that do not reflect the light.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Surestep Wood 18832 | grey oak

HSE Compliance – Wet Pendulum Test ≥36

All Step floors are tested using the TRRL Pendulum test, the preferred test method of the HSE which is used to assess the slip resistance of a floor surface. Floors can be tested with different rubber sliders to assess either footwear or barefoot use. Using this test, a Pendulum test value (PTV) of ≥36 or higher is considered to offer a low slip risk.

Slip resistance testing is carried out using the Pendulum test in accordance with BS7976 Part 2 and UK Slip Resistance Group Guidelines. Using this test, a Pendulum Test Value (PTV) of ≥36 or higher is considered to offer a low potential for slip. Surestep, Safestep R11 and R12 products achieve Wet Pendulum Test Values of ≥36 for footwear applications. In addition, Surestep Laguna, Safestep Aqua and Surestep Star barefoot offer Wet Pendulum Test Values of ≥36 for barefoot use areas.



≥ 20 microns
surface roughness

≥ 36
Wet Pendulum

≥ 40
Wet Pendulum

≥ 50
Wet Pendulum

STEP COLLECTION AT A GLANCE

surestep® material



A concise mix of stone, textured and mineral structures add depth and refinement to the collection.



surestep® wood



Realistic natural designs provide a warm ambience to all areas. The Surestep Wood palette of 11 colourways contains our most popular bestselling colours alongside new abstract woods and all-over designs. 4 items feature our new PUR Wood Pearl embossing and 4 are available in a decibel construction.



surestep® laguna



This product combines barefoot and footwear slip resistance, for areas where both are likely and frequently to take place. Complying with the relevant norms for the application, Laguna is suitable for use in transition areas such as changing rooms and circulation areas.



safestep® aqua

This modern, organic design with a new and unique embossing shape is designed for barefoot (and soft soled shoes) areas. A flexible product, available across 8 colours, can easily be installed to meet the specific requirements of the wetroom sector.



surestep® decibel



A genuine Health and Safety Executive compliant safety floor, Surestep Decibel offers sustainable R10 slip resistance underfoot, beautiful designs and a 17 dB impact sound reduction.



Visit the Step section on our website.



See all available technical downloads for Step.

surestep® material




A concise mix of stone, textured and mineral structures add depth and refinement to the collection.

*4 colours of the Surestep Material range shown below are available with 17 dB impact sound reduction as Surestep Material decibel.



Surestep Material 17122 | cool concrete



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Description	Sheet safety vinyl	
Dimensions	Roll width 2m Roll length 20-27 lm	
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size	7	
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk




surestep® wood

Realistic natural designs provide a warm ambience to all areas. The Surestep Wood palette of 11 colourways contains our most popular best selling colours alongside new abstract woods and all-over designs. All the wood designs have a clear and sharp visual due to the use of the almost invisible 'Step Crystals', which also guarantee lifetime slip resistance. Four items also feature our new PUR Wood Pearl embossing.

*4 colours of the Surestep Wood range shown are available with 17 dB impact sound reduction as Surestep decibel.



Surestep Wood 18942 | natural oak



Description	Sheet safety vinyl	
Dimensions	Roll width 2m Roll length 20-27 lm	
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size	11	
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

step® safety vinyl achieves

≥ 36

Wet Pendulum



This product combines barefoot and footwear slip resistance, for areas where both are likely and frequently to take place. Complying with the relevant norms for this application, Laguna is suitable for use in transition areas such as changing rooms and circulation areas. The subtle, soil hiding design is available in 15 colourways, offering a clean and fresh look. Suitable for wheelchair use.



Surestep Laguna's plain and non-reflective decoration makes it ideal for use in dementia applications. Visit www.forbo-flooring.co.uk/care for more information.

Description	Sheet safety vinyl	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length 20-27 lm
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size	15	
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESb/ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Surestep Laguna 181692 | mouse



Surestep Laguna 181802 | lemon + 181912 | flamingo + 181982 | aquamarine




Safestep Aqua

This modern, organic design with a new and unique embossing shape is designed for barefoot (and soft soled shoes) areas. A flexible product, available across 8 colours, Safestep Aqua can easily be installed to meet the specific requirements of the wetroom sector. The clean and modern collection meets the hygienic and aesthetic requirements of application areas such as bathrooms and swimming pool surrounds. Suitable for wheelchair use.



Safestep Aqua 180232 | taupe + 180482 | griege



Description	Sheet safety vinyl	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length 20-27 lm
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size	8	
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESb (Aqua)
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 55	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.


surestep® decibel 17 dB



A genuine Health and Safety Executive compliant safety floor, Surestep Decibel offers sustainable R10 slip resistance underfoot, and meets wet pendulum test values ≥ 36 (slider 96), beautiful designs and a 17 dB impact sound reduction.




Surestep Decibel 717122 | cool concrete + 718962 | whitewash oak



1b

718962 | whitewash oak

LRV 25



1b

717122 | cool concrete

LRV 37



1a

718802 | elegant oak

LRV 32



1b

717422 | beton concrete

LRV 28



2

718882 | classic oak

LRV 24



2

717482 | gravel concrete


LRV 15



1b

718972 | rustic oak

LRV 18



2

717172 | black concrete


LRV 8

Description	Sheet safety vinyl
Dimensions	Roll width 2/4m Roll length 20-27 lm
Total thickness	ISO 1765 3.0mm
Thickness wear layer	EN-ISO 24340 0.7mm
Collection size	12
Application	EN 10874 Class 34/42
Slip resistance	EN 13845 Annex C ESf DIN 51130 R10
	TRRL Pendulum – Wet test – slider 96 ≥ 36
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1
Slip resistance	EN 13893 DS: ≥ 0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.



Surestep Decibel 717422 | beton concrete + 718802 | elegant oak

HOMOGENEOUS PROJECT VINYL

Our Sphera homogeneous flooring is a superb flooring choice for care facilities. Not only is it extremely durable, but it also boasts a SMART-top surface finish with a high resistance to chemicals, scratches and stains. It's also 100% phthalate free and has very low emissions, helping to ensure excellent indoor air quality.

Sphera is available in two ranges: Sphera Element offers a sophisticated palette of 62 colours, many of which offer high LRVs, while, Sphera SD delivers static dissipative properties in homogeneous vinyl sheet format.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Sphera Element 50045 | jade

SPHERA COLLECTION AT A GLANCE

sphera® element



Sphera Element offers a fresh, light and contemporary colour palette which adds a sophistication to floor design. The collection includes warm and cool neutrals which complement interior finishes such as wood and stone along with pastels and bright accent colours for areas requiring way-finding or zoning.



82

sphera® SD



Sphera SD is a durable homogeneous vinyl sheet collection, specifically designed to control static discharge and particle emission in sensitive areas in industrial, pharmaceutical and healthcare facilities.



84



Visit the Sphera section on our website.



See all available technical downloads for Sphera.

Sphera Element offers a fresh, light and contemporary colour palette which adds a sophistication to floor design. The collection includes warm and cool neutrals which complement interior finishes such as wood and stone along with pastels and bright accent colours for areas requiring way-finding or zoning.

Please note: Pre-formed inner and outer corner pieces are also available for all Sphera colours. For more information, please visit www.forbo-flooring.co.uk/sphera

Description	Homogeneous sheet vinyl	
Dimensions	ISO 24341/ EN 426	Roll width 2.0m Roll length ≤ 25m
Total thickness	ISO 24340/ EN 428	2.0mm
Binder content	ISO 24340/ EN 429	Type 1: binder
Surface finish	SMART top	
Collection size	62	
Application	EN 10874	Class 34/43
Dimension stability	ISO 23999	≤ 0.2%
Abrasion resistance	EN 660-2	Group T
CE	EN 14041	0200301-DoP-605
Reaction to fire	EN 13501-1	B ₁ -s1
Slip resistance	EN 13893	D5 - μ ≥ 0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Sphera Element 50051 | butter + 50053 | sun

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

Sphera SD is Forbo's homogeneous vinyl collection with conductive properties in sheet format. Offering the best solution for sensitive areas where a durable floor is required, providing permanent ESD control and ensuring the highest hygienic properties.

The collection is specifically designed to control static discharges and particle emission in the most sensitive environments, such as pharmaceutical, MedTech and healthcare facilities.

WHY CHOOSE SPHERA SD?

Dissipative (SD) properties which comply with all ESD standards

Sphera SD complies with all relevant ESD standards for flooring, as described in IEC 61340-5-1 and ANSI/ESD S20.20.

The conductive (black) backing is suitable for a mixed adhesive application, with conductive adhesive only required to affix the copper strips

This installation option can reduce installation costs and lower risks of installation errors.

Guaranteed performance regardless the humidity level of the area

Many SD products on the market are based on additives, which only function with relative humidity (RH) levels above 40%. Sphera SD is designed with a dissipative material which is proven to be a permanent solution, even as low as 12% RH.

The sheet format of Sphera SD ensures the highest hygienic properties


In combination with market leading dimensional stability ($\leq 0.20\%$) seams stay hygienic and stable over time.

Sphera SD contains extremely low TVOC and particle emissions


TVOC emissions are $\leq 0.01 \text{ mg/m}^3$ which is in line, or better, than comparable products. Particle emission is ISO cleanroom class 6 for Sphera SD, good enough for most application areas.




Sphera SD 550000 | white



SD 550000 | white



SD 550017 | ivory



SD 550007 | grey sky


Smart control ⚡ surface treatment resists stains and scratches

Permanent dissipative properties which comply with all ESD standards

No need for conductive adhesive underneath the full sheet, only to affix the copper strip

Extremely low emissions and outgassing

Performs regardless of the humidity level of the area



Sheet format requires less welding, ensuring the highest hygienic properties

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.

Description	Homogeneous sheet vinyl	
Dimensions	ISO 24341	Roll width 2.0m Roll length $\leq 27\text{m}$ $\sim 26\text{m}$
	EN-ISO 24346	2.0mm
Total thickness	EN-ISO 10581	Type 1
Binder content	SMART top	
Surface finish	3	
Collection size	EN 10874	Class 43
Application	ISO 23999	$\leq 0.4\%$ $\sim 0.2\%$
Dimension stability	EN 13501-1	B _f -s1, G, NCS
Reaction to fire	EN 13893	$\mu \geq 0.30$
Slip resistance	EN 12524	0.25 W/m ² K
Thermal conductivity	EN 1815	$\leq 2 \text{ kV}$
Body voltage	EN 1081	$1 \times 10^6 \leq R \leq 10^9 \Omega$
Electrical behaviour – static dissipative		

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

THE ACOUSTIC COLLECTION

ACOUSTIC FLOORING SOLUTIONS

Communal areas of care homes can be noisy places. Minimising noise is key to reducing stress and promote the comfort and wellbeing of residents.

Our acoustic ranges, available in 14 dB to 19 dB versions and in a range of design options, absorbs impact sound to create a calmer environment.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme

sarlon® modul'up®

In the Acoustic Collection, we have brought together two of our most successful sheet vinyl ranges, Sarlon and Modul'up, to provide one cohesive offer of 94 designs in three formats. Every design in this collection is offered in the following three formats: Sarlon 15 dB, Sarlon 19 dB and Modul'up 19 dB.



88

marmoleum® acoustic 14 dB

A small collection of 6 colourways available with 14 dB impact sound reduction.



94

marmoleum® decibel 18 dB

Providing impact sound reduction of 18 dB, this linoleum collection is available in 27 colourways.



95

ACOUSTIC PRODUCTS AT A GLANCE

eternal de luxe decibel 17 dB



The Eternal de Luxe decibel range features fresh wood and stone designs, enhanced by authentic embossing structures that add even more realism to the designs. All the designs offer 17 dB impact sound reduction.



96

surestep® decibel 17 dB



A genuine Health and Safety Executive compliant safety floor, Surestep Decibel offers sustainable R10 slip resistance underfoot, beautiful designs and a 17 dB impact sound reduction.



98

allura decibel 19 dB



A collection of 30 LVT tiles and planks available with 19 dB impact sound reduction.



100

novilon® viva

Novilon Viva is a tough and durable cushion vinyl flooring that is easy to clean, sound absorbing and is warm underfoot.



102







Visit the Acoustic section on our website.



See all available technical downloads for Acoustic.

Wood

The Wood range consists of a nice variety of relevant wood designs and colours, including the new Chill Oak design with a realistic colour variation within the planks. A design statement is the Hybrid Wood Concrete design; combining herringbone wood with concrete planks in a repeat of 300 x 200cm, combining well with wood and concrete designs.









 1b	 2	 1b	 1b
8513 blond chill oak LRV 29	8514 pure chill oak LRV 27	8512 smoked chill oak LRV 25	8483 scandinavian oak LRV 32
 1b	 1b	 1b	 1b
8413 natural oak LRV 32	8421 polar oak LRV 39	8412 grey silver oak LRV 26	8420 clay oak xl LRV 23
 1b	 2	 2	
8422 carbon oak xl LRV 16	8224 brown rustic oak LRV 11	8229 burned charcoal rustic oak LRV 9	
 1b			
121 grey linea LRV 36			
 2			
132 charcoal linea LRV 17			

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk







Material

The Material range presents a modern range of designs based on popular flooring materials like cement, concrete, stones and textiles. Nairobi and Canvas are textile weave effects with different scale and sophistication levels, both very suitable for shading combinations where low contrast is required. Cement and concrete designs are widely appreciated and used.

 1b	 2	 2	
651 silver slabstone LRV 44	659 mercury slabstone LRV 28	573 clay cement LRV 41	
 2	 2	 1b	 1b
572 medium grey cement LRV 25	579 slate cement LRV 15	303 sand nairobi LRV 26	304 taupe nairobi LRV 13
 1b	 1b	 1b	 1b
302 light grey nairobi LRV 30	312 anthracite nairobi LRV 22	307 pastel blue nairobi LRV 40	337 indigo blue canvas LRV 15
 1b	 1b		
332 light grey canvas LRV 20	339 brown canvas LRV 13		
 1b	 1b		
342 natural grey canvas LRV 26	333 warm sand canvas LRV 28		
 1b	 1b	 2	 2
713 peanut concrete LRV 28	771 silver concrete LRV 28	761 steel concrete LRV 16	742 pewter concrete LRV 12






Colour

The Colour range presents uni and fine textured all-over designs. The designs Uni and Stardust have a coloured wearlayer. This gives an intense deep colour effect. The range reflects the latest developments in colour trends and is easy to combine with almost all designs in the total range. A colourful statement of positivity is the playful Color Splash design. This organic, daring, colourful design consists of 24 colours and has a repeat of 600 x 200cm.



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

200 | ivory canyon | LRV 50 | 211 | light grey canyon | LRV 34 | 212 | grey canyon | LRV 27 | 235 | lemon canyon + 406 | red doodle



863 | beige grey uni | LRV 39 | 862 | stone grey uni | LRV 27 | 869 | charcoal uni | LRV 13 | 9608 | green graphito + 878 | dark green uni + 235 | lemon canyon


Colour



Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk




4803 | vanilla stardust + 307 | pastel blue nairobi



4808 | soft pistache stardust LRV 69 4818 | lime stardust LRV 70 4817 | soft blue stardust LRV 61 4827 | deep blue stardust LRV 24



4804 | copper stardust + 4806 | soft peach stardust



4801 | silver stardust LRV 35 4805 | golden stardust LRV 52 4804 | copper stardust LRV 20

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.




761 | steel concrete + 4804 | copper stardust

marmoleum® acoustic 14 dB



Marmoleum Acoustic has a total thickness of 4mm and reduces impact sound by 14 dB (ISO 717-2).

It is a twinlayer linoleum built up from 2mm of Marmoleum and 2mm Corkment backing. Using Marmoleum Acoustic reduces installation costs as it can be installed in one go, avoiding the need to first lay Corkment and then Marmoleum. Marmoleum Acoustic is available in six colours.



33048 | graphite LRV 14



33032 | mist grey LRV 42



33252 | sparrow LRV 29



33139 | lava LRV 9




33055 | fresco blue LRV 23



33038 | Caribbean LRV 55



1200 | corkment



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 32 lm
Total thickness	ISO 1765	4.0mm
Collection size	6	
Application	EN 1307	Class 23/33/41
Acoustical impact noise reduction	≤ 14 dB	
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

marmoleum® decibel 18 dB



Marmoleum Decibel is 3.5mm thick and provides an impact sound reduction of 18 dB. The acoustic performance is achieved by laminating 2.5mm Marmoleum onto a 1mm thick layer of polyolefin foam.

Marmoleum Decibel is also available in all Marmoleum colours as a made-to-order item with an 18 dB impact sound rating. Please note that minimum order quantities and lead times will apply. Please contact Forbo Customer Service for more details.

Description	Linoleum sheet	
Dimensions	EN-ISO 24341	Roll width 2.0m Roll length ≤ 32 lm
Total thickness	ISO 1765	3.5mm
Collection size	27	
Application	EN 1307	Class 23/33/41
Acoustical impact noise reduction	≤ 18 dB	
CE	EN 14041	
Reaction to fire	EN 13501-1	C _s -s1
Slip resistance	EN 13893	DS: ≥0.30

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



 3860 silver shadow LRV 48	 372435 orbit LRV 37	 371135 cloudy sand LRV 49	 312035 rosato LRV 51	 322535 dandelion LRV 46	 18dB
 262135 dove grey LRV 36	 370835 fossil LRV 34	 324635 shrike LRV 21	 303835 Caribbean LRV 55	 374135 yellow glow LRV 58	
 314635 serene grey LRV 27	 370635 beton LRV 28	 370935 silt LRV 22	 305335 dove blue LRV 23	 374335 red glow LRV 14	 312735 Bleeckerstreet LRV 9
 304835 graphite LRV 14	 372335 nebula LRV 17	 356835 delta lace LRV 13	 374235 green glow LRV 39	 322435 chartreuse LRV 38	
 387235 volcanic ash LRV 10	 370735 black hole LRV 7	 303035 blue LRV 12			

eternal de luxe decibel 17 dB



The Eternal de Luxe Decibel range features fresh wood and stone designs, enhanced by authentic embossing structures that add even more realism to the designs. The collection offers superior underfoot comfort, excellent residual indentation and 17 dB impact noise reduction properties.



Eternal de Luxe Decibel 3024 | grey pine



3024 | grey pine



LRV 30

3026 | aged pine

LRV 21

In-register embossing



Eternal de Luxe Decibel 3016 | light honey oak



3016 | light honey oak

LRV 36



3018 | whitewashed oak

LRV 37



3019 | shadow oak

LRV 17



3142 comfort | grey washed oak

LRV 31



3143 comfort | coal oak

LRV 13



3141 comfort | traditional oak

LRV 21



3153 decibel | light concrete tile



3111 comfort | light neutral grey

LRV 25




3112 comfort | mid neutral grey

LRV 14



3174 comfort | iced stream

LRV 36




3153 comfort | light concrete tile

LRV 25



3194 comfort | black metal

LRV 12



3113 comfort | dark neutral grey

LRV 9



3176 comfort | silver stream

LRV 22



3155 comfort | dark concrete tile

LRV 17



3299 comfort | charcoal tile

LRV 5

In-register embossing

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

Description	Sheet vinyl
Dimensions	Roll width 2/4m Roll length ±25m
Total thickness	EN ISO 24346 3.0mm
Thickness wear layer	EN ISO 24340 0.7mm
Collection size	22
Impact sound reduction	EN ISO 717-2 ΔLw = 17dB
Application	EN 10874 33/42
CE	EN 14041
Reaction to fire	EN 13501-1 B _s -s1, L, NCS
Slip resistance	EN 13893 μ ≥0.30

Our recommended adhesives are 540 Eurosafe Special and 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.com
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

surestep® decibel 17 dB



A genuine Health and Safety Executive compliant safety floor, Surestep Decibel offers sustainable R10 slip resistance underfoot, and meets wet pendulum test values ≥ 36 (slider 96), beautiful designs and a 17 dB impact sound reduction.



Surestep Decibel 718962 | whitewash oak



718802 | elegant oak

LRV 32



718962 | whitewash oak

LRV 25



718882 | classic oak

LRV 24




718972 | rustic oak

LRV 18



Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.com
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



717122 | cool concrete

LRV 37



717422 | beton concrete

LRV 28



717482 | gravel concrete

LRV 15



717172 | black concrete

LRV 8



Surestep Decibel 717122 | cool concrete

Description	Sheet safety vinyl	
Dimensions	Roll width 2/4m Roll length 20-27 lm	
Total thickness	ISO 1765	3.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size	12	
Application	EN 10874	Class 34/42
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥ 0.30

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.

allura decibel 19 dB



Allura Decibel luxury acoustic vinyl tiles are made with passion for innovation, design and the environment. The balanced palette of 30 Wood and Material designs combines beautiful floor design with high performance and excellent acoustic properties of 19 dB.

The D3S core technology makes this the best dimensional stable flooring possible for this type of floor covering.




Description	Luxury vinyl tiles
Dimensions (tiles)	50 x 50cm, (1 x 1m on request)
Dimensions (planks)	100 x 16.6cm, 100 x 20 cm, 120 x 20cm
Total thickness	ISO 1765 3.15mm, 4.00mm
Thickness wear layer	ISO 24340 EN 428 0.35mm, 0.80mm
Collection size	30
Acoustical Impact sound reduction	EN-ISO 717-2 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 C _s -s1, L, CS
Slip resistance	EN 13893 DS: ≥0.25

Our recommended adhesives are 640 Eurostar Special, 543 Eurosafe Deco or 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.




* metallic effect



Novilon Viva is a tough and durable cushion vinyl flooring that is easy to clean, sound absorbing and is warm underfoot.

AQUA GRIP
DIAMOND SEAL
NOVI CLEAN



5459 | brown oak



5444 | hazelnut timber




5432 | natural oak




6154 | warm walnut



5441 | brown timber



5823 | dark chestnut



5434 | weathered oak

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.



Novilon Viva 5432 | natural oak



5442 | light timber



5788 | limed oak



5457 | bright oak



5822 | light chestnut



5458 | classic oak



5430 | pale oak



5712 | warm patchwood



5669 | warm concrete



5443 | grey timber



5785 | warm greywash oak



5620 | dark spotted tile



5621 | light spotted tile



5632 | grey cement tile




5607 | light neutral grey




7362 | dark grey



5631 | smoked cement tile



5602 | mid neutral grey



6517 | grey



Novilon Viva Tile 5631 | smoked cement tile

Description	Cushioned vinyl sheet
Dimensions	Roll width 200 / 300 / 400cm Roll length ≤ 30m
Total thickness ISO 24346	2.4mm
Thickness wear layer ISO 24340	0.25mm
Collection size	16
Impact sound reduction	EN ISO 717-2 ΔLw = 17 dB
Application	EN 10874 Class 23/31
CE	EN 14041
Reaction to fire	EN 13501-1 B _s -s1, G, CS
Slip resistance	EN 13893 Class DS

Our recommended adhesive is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/consumerdownloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

UNDER CONTROL

COMPLETE ESD FLOORING SOLUTIONS

Our Electrostatic Discharge (ESD) collection delivers advanced technical flooring systems designed specifically to control static discharge in areas with sensitive medical equipment.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme




sphera® SD




Sphera SD is Forbo's homogeneous vinyl collection with conductive properties in sheet format. Offering the best solution for sensitive areas where a durable floor is required, providing permanent ESD control and ensuring the highest hygienic properties.

DSDC Ratings:


- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.



SD 550000 | white LRV 65



SD 550017 | ivory LRV 62



SD 550007 | grey sky LRV 59



Rated 1b as the speckles within the pattern are very close tonally to the background. A more subtle natural dappled effect with less contrast across the design. When viewed in mono setting (where hue is removed) the sample looks almost plain.

Description	Homogeneous sheet vinyl	
Dimensions	ISO 24341	Roll width 2.0m Roll length ≤ 27m ~ 26m
Total thickness	EN-ISO 24346	2.0mm
Binder content	EN-ISO 10581	Type 1
Surface finish	SMART top	
Collection size	3	
Application	EN 10874	Class 43
Dimension stability	ISO 23999	≤ 0.4% ~ 0.2%
Reaction to fire	EN 13501-1	B ₁ -s1, G, NCS
Slip resistance	EN 13893	μ ≥ 0.30
Thermal conductivity	EN 12524	0.25 W/m·K
Body voltage	EN 1815	≤ 2 kV
Electrical behaviour – static dissipative	EN 1081	1 x 10 ⁶ ≤ R ≤ 10 ⁸ Ω

Our recommended adhesive is 640 Eurostar Special. When fitting the copper tape, our recommended adhesive is 641 Eurostar Special EL. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Visit the Under Control section on our website.



See all available technical downloads for Under Control.

FAST FIT

Our Fast Fit Flooring collection of adhesive free products includes entrance systems and interior flooring ranges in tile, sheet and plank formats for maximum flexibility. All our Fast Fit products are perfect for refurbishments in care facilities where speed of installation and minimal disruption is essential.

With no adhesive used, there's no need to wait 48 hours for the floor to cure so our Fast Fit Flooring can be walked on immediately after installation. There is also minimal dust and no lingering odours for improved wellbeing for residents and staff.



Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme


Reduce installation*
times by over

50%

Save over

20%

when using
Modul'up*



Quick

- Minimal disruption and downtime as a Fast Fit installation can save over 50% of downtime if a new subfloor is not needed
- No need to apply adhesive, so quicker for contractor to install and no drying times
- Floor is ready for immediate use after installation, no need to wait 48 hours before using with heavy traffic

Easy

- None of the usual adhesive constraints such as drying times, lingering odours or the possibility of adhesive failure
- Less dust, mess and a reduced environmental impact as no adhesive
- Easy to uplift and reuse, or remove and recycle at end of life as no adhesive residue on back of the material

Economical

- A Fast Fit installation can reduce downtime by over 50% if a new sub-floor is not needed, thereby saving you significant money
- Potential savings on future renovations as no costly subfloor preparation required on removal

*Cost and time savings are compared to the use of standard, glued down products.

FAST FIT COLLECTION AT A GLANCE


coral® click

Coral Click is an exceptionally versatile 'off the shelf' modular matting system that can be assembled on site.



modul'up® 19 dB modul'up® compact

Modul'up is a proven adhesive free floor covering suitable for high traffic applications. Both Modul'up compact and modul'up 19 dB are available in 94 colours across 4 design families.




modul'up® T.E.

A quick and easy to install solution for damp subfloors with up to 97% RH. Featuring our Aquablock back layer embossing, Modul'up T.E. allows the subfloor to breathe and moisture to dissipate.



allura click pro

Allura Click Pro is a superb clickable design solution for areas up to 1000m².




allura puzzle

Forbo's Allura Puzzle vinyl tiles come in a unique puzzle-shaped 96 x 96cm size and are designed specially for adhesive free installation.



allura ease


Ideal for use across a wide range of applications and completely adhesive free, new Allura Ease is easy to install. It's also simple to remove, re-use and recycle.



FAST FIT ENTRANCE coral® click

The first steps in protecting your building.

Coral Click is an exceptionally versatile 'off the shelf' modular matting system that can be assembled on site. Coral Click can be used on its own or in conjunction with our Coral clean-off textile ranges to provide an integrated entrance system.



DSDC Ratings:

1a: Used widely as part of a holistic scheme.

1b: Used throughout as long as it is coordinated with other elements.


2: Used with caution.

For more information please see page 12.


This versatile PVC tile with Coral Brush inserts can be used in all types of buildings and, because it contains no metal components, Coral Click entrance products are particularly suitable for installation in retail environments as they do not interfere with electronic-tagging systems.



- 'Off the shelf' modular matting system
- Exceptionally easy to fit, handle and store
- Available in 12mm & 17mm depths
- Textile inserts from the award winning Coral Brush collection
- Coral Brush insert is produced using 100% Econyl® regenerated yarn
- Coral Entrance flooring systems removes up to 95% of dirt and moisture from shoes and wheeled traffic
- 5 year guarantee



7833 (12mm) | 7883 (17mm)



7837 (12mm) | 7887 (17mm)


Description	Modular matting system	
Dimensions	24 x 24cm	
Total thickness	ISO 1765	11/16mm (without textile insert) 14/19mm (with Coral Brush insert)
Pile material	100% regenerated Econyl® Nylon	
Collection size	2	
Application	EN 1307	Class 33
CE	EN 14041	

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Wood

The Wood range consists of a nice variety of relevant wood designs and colours, including the new Chill Oak design with a realistic colour variation within the planks. A design statement is the Hybrid Wood Concrete design; combining herringbone wood with concrete planks in a repeat of 300 x 200cm, combining well with wood and concrete designs.



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

Material


Cement and concrete designs are widely appreciated and used and the range now also includes subtle metallic Slabstone, natural lively stone Stromboli and hybrid Dissolved Stone concrete/stone effects.





Colour

The Colour range presents uni and fine textured all-over designs. The designs Uni and Stardust have a coloured wearlayer. This gives an intense deep colour effect. The range reflects the latest developments in colour trends and is easy to combine with almost all designs in the total range. A colourful statement of positivity is the playful Color Splash design. This organic, daring, colourful design consists of 24 colours and has a repeat of 600 x 200cm.



267 | cobalt blue canyon LRV 42



248 | lime green canyon LRV 49



235 | lemon canyon LRV 60



235 | lemon canyon + 406 | red doodle




223 | sand canyon LRV 53

DSDC Ratings:


- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.




223 | sand canyon + 409 | black & white doodle



200 | ivory canyon LRV 50



211 | light grey canyon LRV 54



212 | grey canyon LRV 27

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown.
To see the full range, please visit www.forbo-flooring.co.uk



868 | lime uni LRV 48



878 | dark green uni LRV 14



867 | blue uni LRV 17



877 | dark blue uni LRV 6



865 | yellow uni LRV 61



866 | mandarine uni LRV 33




876 | orange uni LRV 22




886 | red uni LRV 13



9608 | green graphito + 878 | dark green uni + 235 | lemon canyon



863 | beige grey uni LRV 39



862 | stone grey uni LRV 27



869 | charcoal uni LRV 13



Colour



4807 | lilac stardust



4803 | vanilla stardust




4806 | soft peach stardust


Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown.
To see the full range, please visit www.forbo-flooring.co.uk



4803 | vanilla stardust + 307 | pastel blue nairobi



4808 | soft pistache stardust



4818 | lime stardust




4817 | soft blue stardust




4827 | deep blue stardust



4804 | copper stardust + 4806 | soft peach stardust



4801 | silver stardust



4805 | golden stardust



4804 | copper stardust

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
For more information please see page 12.



761 | steel concrete + 4804 | copper stardust



PERFECT SOLUTION FOR DAMP SUBSTRATES

A 2-IN-1 SOLUTION

Modul'up T.E. offers two solutions in one floor covering; the benefits of adhesive free vinyl and the possibility of installing onto existing damp subfloors, without an effective DPM, and with a residual moisture content up to 97% RH (a ventilated skirting should be used in these circumstances).

It is the ideal solution for covering damp substrates or those subject to frequent damp problems.

EASY INSTALLATION & REMOVAL

- Quick to install and quick to remove
- No glue needed which means no odours and immediate use of the premises after installation
- Perfect solution for high traffic areas where indentation performance is key
- Can be installed over existing compact floor coverings
- Easy to reuse and recycle

HIGH PERFORMANCE AND COST-EFFECTIVE

- 25% cost saving during future renovations**
- Can reduce new-build programme times
- Flooring can be laid over most old floor surfaces, including asbestos†
- Subfloor is not damaged during refurbishment
- 'Overclean' protective finish for ease of cleaning and maintenance

QUICK AND COST-EFFECTIVE

- Modul'up T.E. is the quickest and most cost-effective solution
- Cost and time savings compared to the use of standard, glued down products

MODUL'UP SINGLE SIDED TAPE


This innovative single-sided tape system should only be used to support seams and joints as they are welded. However, there is no need to perimeter tape the room or door thresholds, delivering further time and cost savings.



* Depending on the substrate (flatness, joint width...)

** For more information please visit www.forbo-flooring.co.uk/modulupTE

† In accordance with applicable legislation. Contact Forbo Flooring Technical Services for specific advice.



1 Overclean protective finish for ease of cleaning and maintenance.

2 The backing of Modul'up T.E. benefits from the AQUABLOCK technology that ensures perfect ventilation of the substrate and evacuates moisture to the periphery of the room.

3 Ventilated skirtings

The moisture evacuated at the edges escapes via the grooves of the ventilated skirting.

A minimum clearance of 5 to 10mm between the floor covering and the wall is required with the use of a ventilated skirting.

In the absence of skirtings, it is necessary to leave a gap of 2 to 4mm.

VENTILATED SKIRTINGS – 5 available colours



Reduce installation time by over 50%



Save over 20% when using modul'up



Single product solution for damp floors



43T80473 | oak natural

1b




43T30001 | terra dove

1b



43T80421 | oak polar

1b



43T30771 | concrete silver

1b



43T80472 | oak silver

1b



43T30572 | cement grey

2



See page 12 for information on the DSDC ratings.

Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

FAST FIT BY ALLURA EXPLAINED

Allura Click Pro, Puzzle and Ease have been specifically devised for adhesive free installation. Not only are our tiles and planks easy and quick to install, they are also simple to remove, re-use and recycle.

ALLURA CLICK PRO	ALLURA PUZZLE	ALLURA EASE
		
<p>CL5</p> <p>Click connected adhesive free</p> <ul style="list-style-type: none"> • Clickable design solution for any single area without transition up to 1000m² • Suitable for use with uneven subfloors and is genuinely adhesive free • As part of Forbo's Fast Fit collection, it can reduce installation time by over 50% 	<p>PZ7</p> <p>Puzzle connected adhesive free</p> <ul style="list-style-type: none"> • Puzzle solution for any single area without transition up to 500m² • High traffic solution with strong puzzle connection • Minimal subfloor preparation and quick to install • Large tile format in Wood/Materials colourways that is ready to use immediately • As part of Forbo's Fast Fit collection, it can reduce installation time by over 50% 	<p>EA7</p> <p>Adhesive free</p> <ul style="list-style-type: none"> • Suitable for use across a wide variety of applications • Easy to install but also to remove, re-use and recycle • Adhesive free installation in any single area without transition up to 250m² • As part of Forbo's Fast Fit collection, it can reduce installation time by over 50%



 <p>natural giant oak DR FL EA PZ 60284 150 x 23.7 cm 4</p>	 <p>grey giant oak DR FL EA PZ 60280 150 x 23.7 cm 4</p>	 <p>whitened oak DR FL 60301 150 x 23.7 cm 4</p>	 <p>rustic anthracite oak DR FL EA 60306 150 x 23.7 cm 4</p>	 <p>light honey oak DR FL EA 60305 150 x 23.7 cm 4</p>																								
 <p>blond timber DR EA FL 63412 121.2 x 18.7 cm 4</p>	 <p>bleached timber DR EA FL 63406 121.2 x 18.7 cm 4</p>	 <p>greywashed timber DR EA FL 63408 121.2 x 18.7 cm 4</p>	 <p>hazelnut timber DR FL 63410 121.2 x 18.7 cm 4</p>	 <p>natural collage oak DR FL 60374 121.2 x 18.7 cm 4</p>																								
 <p>classic beech FL 60026 121.2 x 18.7 cm 4</p>	 <p>grey collage oak DR FL 60375 121.2 x 18.7 cm 4</p>	 <p>oyster seagrass DR FL PZ 61253 121.2 x 18.7 cm 4</p>	 <p>natural seagrass DR FL 61255 121.2 x 18.7 cm 4</p>	<table border="1"> <tbody> <tr> <td>Description</td> <td>Luxury vinyl tiles</td> </tr> <tr> <td>Dimensions (tiles)</td> <td>60 x 31.7cm</td> </tr> <tr> <td>Dimensions (planks)</td> <td>121.2 x 18.7cm / 150.5 x 23.7cm</td> </tr> <tr> <td>Packaging per carton (tiles)</td> <td>1.9m² (10 pcs)</td> </tr> <tr> <td>Packaging per carton (planks)</td> <td>1.81m² (8 pcs) / 2.14m² (6 pcs)</td> </tr> <tr> <td>Total thickness</td> <td>ISO 1765 5mm</td> </tr> <tr> <td>Thickness wear layer</td> <td>ISO 24340/ EN 428 0.55mm</td> </tr> <tr> <td>Collection size</td> <td>45</td> </tr> <tr> <td>Application</td> <td>EN 651 Class 33 / 42</td> </tr> <tr> <td>CE</td> <td>EN 14041</td> </tr> <tr> <td>Reaction to fire</td> <td>EN 13501-1 B_{fl}-s1, L, CS</td> </tr> <tr> <td>Slip resistance</td> <td>EN 13893 μ > 0.30</td> </tr> </tbody> </table>	Description	Luxury vinyl tiles	Dimensions (tiles)	60 x 31.7cm	Dimensions (planks)	121.2 x 18.7cm / 150.5 x 23.7cm	Packaging per carton (tiles)	1.9m ² (10 pcs)	Packaging per carton (planks)	1.81m ² (8 pcs) / 2.14m ² (6 pcs)	Total thickness	ISO 1765 5mm	Thickness wear layer	ISO 24340/ EN 428 0.55mm	Collection size	45	Application	EN 651 Class 33 / 42	CE	EN 14041	Reaction to fire	EN 13501-1 B _{fl} -s1, L, CS	Slip resistance	EN 13893 μ > 0.30
Description	Luxury vinyl tiles																											
Dimensions (tiles)	60 x 31.7cm																											
Dimensions (planks)	121.2 x 18.7cm / 150.5 x 23.7cm																											
Packaging per carton (tiles)	1.9m ² (10 pcs)																											
Packaging per carton (planks)	1.81m ² (8 pcs) / 2.14m ² (6 pcs)																											
Total thickness	ISO 1765 5mm																											
Thickness wear layer	ISO 24340/ EN 428 0.55mm																											
Collection size	45																											
Application	EN 651 Class 33 / 42																											
CE	EN 14041																											
Reaction to fire	EN 13501-1 B _{fl} -s1, L, CS																											
Slip resistance	EN 13893 μ > 0.30																											


DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Key:
 = 4 sided bevelled
 = in-register embossing

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Key:
 4 ⊕ = 4 sided bevelled
 ⊕ = in-register embossing
 ⊕ = natural colour variation



Description	Luxury vinyl tiles
Dimensions (tiles)	60 x 31.7cm
Dimensions (planks)	121.2 x 18.7cm / 150.5 x 23.7cm
Packaging per carton (tiles)	1.9m ² (10 pcs)
Packaging per carton (planks)	1.81m ² (8 pcs) / 2.14m ² (6 pcs)
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/ EN 428 0.55mm
Collection size	45
Application	EN 651 Class 33 / 42
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, CS
Slip resistance	EN 13893 μ > 0.30

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk


DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Description	Luxury vinyl tiles
Dimensions	96 x 96cm
Packaging per carton (tiles)	Tiles are delivered palletised
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/EN 428 0.70mm
Collection size	15
Application	EN 10874 Class 34 / 43
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1, L, NCS
Slip resistance	EN 13893 μ >0.30

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Key:
 4- = 4 sided bevelled
 ⊕ = in-register embossing



Description	Luxury vinyl tiles
Dimensions	48 x 48cm / 120 x 19cm / 150 x 24cm
Packaging per carton (tiles)	See page 95 for packaging information
Total thickness	ISO 1765 5mm
Thickness wear layer	ISO 24340/EN 428 0.70mm
Collection size	17
Application	EN 10874 Class 34 / 43
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1
Slip resistance	EN 13893 μ >0.30

Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk


MULTI CONSTRUCTION CARPET TILES & PLANKS

Tessera carpet tiles help to create a comfortable, relaxed atmosphere for residents, whilst offering the durability required to cope with daily footfall and wheeled traffic.

Available in tiles and planks, and offering a wide range of colours and designs, Tessera carpet tiles deliver superb underfoot comfort and acoustic properties of up to 30 dB. Also, thanks to its modular format, individual Tessera carpet tiles can be lifted and replaced if accidentally soiled or damaged with no need to replace the entire floor covering.

Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



Tessera Perspective 3908 | vivacious + 3907 | melodious + 3905 | ethereal


TESSERA TILES & PLANKS, COLLECTIONS AT A GLANCE

Loop Pile



Carpet tiles with a standard loop pile construction are designed to maintain their good looks in the most demanding heavy traffic areas of buildings, such as corridors and reception areas.

Multi-height loop pile carpet tiles offer distinctive in-built texture and contemporary styling, coupled with a robust and durable construction.



126

Cut & Loop



Cut and loop pile tiles feature a clever hybrid construction that offers all the robustness of a conventional loop pile product but with the superior aesthetics and more luxurious feel of a cut pile carpet tile.

Tessera offers cut and loop pile tiles in various aesthetic styles, suited to all types of office environments.



134

Loop Pile Planks



Sophistication and style in modularity. As modular flooring is a major trend, Forbo has developed a unique range of Tessera planks of 100 x 25cm and 100 x 20cm with which stunning floorplans can be created.



136



Visit the Tessera section on our website.



See all available technical downloads for Tessera.



Chroma is the quality by which we communicate colour. It is how we define a colour's purity, its intensity or saturation. In this way it provides a measure by which we can create a relationship between colours, allowing them to bring balance and harmony to a space.

DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

3601 platinum LRV 27	3600 castle LRV 19	3604 elephant LRV 13	3603 asphalt LRV 14	3607 mineral LRV 10	3606 tuxedo LRV 6																								
3602 chanterelle LRV 22	3609 coconut LRV 30																												
3605 pathway LRV 13	3610 thatch LRV 17																												
3608 quinoa LRV 9	3611 treacle LRV 8	3623 tangerine LRV 20	3621 camisole LRV 29	3622 wisteria LRV 19	Tile size 50 x 50 cm																								
3612 estuary LRV 19	3613 pasture LRV 13	3614 submarine LRV 26	3625 calypso LRV 13	<table border="1"> <tr> <td>Description</td> <td>Tufted textured loop pile carpet tile</td> </tr> <tr> <td>Dimensions</td> <td>50cm x 50cm</td> </tr> <tr> <td>Total thickness</td> <td>6.4mm ± 10%</td> </tr> <tr> <td>Pile height</td> <td>3.5mm ± 0.5mm</td> </tr> <tr> <td>Pile weight</td> <td>750gsm ± 10%</td> </tr> <tr> <td>Yarn</td> <td>100% polyamide 6</td> </tr> <tr> <td>Collection size</td> <td>27 (4m² per box)</td> </tr> <tr> <td>Application</td> <td>EN 1307 Class 33</td> </tr> <tr> <td>Impact sound reduction</td> <td>ISO 140-3 ΔL_w = 26 dB</td> </tr> <tr> <td>Recycled content</td> <td>61%</td> </tr> <tr> <td>CE</td> <td>EN 14041</td> </tr> <tr> <td>Reaction to fire</td> <td>EN 13501-1 B_{fl}-s1</td> </tr> </table>		Description	Tufted textured loop pile carpet tile	Dimensions	50cm x 50cm	Total thickness	6.4mm ± 10%	Pile height	3.5mm ± 0.5mm	Pile weight	750gsm ± 10%	Yarn	100% polyamide 6	Collection size	27 (4m ² per box)	Application	EN 1307 Class 33	Impact sound reduction	ISO 140-3 ΔL _w = 26 dB	Recycled content	61%	CE	EN 14041	Reaction to fire	EN 13501-1 B _{fl} -s1
Description	Tufted textured loop pile carpet tile																												
Dimensions	50cm x 50cm																												
Total thickness	6.4mm ± 10%																												
Pile height	3.5mm ± 0.5mm																												
Pile weight	750gsm ± 10%																												
Yarn	100% polyamide 6																												
Collection size	27 (4m ² per box)																												
Application	EN 1307 Class 33																												
Impact sound reduction	ISO 140-3 ΔL _w = 26 dB																												
Recycled content	61%																												
CE	EN 14041																												
Reaction to fire	EN 13501-1 B _{fl} -s1																												
3615 nautical LRV 10	3616 eucalyptus LRV 16	3617 botanical LRV 21	3624 blossom LRV 17	<p>Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads</p> <p>Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk</p>																									
3618 torrent LRV 7	3619 jungle LRV 7	3620 evergreen LRV 9	3626 cardinal LRV 10																										




An exceptionally flexible range of 18 commercial colourways, Create Space 1 is suitable for any commercial space, large or small. Styled for today's interiors, Create Space 1 lends itself to single colourway installations, feature area designs and bespoke creative schemes. Manufactured using regenerated solution dyed ECONYL® polyamide, means it's not only tough and durable but sustainable too.

1804 opal LRV 20	1819 jasper LRV 25																																								
1818 pearl LRV 19	1821 citrine LRV 18	1813 nickel LRV 19																																							
1801 feldspar LRV 7	1816 lithium LRV 10	1807 tawny LRV 13																																							
1800 ebonite LRV 3	1815 hematite LRV 5	1820 agate LRV 8																																							
<table border="1"> <tr> <td>Description</td> <td colspan="2">Tufted low level loop pile carpet tile</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">50cm x 50cm</td> </tr> <tr> <td>Total thickness</td> <td colspan="2">5.5mm ± 10%</td> </tr> <tr> <td>Pile height</td> <td colspan="2">2.7mm ± 0.5mm</td> </tr> <tr> <td>Pile weight</td> <td colspan="2">500gsm ± 10%</td> </tr> <tr> <td>Yarn</td> <td colspan="2">100% ECONYL®/Altochroma regenerated polyamide 6</td> </tr> <tr> <td>Dye method</td> <td colspan="2">100% solution dyed</td> </tr> <tr> <td>Collection size</td> <td colspan="2">18 (5m² per box)</td> </tr> <tr> <td>Application</td> <td>EN 1307</td> <td>Class 33</td> </tr> <tr> <td>Impact sound reduction</td> <td>ISO 140-8</td> <td>ΔL_w = 25 dB</td> </tr> <tr> <td>Recycled content</td> <td colspan="2">75%</td> </tr> <tr> <td>CE</td> <td colspan="2">EN 14041</td> </tr> <tr> <td>Reaction to fire</td> <td>EN 13501-1</td> <td>B_{fl}-s1</td> </tr> </table>			Description	Tufted low level loop pile carpet tile		Dimensions	50cm x 50cm		Total thickness	5.5mm ± 10%		Pile height	2.7mm ± 0.5mm		Pile weight	500gsm ± 10%		Yarn	100% ECONYL®/Altochroma regenerated polyamide 6		Dye method	100% solution dyed		Collection size	18 (5m ² per box)		Application	EN 1307	Class 33	Impact sound reduction	ISO 140-8	ΔL _w = 25 dB	Recycled content	75%		CE	EN 14041		Reaction to fire	EN 13501-1	B _{fl} -s1
Description	Tufted low level loop pile carpet tile																																								
Dimensions	50cm x 50cm																																								
Total thickness	5.5mm ± 10%																																								
Pile height	2.7mm ± 0.5mm																																								
Pile weight	500gsm ± 10%																																								
Yarn	100% ECONYL®/Altochroma regenerated polyamide 6																																								
Dye method	100% solution dyed																																								
Collection size	18 (5m ² per box)																																								
Application	EN 1307	Class 33																																							
Impact sound reduction	ISO 140-8	ΔL _w = 25 dB																																							
Recycled content	75%																																								
CE	EN 14041																																								
Reaction to fire	EN 13501-1	B _{fl} -s1																																							
1826 serpentine LRV 7	Tile size 50 x 50 cm																																								
1823 jadeite LRV 17	1825 spinel LRV 8	1828 garnet LRV 6																																							
1824 kyanite LRV 10	1827 lazulite LRV 5																																								



Every so often we need to pause, reflect, take a moment to focus on the important things. We need to find time to re-establish our balance and appreciate the value and integrity of a simpler, less cluttered existence.




In Struktur, we find a familiar sense of wellbeing and equilibrium.

- 18 tonal blends allow creation of softer and warmer spaces
- 350 gsm pile weight, creating a durable authentic flatweave texture
- Meets Ska criteria for M12 soft floor coverings
- Contains 65% recycled content by weight
- 100% solution dyed polyamide 6 yarn, for durability in colour fastness

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.



Description	Microtuft carpet tile
Dimensions	50cm x 50cm
Total thickness	5.1mm ± 10%
Pile height	1.0mm ± 15% -10%
Pile weight	350gsm ± 10%
Dye method	100% solution dyed
Collection size	18 (5m ² per box)
Application	EN ISO 10874 Class 33
Impact sound reduction	ISO 717-2 ΔL _w = 17 dB
Recycled content	65%
CE	EN 14041
Reaction to fire	EN 13501-1 C _f -s1, G, NCS



Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk




Featuring a contemporary palette of 32 colours the Layout range offers a multitude of creative and inspiring combinations in any flooring scheme.

The dynamic colour palette of Layout is hugely versatile featuring a comprehensive choice of modern neutrals in combination with diverse and directional brighter shades. Colours can be used independently or in combination to achieve a myriad of interior styles.



Tessera Layout 2130 | icepop + 2108 | calcium




Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk


Tile and plank formats




Description	Tufted low loop pile carpet tile	
Dimensions	Tile: 50cm x 50cm	Plank: 100cm x 25cm
Total thickness	5.8mm ± 10%	
Pile height	2.9mm ± 0.5mm	
Pile weight	580gsm ± 10%	
Yarn	100% polyamide 6	
Dye method	100% solution dyed	
Collection size	Layout 32 (5m ² per box)	
Application	EN 1307	Class 33
Impact sound reduction	ISO 10140-3 ΔL _w = 27 dB	
Recycled content	61%	
CE	EN 14041	
Reaction to fire	EN 13501-1	B _f -s1



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.



The rich tapestry of landscape that forms the unique Scottish island of Arran has influenced artists for generations. The quality of light and the huge variety of natural colours create a complex palette that changes with each season. From the muted hues of autumn bracken to the vibrant tones of the summer heather, Arran has a beauty that inspires.




Tessera Arran 1521 | golden sand + 1519 | stone wall



Tile size
50 x 50 cm

Description	Tufted multi-height loop pile carpet tile	
Dimensions	50cm x 50cm	
Total thickness	7.0 mm ± 10%	
Pile height	4.0mm ± 0.5mm	
Pile weight	950gsm ± 10%	
Yarn	100% Invista Antron® Lumena polyamide 6.6	
Dye method	100% solution dyed	
Collection size	12 (4m ² per box)	
Application	EN 1307	Class 33
Impact sound reduction	ISO 10140-3	ΔL _w = 25 dB
Recycled content	57%	
CE	EN 14041	
Reaction to fire	EN 13501-1	B ₁ -s1



Tessera Arran 1518 | foggy day + 1519 | stone wall + 1523 | dusty green



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.

Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

tessera[®] contour

Influenced by lines in architecture and relieved by softer more natural elements, Contour offers a geometric framework across a palette of 13 naturally inspired colourways.

The cut and loop pile construction provides the gentle, striated form and with 67% recycled content, Contour also offers a low environmental impact. The yarn is solution dyed Refresh™ by Universal fibres ensuring premium quality and improved cleanability and longevity.




1904 | lava core LRV 2


DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.



Description	Tufted multi-height cut and loop pile carpet tile	
Dimensions	50cm x 50cm	
Total thickness	6.3mm ± 10%	
Pile height	3.5mm ± 0.5mm	
Pile weight (after shearing)	580gsm ± 10%	
Yarn	Refresh™ by Universal Fibers™ 100% polyamide 6.6	
Dye method	100% solution dyed	
Collection size	13 (4m ² per box)	
Application	EN 1307	Class 33
Impact sound reduction	ISO 10140-3	ΔL _w = 27 dB
Recycled content	66%	
CE	EN 14041	
Reaction to fire	EN 13501-1	B _n -s1



Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

tessera[®] perspective



Using cut and loop design technology, the tip-sheared aesthetic of Perspective delivers a feeling of luxury that is perfect for modern workspaces.

The blend of surface textures within each tile absorbs light differently, creating a rich and opulent all-over visual which subtly changes from differing perspectives within any interior.

- 8 neutral tones complemented by 6 rich, decadent accent colours, each option combines two yarn colours, creating a modern, softly striated design
- 100% solution-dyed, Refresh® by Universal Fibers®. Nylon 66 and Nylon 6 with 30% recycled content
- Meets Ska criteria for M12 soft floor coverings
- Contains 65% recycled content by weight




Tessera Perspective 3906 | lyrical + 3901 | esprit + 3910 | rhapsody



3907 | melodious LRV 11



3909 | aura LRV 12 3911 | zestful LRV 8 3913 | iridescent LRV 3



3912 | mystique LRV 4 3910 | rhapsody LRV 4

Description	Tufted cut and loop pile carpet tile	
Dimensions	50cm x 50cm	
Total thickness	6.1mm	
Pile height	3.0mm	
Pile weight (after shearing)	670 g/m ²	
Yarn	100% Refresh® by Universal Fibers®	
Dye method	100% solution dyed	
Collection size	14 (4m ² per box)	
Application	EN 1307	Class 33
Impact sound reduction	ISO 10140-3	ΔL _w = 25 dB
Recycled content	65%	
CE	EN 14041	
Reaction to fire	EN 13501-1	B _n -s1, G, NCS



Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



The linearity of Seagrass makes it possible to create striking floor designs when these planks are laid herringbone or in the more traditional half drop style. When laid alongside Allura Flex, Seagrass the difference in textures makes for a very striking interior.

Plank size
100 x 20 cm



Tessera Seagrass 3203 | oyster + 3224 | dandelion + Allura Flex 61253 | oyster seagrass





Tessera Seagrass 3201 | indigo + 3200 | white + 3224 | dandelion + 3227 | teal + Allura Flex 61253 | oyster seagrass + 61255 | natural seagrass



Tessera Seagrass 3201 | indigo + 3200 | white + 3227 | teal

Description	Tufted multi-height loop pile carpet tile
Dimensions	100cm x 20cm
Total thickness	6.6mm ± 10%
Pile height	3.8mm ± 0.5mm
Pile weight	752gsm ± 10%
Yarn	100% Invista Antron® Lumena polyamide 6.6
Dye method	100% solution dyed
Collection size	9 (3m² per box)
Application	EN 1307 Class 33
Impact sound reduction	ISO 10140-3 ΔL _w = 28 dB
Recycled content	59%
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1



3220 | silver LRV 18 3200 | white LRV 32 3221 | pewter LRV 12 3203 | oyster LRV 20 3223 | sandstone LRV 18 3226 | aqua LRV 14



3222 | weathered LRV 13 3225 | meadow LRV 13 3224 | dandelion LRV 20

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.

Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

tessera® layout



Following on from the success of our Tessera Layout carpet tile collection, the Layout planks range also provides a contemporary and co-ordinated colour palette with the added benefit of a plank format.

We've introduced a total of 14 carpet tiles in a new 100cm x 25cm plank format, which provides the maximum flexibility for creating stunning floor designs. Available in sophisticated and bright colourways, Layout planks are offered in a very versatile palette.

Contains 62% recycled content by weight.

Plank size
100 x 25 cm




Tessera Layout 2112PL frosting + 2130PL icepop + 2118PL oceanis

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
 - 1b:** Used throughout as long as it is coordinated with other elements.
 - 2:** Used with caution.
- For more information please see page 12.

Our recommended adhesive is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads. Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



2112PL | frosting LRV 28 2107PL | brulee LRV 7 2122PL | drench LRV 7 2120PL | apple LRV 20 2123PL | candy LRV 23
 2104PL | alloy LRV 9 2108PL | calcium LRV 13 2118PL | oceanis LRV 5 2129PL | menthe LRV 16 2131PL | mango LRV 18
 2100PL | mono LRV 4 2103PL | balsamic LRV 13 2130PL | icepop LRV 12 2119PL | maraschino LRV 7

Description	Tufted low loop pile carpet tile	
Dimensions	100cm x 25cm	
Total thickness	5.8mm ± 10%	
Pile height	2.9mm ± 0.5mm	
Pile weight	580gsm ± 10%	
Yarn	100% polyamide 6	
Dye method	100% solution dyed	
Collection size	14 (4.5m ² per box)	
Application	EN 1307	Class 33
Impact sound reduction	ISO 10140-3	ΔL _w = 27 dB
Recycled content	61%	
CE	EN 14041	
Reaction to fire	EN 13501-1	B _{f1} -s1



FLOCKED FLOORING IN SHEET, TILE AND PLANK

Providing comfortable and familiar surroundings is essential for care residents. Our unique Flotex flocked flooring, available in sheet, tile and plank formats, combines the comfort, warmth and acoustic properties of a textile floor covering with the practical, hygienic advantages of resilient flooring.

Comfortable to walk on and warm underfoot, Flotex is durable and offers excellent slip resistance. Flotex can be cleaned right down to the base of the flock and as such, is the most hygienic textile on the market. It's also the only textile floor covering with the prestigious Allergy UK Seal of Approval.



Dementia-friendly flooring check list

- ✓ Tonal contrast
- ✓ Develop continuous flooring surface
- ✓ Reduce impact sound
- ✓ Reduce sparkle
- ✓ Avoid sensory overload
- ✓ Matt floor finish
- ✓ Provide smooth transitions
- ✓ Check installation methods
- ✓ DSDC accredited
- ✓ Consider products as part of a scheme



FLOTEX USAGE CLASSIFICATION

As with any product, colour and design influence the appearance retention of the floor. Likewise, Flotex is able to “hide” any soiling or dirt to a greater or lesser degree depending on the base colour and the visual design.

Using European (EN) approved testing methodology we have graded every item in the collection on its ability to ‘hide’ general dirt or staining that occurs during normal use depending on the application. The result is a usage classification that can be referred to when taking into consideration such things as type and level of traffic in the chosen application area. The classification is shown alongside each colour and design in this brochure.

- Superior appearance rating
- Good appearance rating
- Moderate appearance rating

FLOTEX COLLECTION AT A GLANCE

flotex® colour



Four versatile and fresh designs make up the Flotex Colour collection: Metro, Calgary, Penang and Canyon. Together they offer a range of 90 unique colourways, all available in sheet and tile format.



flotex® colour planks



Flotex Colour planks offer a wide variety of texture and colour in 100cm x 25cm plank format. They provide ultimate flexibility in floor plan design and are quick and easy to install. Flotex Colour Planks are available from stock and are suitable for raised access floors and ideal for, but not limited to, office environments.



flotex® planks



The performance attributes of Flotex along with the design versatility of the Plank collection, make these modular floor coverings ideal for use in workspaces as well as high traffic areas such as universities, hotels, gyms and busy offices.



flotex® naturals



Flotex Naturals offers photorealistic images of natural wood textures and colours. This stocked range of the renowned Flotex Naturals collection brings together 10 best-selling items and 10 new items that offer variety in colour and plank structure whilst meeting the latest design trends.



Visit the Flotex section on our website.



See all available technical downloads for Flotex.



flotex® colour metro

Flotex Metro is a versatile semi-plain floor design which covers a wide and modern colour bank. The understated pattern conveys texture without definite form, creating an authentic feel that is unique to Flotex flooring.



Flotex Colour Metro s246005 | nimbus

flotex® colour penang

Flotex Penang offers a stunning look for any modern environment. It creates a subtle linear effect and comes in a range of rich modern shades.



Flotex Colour Penang s482005 | smoke

flotex® colour calgary

Flotex Calgary offers a wide colour choice in a soft, natural design that works well in larger areas. The pattern can be easily combined with complementary Flotex or resilient ranges and is the perfect choice for application areas that require a muted ambience.



Flotex Colour Calgary s290012 | cement


flotex® colour canyon

Flotex Canyon is a heavily grained semi-plain inspired by natural earth and rock. It has a distinctive strong texture with a medium contrast.


All Flotex Colour tiles can be made as **Flotex Acoustic Plus** on a made-to-order basis with a minimum order quantity of 700m². However, **Metro Grey Acoustic Plus** is a stocked colour. For more information please contact Customer Services or your local Account Manager.




Flotex Colour Canyon s445022 | limestone



DSDC Ratings:
1a: Used widely as part of a holistic scheme.
1b: Used throughout as long as it is coordinated with other elements.
2: Used with caution.
 For more information please see page 12.





Description	Flocked flooring
Dimensions	Sheet: Roll width 2m Roll length ≤ 30 lm Tile: 50cm x 50cm (3m ² per box) Plank: 100 x 25cm (2.5m ² per box)
Total thickness	ISO 1765 Sheet: 4.3mm Tile: 5.0mm Plank: 5.0mm
Slip resistance	Pendulum test Wet – low slip risk
Collection size	90
Application	EN ISO 10874 Class 33 heavy
Impact sound reduction	EN ISO 717-2 Sheet: ΔLw = ≥ 20 dB Tile: ΔLw = ≥ 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 B ₂ -s1, L, NCS
Slip resistance	EN 13893 DS: ≥0.30
Body voltage	ISO 6356 ≤ 2 kV



Usage classification
 Superior appearance rating Good appearance rating Moderate appearance rating
 For more information see page 138.

s = Sheet
 t = Tile
 p = Planks
 *Available in 100 x 25cm planks
 The AcousticPlus can be ordered for all tiles as a special order as of 700m² per colour.
 Our recommended adhesive for Flotex Sheet is 640 Eurostar Special.
 For Flotex tiles and planks our recommended adhesive is 542 Eurofix Tack Plus.
 Full technical specifications are available at www.forbo-flooring.co.uk/downloads
 Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Description	Flocked flooring
Dimensions	Sheet: Roll width 2m Roll length ≤ 30 Im Tile: 50cm x 50cm (3m² per box) Plank: 100 x 25cm (2.5m² per box)
Total thickness	ISO 1765 Sheet: 4.3mm Tile: 5.0mm Plank: 5.0mm
Slip resistance	Pendulum test Wet – low slip risk
Collection size	90
Application	EN ISO 10874 Class 33 heavy
Impact sound reduction	EN ISO 717-2 Sheet: ΔLw = ≥ 20 dB Tile: ΔLw = ≥ 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 B _{fl} -s1, L, NCS
Slip resistance	EN 13893 DS: ≥ 0.30
Body voltage	ISO 6356 ≤ 2 kV



DSDC Ratings:

1a: Used widely as part of a holistic scheme.

1b: Used throughout as long as it is coordinated with other elements.

2: Used with caution.

For more information please see page 12.

Usage classification

- Superior appearance rating
- Good appearance rating
- Moderate appearance rating

For more information see page 138.

s = Sheet
t = Tile
p = Planks



*Available in 100 x 25cm planks

Our recommended adhesive for Flotex Sheet is 640 Eurostar Special.
For Flotex tiles and planks our recommended adhesive is 542 Eurofix Tack Plus.
Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

flotex® colour planks

penang | calgary | metro | canyon | savannah

Flotex Colour planks offer a wide variety of texture and colour in 100cm x 25cm plank format. They provide ultimate flexibility in floor plan design and are quick and easy to install. Flotex Colour Planks are available from stock and are suitable for raised access floors and ideal for, but not limited to, office environments. To see our wider range of digitally printed planks, see page 292.

Plank size
100 x 25 cm

Plank size
100 x 25 cm



Savannah 911001 | pearl + 911002 | cement

Calgary




p990012 | cement LRV 13 ☑




p990010 | ash LRV 4 ☑

Description	Flocked flooring	
Dimensions	100cm x 25cm (2.5m ² per box)	
Total thickness	ISO 1765	5.0mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size	15	
Application	EN 1307	Class 33
Impact sound reduction	EN ISO 717-2	ΔLw = 19 dB
CE	EN 14041	
Reaction to fire	EN 13501-1	B ₁ -s1
Slip resistance	EN 13893	DS: ≥0.30
Body voltage	EN ISO 10965	< 2 kV



Canyon



p945022 | limestone LRV 17 ☑



p945021 | stone LRV 13 ☑



p945020 | pumice LRV 8 ☑



p949019 | slate LRV 4 ☑

Usage classification

- Superior appearance rating
- Good appearance rating
- Moderate appearance rating

For more information see page 138.

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

Savannah



911001 | pearl ☑



911002 | cement ☑



911004 | charcoal ☑



p982017 | nimbus LRV 14 ☑



p982020 | shale LRV 10 ☑



p982007 | zinc LRV 9 ☑



911003 | almond ☑



911005 | walnut ☑



911006 | liquorice ☑



p982004 | mercury LRV 10 ☑



p982031 | ash LRV 5 ☑

Penang

Metro




p946024 | carbon LRV 5 ☑



p946007 | ash LRV 4 ☑



p946008 | anthracite LRV 3 ☑



p946001 | indigo LRV 3 ☑



p946032 | petrol LRV 4 ☑



p946026 | red LRV 9 ☑

DSDC Ratings:

1a: Used widely as part of a holistic scheme.

1b: Used throughout as long as it is coordinated with other elements.

2: Used with caution.

For more information please see page 12.



Flotex Naturals offers ultra-realistic designs of natural wood textures and colours. This stocked range offers variety in colour and plank structure whilst meeting the latest trends. Forbo's high definition printing technology enables us to create amazingly realistic wood-look floors with the added benefit of impressive acoustic and slip resistance properties, as well as reduced maintenance costs.

Description	Flocked flooring	
Dimensions	Roll width 2m	Roll length ≤ 30 Im
Total thickness	ISO 1765	4.3mm
Slip resistance	Pendulum test	Wet – low slip risk
Collection size	15	
Application	EN ISO 10874	Class 33
Impact sound reduction	EN ISO 717-2	ΔLw = ≥ 20 dB
CE	EN 14041	
Reaction to fire	EN 13501-1	B _f -s1, L, NCS
Slip resistance	EN 13893	μ ≥ 0.30
Body voltage	ISO 6356	≤ 2 kV



010078 | shaded oak Pattern repeat: 200 x 150cm LRV 21



010073 | heritage plank Pattern repeat: 200 x 150cm LRV 14



010075 | warm oak Pattern repeat: 200 x 150cm LRV 15



010039 | european white wood Pattern repeat: 200 x 150cm LRV 23



010074 | shadow plank Pattern repeat: 200 x 150cm LRV 8




010037 | blackened oak Pattern repeat: 200 x 150cm LRV 7




010058 | titanium oak Pattern repeat: 200 x 150cm LRV 26




010038 | white oak Pattern repeat: 200 x 150cm LRV 30



010055 | chestnut Pattern repeat: 200 x 150cm LRV 9



010035 | distressed oak Pattern repeat: 200 x 150cm LRV 19



010040 | antique pine Pattern repeat: 200 x 150cm LRV 12

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.



010076 | limed wood Pattern repeat: 200 x 150cm LRV 25



010036 | american oak Pattern repeat: 200 x 150cm LRV 20



010042 | steamed beech Pattern repeat: 200 x 150cm LRV 26



010041 | smoked beech Pattern repeat: 200 x 150cm LRV 28



Flotex Naturals 010037 | blackened oak + Flotex Vision Image Pavillion 000756 | titanium



Flotex Naturals 010039 | european white wood

A special range of 15 flocked floor coverings that all deliver the appearance of a real wood floor.

The range includes timber designs to suit everyone's needs and colour schemes, from beech and blackened oak to antique pine and european white wood.

Usage classification

☑ Superior appearance rating ☑ Good appearance rating ● Moderate appearance rating
For more information see page 138.

Our recommended adhesive for Flotex Sheet is 640 Eurostar Special. Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

flotex® planks

ombré


Strongly textile, subtly textured and shading from dark to light. The effect is one of deliberate contrasts, as the elements of the design mix with the format of plank. Ombré colours can easily be combined to make beautiful designs or used with their co-ordinating Montage colourways.




Plank size
100 x 25 cm




Ombre 149004 | moraine



149007 | arctic LRV 11




149004 | moraine LRV 14




149006 | glacier LRV 11



149004 | moraine LRV 14



149003 | tropic LRV 11




149008 | tundra LRV 13



149001 | boreal LRV 15



149002 | horizon LRV 10



149005 | estuary LRV 13

DSDC Ratings:


1a: Used widely as part of a holistic scheme.

1b: Used throughout as long as it is coordinated with other elements.

2: Used with caution.

For more information please see page 12.

Description	Flocked flooring
Dimensions	100cm x 25cm (2.5m ² per box)
Total thickness	ISO 1765 5.0mm
Slip resistance	Pendulum test Wet – low slip risk
Collection size	8
Application	EN 1307 Class 33
Impact sound reduction	EN ISO 717-2 ΔLw = 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, NCS
Slip resistance	EN 13893 DS: ≥0.30
Body voltage	EN ISO 10965 < 2 kV



flotex® planks

seagrass

Organic but linear, naturally inspired and beautifully textured. A classic pattern with colours that can easily be mixed together in a variety of installation methods. Seagrass is versatile and understated, making it suitable for any environment.



Plank size
100 x 25 cm



Seagrass 111001 | pearl + 111002 | cement + 111003 | almond + 111004 | charcoal + 111006 | liquorice



111001 | pearl LRV 26



111003 | almond LRV 19



111002 | cement LRV 13



111005 | walnut LRV 8




111004 | charcoal LRV 9



111006 | liquorice LRV 5

Description	Flocked flooring
Dimensions	100cm x 25cm (2.5m ² per box)
Total thickness	ISO 1765 5.0mm
Slip resistance	Pendulum test Wet – low slip risk
Collection size	6
Application	EN 1307 Class 33
Impact sound reduction	EN ISO 717-2 ΔLw = 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, NCS
Slip resistance	EN 13893 DS: ≥0.30
Body voltage	EN ISO 10965 < 2 kV



Usage classification

- Superior appearance rating
- Good appearance rating
- Moderate appearance rating

For more information see page 138

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk

flotex® planks

wood



Inspired by natural wood, this familiar aesthetic takes on a new versatile guise offering a traditional look in an untraditional format. These wood patterns are beautifully detailed, look good individually and can be combined to create stunning flooring designs.

Plank size
100 x 25 cm


Description	Flocked flooring
Dimensions	100cm x 25cm (2.5m ² per box)
Total thickness	ISO 1765 5.0mm
Slip resistance	Pendulum test Wet – low slip risk
Collection size	8
Application	EN 1307 Class 33
Impact sound reduction	EN ISO 717-2 ΔLw = 19 dB
CE	EN 14041
Reaction to fire	EN 13501-1 B ₁ -s1, L, NCS
Slip resistance	EN 13893 DS: ≥0.30
Body voltage	EN ISO 10965 < 2 kV

Our recommended adhesive for Flotex planks is 542 Eurofix Tack Plus. Full technical specifications are available at www.forbo-flooring.co.uk/downloads

Only DSDC accredited products shown. To see the full range, please visit www.forbo-flooring.co.uk



Wood 151001 | black wood + 151002 | grey wood + 151004 | american wood + 151006 | antique wood



Usage classification


- Superior appearance rating
- Good appearance rating
- Moderate appearance rating

For more information see page 138

DSDC Ratings:

- 1a:** Used widely as part of a holistic scheme.
- 1b:** Used throughout as long as it is coordinated with other elements.
- 2:** Used with caution.

For more information please see page 12.



Flotex Planks Wood | 002426

CASE STUDIES

Our products have been used in a wide range of care environments to create a comfortable, safe and welcoming environment. Designers and specifiers are increasingly 'designing for the mind' in a variety of sectors, recognising the benefits for neurodiverse people as well as those with dementia. As a result, our carefully designed product range is also being specified for offices, retail locations, public buildings, leisure facilities and even prisons.

Hillingdon Hospitals NHS Foundation Trust

Product: **Surestep Decibel**

Our Surestep Decibel product was used in the creation of a new facility as part of the Beaconsfield East Dementia Care Project. The Hillingdon Hospitals NHS Foundation Trust refurbished the Beaconsfield East Ward to create a rehabilitation ward for older adults, many of whom have dementia.

Installed throughout the 20 bed rehabilitation ward, which also included a reception, sensory spaces and utility service areas. Surestep was specified for its non-clinical wood finish, non-reflective surface, R10 slip resistance and 17 dB impact sound reduction. The Beaconsfield East Ward won the Best Internal Environment Award at the Building Better Healthcare Awards in 2014.



CASE STUDIES

Caudwell International Children’s Centre (CICC)

Products: **Flotex Flocked Flooring & Allura Wood Luxury Vinyl Tiles**

Our Flotex flocked flooring was installed at the Caudwell International Children’s Centre (CICC), the UK’s first independent purpose-built facility dedicated to autism diagnosis, intervention and research. The 60,000 sq ft building at Keele University Science and Innovation Park was meticulously designed through insight from the charity Caudwell Children as well as through consultations with clinicians, academics and, most importantly, the families that will use the facility.



The semi-plain Penang design from the Flotex Colour range offers subtle aesthetics and the tactile nature of Flotex helps to create a calming and easily cleanable environment for children with autism and neurodevelopmental conditions. Furthermore, our Allura Wood LVT was selected for the main corridors of the public area. The assessment suites and breakout spaces lead off from the corridors, so the variation of flooring allow the children to differentiate each space and identify their direction of travel.



The Catalyst

Product: **Allura Wood Luxury Vinyl Tiles**

Our Allura Wood Luxury Vinyl Tiles (LVT) were recently specified at The Catalyst; an architecturally striking building, home to Newcastle University’s National Innovation Centre for Ageing (NICA) and National Innovation Centre for Data (NICD). The 100,000 sq ft building brings together businesses, academics and members of the public to collaborate and support the research and development of new ageing and data products and services.

The aim for the building was to create interior spaces that were truly accessible, welcoming and inclusive for everyone. As some floors are open to the public, the building needed to be easy to navigate, particularly for visitors who may have age-related conditions, visual impairments, disabilities or use walking aids. Using guidance from the DSDC, a holistic approach was taken to the whole specification process and a ‘dementia-friendly’ approach to the design was adopted.



Allura Wood LVT in the Vintage Oak colourway was used for the staircase, main circulation areas and breakout spaces on each floor; achieving one tonally continuous flooring surface. In addition, our Surestep safety vinyl in Beton Concrete was used in areas where there is an increased slip risk, such as the toilets, kitchens and tea points.

THE NEXT STEPS

At Forbo, we have a range of services that can help you select the right flooring for each area of your care facility. From a free sample service, to dedicated sales staff who know our care portfolio inside out, let us help you to take the next steps.

To order your free samples visit www.forbo-flooring.co.uk, call **0800 731 2369** or email samples.uk@forbo.com.



Bespoke Design Service

Our in-house design team can help bring your ideas to life with the free Bespoke Design Service. Whether you are taking inspiration from one particular DSDC accredited product, which needs to be carried through the plan, or you simply need to see your scheme in the flesh, our design team can create plan boards of your design, complete with product samples.



Dementia resources

On our website you can check the DSDC ratings, read more about dementia friendly design and view case studies of how our flooring has been used to build a better care environment.

Visit www.forbo-flooring.co.uk/dementia



BIM

For new build projects, did you know that we offer fully rendered BIM objects? Simply visit Bimstore, BimObject or NBS Source to download our objects for free.

Further reading

We also have a number of articles on our blog on the topics of 'Designing for the Mind', including the summary of our roundtable discussion, autism-friendly design, dementia care and creating sensory experiences.

Follow our blogs here: www.forbo-flooring.co.uk/blog



Samples:

0800 731 2369
www.forbo-flooring.co.uk/samples
samples.uk@forbo.com

Email:

info.flooring.uk@forbo.com

Downloads & CPDs:

www.forbo-flooring.co.uk/dementidownloads
www.forbo-flooring.co.uk/dementiaCPD



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this brochure are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this brochure and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.

Please note: Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 2369.

Within this brochure, Forbo has endeavoured to be positive and inclusive with the language used and product imagery shown. However, please be aware that some images may not reflect the correct dementia guidelines and are used purely as a product reference. When creating your own 'dementia-inclusive' or 'dementia-friendly' designs, please always refer to the dementia guidelines. For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring. For further guidance and information please visit www.dementia.stir.ac.uk



Within this brochure, Forbo has endeavoured to be positive and inclusive with the language used and product imagery shown. However, please be aware that some images may not reflect the correct dementia guidelines and are used purely as a product reference. When creating your own 'dementia-inclusive' or 'dementia-friendly' designs, please always refer to the dementia guidelines. For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring. For further guidance and information please visit www.dementia.stir.ac.uk

UK

Forbo Flooring UK Limited
High Holborn Road
Ripley
Derbyshire DE5 3NT

London EC1 showroom

79 St John Street, Clerkenwell
London EC1M 4NR
Tel: 0207 553 9300

For commercial enquiries:

If calling from the North,
London & South East
Tel: 0800 0282 162
bcs.flooring.uk@forbo.com

If calling from Scotland,
Midlands & South West
Tel: 0800 0935 258
kcs.flooring.uk@forbo.com

Nuway enquiries:

Tel: 01773 740 688
efs.flooring.uk@forbo.com

Residential enquiries:

Tel: 0800 0935 846
krqs.flooring.uk@forbo.com
www.forbo-flooring.co.uk

Sample orders:

Tel: 0800 731 2369
samples.uk@forbo.com

Ireland

Forbo Ireland Ltd
2 Deansgrange Business Park
Blackrock
Co Dublin
Tel: 00353 1 2898 898
Fax: 00353 1 2898 177
info.ireland@forbo.com
www.forbo-flooring.ie

Find us on



Registered office:

Forbo Flooring UK Limited
High Holborn Road
Ripley
Derbyshire DE5 3NT
Registered in England 9200318

