

Forbo Environmental Data Sheet

Product name	Tessera Topology
Product description	Combining geometric elements and organic structure, the Tessera Topology collection offers flexibility with a range of colours inspired by a natural palette Topology complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000®



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content of product by weight	75%	ISO 9001 Quality Management System	
		ISO 14001 Environmental Management System	ental ent
Post industrial recycled content	75%	ISO 45001 Occupational Health and Safety Management	nent
% renewable electricity & biogas used	100%	Tessera is made in an SA8000° certified facility	
Carbon footprint			
Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Cradle to gate (A1-A3)	1.40 kg CO ₂ eq/m ²	
	Use (1 year) (B2)	0.639 kg CO ₂ eq/m ²	

Your footsteps – how it performs

Health and well being

Air quality	Indoor Air Comfort Gold
Prodis-GUT	TBC
Impact sound reduction	27 dB
Installation	

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended. Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.



creating better environments

Ma	inte	ena	nce

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK.

Contribution to Green Building Schemes

BREEAM 2018

Ska scheme (RICS)			
M12 soft floor covering criteria	(Ska Offices Vs 1.2 2013)	(Ska Retail Vs 1.0 2012)	(Ska Higher Education Vs 1.0 2016)
	Meets	Meets	Meets

Compliant through declaration number 4791394456.101.1 - valid until July 2029

LEED (version 4.1)

Potential direct or indirect
contribution to following
categories and credits:

Materials and Resources	
	Building product disclosure and optimisation - sourcing of raw materials - up to 1 point
	Construction and demolition waste management up to 2 points
Indoor environmental quality	Low emitting materials up to 3 points
	Acoustic performance up to 1 point

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce	Investment in an extruder has reduced our bitumen usage by 50%.
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles made in the UK contain at least 60% recycled content by weight.
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).

visit www.forbo-flooring.co.uk/downloads for more information