eurocol 810

EUROFLOOR FORCE FABRIC

yes

Reinforcement fabric, for weak subfloors before levelling.



PRODUCT TYPING				
Base	Polyester fabric			
Color	White.			
Format	Length 50 m. Width 1 m.			

- Tear-resistant polyester fabric for subfloor surface reinforcement and load distribution.
- In particular for not sufficiently pressure resistant, unstable or deformable subfloors such as wooden boards, glued down
 insulation underlays, CV floor coverings and point-elastic
 sports floors before levelling works.
- Easy application.

PROPERTIES

Frost resistance

Moisture-resistant.

APPLICATION				
For not sufficiently p	pressure resistant, unstable or deformable subfloors.			
PROCESSING				
Storage	Store cool and dry in unopened packaging.			
Shelf Life	Minimum 72 months, in unopened packaging.			

TODOTechnical information and safety data sheets of other laying materials must be observed!

Substrate

Remarks

- The subfloor must be prepared professionally according to the conditions, so that with levelling and filling work can be started.
- A system-compliant primer is applied, as far as the connection with the selected levelling compound is necessary.

Instruction manual:

- Reinforcing fabric must be rolled out, cut off and fixed with staples at the edges and in the overlapped seam area. It is also possible to fix it with a suitable primer or adhesive.
- For smaller areas, loose laying out is also sufficient.

Processing conditions:

810 EUROFLOOR FORCE FABRIC



^{*} The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

ENVIRONMENT AND HEALTH

Safety and environment

Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste.

ITEM DATA

articel	productname	packaging	shipping unit
810	Eurofloor Reno Fleece	roll à (50*1) m	40 rolls/pallet

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG44560, Version 02, Stand 2021-03-08, ersetzt Ausgabe vom 2018-11-21.



