

Marmoleum Modular

LRV & DSDC product accreditation

Please note: ratings only apply when the tiles are installed broadloom/brick bond and in one colour.

Design	Colour number	Colour name	NCS	LRV Y (BS8493)	DSDC Rating*	DSDC Comments*
Lines	t5232	rocky ice	NCS S 3005-Y20R	44	1b	
	t3573	trace of nature	NCS S 5005 - Y20R	27	2	Striped pattern range resembles timber, making is suitable due to its familiar nature
	t5231	Cliffs of Moher	NCS S 6005-Y20R	17	2	
	t3575	white cliffs	NCS S 2010 - Y	57	1b	No pattern creation/consistent colour
	t5226	grey granite	NCS S 5005 - G50Y	29	2	
	t5237	black sheep	NCS S 6502 - B	18	2	
	t5230	white wash	NCS S 2010 - Y30R	49	1b	
	t5225	compressed time	NCS S 4010 - Y30R	34	2	
	t5235	North Sea coast	NCS S 4010 - Y30R	32	1b	
	t5217	withered prairie	NCS S 5010 - Y30R	23	1b	
	t5218	Welsh moor	NCS S 8005 - Y80R	8	2	
Textura	te5230	white wash	NCS S 2010 - Y30R	49	1b	
	te5235	North Sea coast	NCS S 4010 - Y30R	32	1b	
	te5217	withered prairie	NCS S 5010 - Y30R	23	1b	
	te5229	fresh walnut	NCS S 6020 - Y50R	15	1b	
	te5218	Welsh moor	NCS S 8005 - Y80R	8	2	
	te5231	Cliffs of Moher	NCS S 6005-Y20R	17	2	
	te3573	trace of nature	NCS S 5005 - Y20R	27	1b	
Slate	te3747	Lakeland shale	S 5502-Y	21	2	
	te3745	Cornish grey	S 6502-G	15	2	
	te3746	Newfoundland slate	S 7005-Y50R	11	2	
	te3725	Welsh slate	S 7502-B	9	2	
Shade	t3722	stardust	NCS S 1010 - G80Y	59	1b	
	t3716	Mercury	NCS S 1502 - Y	50	1b	
	t3711	cloudy sand	NCS S 2010 - Y	49	2	
	t3717	Neptune	NCS S 2502 - Y	38	2	
	t3702	liquid clay	NCS S 5005 - Y20R	23	1b	
	t3718	Pluto	NCS S 3502 - Y	30	2	
	t3568	delta lace	NCS S 7005 - Y20R	13	1b	
	t3707	black hole	NCS S 8500 - N	7	1b	
	t3704	satellite	NCS S 5502 - Y	23	2	
	t3745	Cornish grey	S 6502-G	15	1b	

Marmoleum Modular



LRV & DSDC product accreditation

Please note: ratings only apply when the tiles are installed broadloom/brick bond and in one colour.

Design	Colour number	Colour name	NCS	LRV Y (BS8493)	DSDC Rating*	DSDC Comments*
Colour	t3251	lemon zest	NCS S 1050 - Y10R	52	n/a	Awaiting accreditation
	t3352	Berlin red	NCS S 4050-Y80R	10	n/a	Awaiting accreditation
	t3354	pumpkin yellow	NCS S 2050-Y30R	31	n/a	Awaiting accreditation
	t3358	petrol	NCS S 7020 - B10G	9	n/a	Awaiting accreditation
	t3362	yellow moss	NCS S 3040 - G90Y	30	n/a	Awaiting accreditation
	t3238	laguna	NCS S 2040 - B10G	30	n/a	Awaiting accreditation
	t3030	blue	NCS S 5030 - R90B	12	n/a	Awaiting accreditation
	t3131	scarlet	NCS S 1580-Y90R	13	n/a	Awaiting accreditation
Marbled	t3136	concrete	NCS S 3005-G80Y	47	n/a	Awaiting accreditation
	t2713	calico	NCS S 2010 - Y20R	53	n/a	Awaiting accreditation
	t3120	rosato	NCS S 2010 - Y20R	51	n/a	Awaiting accreditation
	t3407	donkey island	NCS S 3010 - Y30R	36	n/a	Awaiting accreditation
	t3146	serene grey	NCS S 4502-Y	27	n/a	Awaiting accreditation
	t3232	horse roan	NCS S 3010-Y20R	40	n/a	Awaiting accreditation
	t2707	barley	NCS S 1515 - Y30R	49	n/a	Awaiting accreditation
	t3053	dove blue	NCS 4005 - B80G	27	n/a	Awaiting accreditation
	t3216	moraine	NCS S 4005-G80Y	34	n/a	Awaiting accreditation
	t3405	Granada	NCS S 5005 - Y20R	28	n/a	Awaiting accreditation
	t3048	graphite	NCS S 7502 - Y	14	n/a	Awaiting accreditation

Marmoleum Modular

LRV & DSDC product accreditation

	2016-074 FORBO FLOORING	
	DSDC RATING KEY	
	NOV-16	
*RATING	*RATING DESCRIPTION	
Class 1a	<p>Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors/frames, furniture and sanitary ware.</p> <p>Contrast is the key word.</p> <p>We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	
Class 1b	<p>Flooring within this rating is semi-plain (minimal texture or fleck/pattern, wood effect with no knots) and in general, can be used throughout.</p> <p>Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	
Class 2	<p>Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured/patinated and although still familiar they need to be used with more caution than the above range.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	

For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring.

As with many design features, individual needs and preferences should also be considered. What is fine for one person, may not be the case for another.

For more information and to download our 'Designing for dementia care' brochure visit www.forbo-flooring.co.uk/care