

Technical specifications

Sphera SD | EC meet the requirements of EN-ISO 10581



sphera® SD/EC

		sphera SD	sphera EC
	Binder content	EN-ISO 10581	Type 1
	Total thickness	EN-ISO 24346	2.0 mm
	Surface finish		SMART control ⚡ top
	Collection size		14
	Commercial use	EN-ISO 10874	34 very heavy
	Light industrial use	EN-ISO 10874	43 heavy
	Roll width	EN-ISO 24341	2 m
	Roll length	EN-ISO 24341	≤ 27 m ~ 26 m
	Total weight	EN-ISO 23997	2.9 kg/m ²
	Electrostatics (general requirements)	IEC 61340-5-1	Compliant
	Electrical resistance	IEC 61340-4-1 ESD STM7.1	1 x 10 ⁶ ≤ R ≤ 10 ⁸ Ω
	Electrical resistance in combination with ESD control footwear	IEC 61340-4-5 ESD STM97.1	R ≤ 1 x 10 ⁹ Ω
	Body voltage generation, in combination with ESD control footwear <i>Typical value</i>	IEC 61340-4-5 ESD STM97.2	< 50 V ~ 0 V <> 30 V
	Electrical insulation to ground	DIN VDE 0100	≥ 50 kΩ
	Dimension stability <i>Typical value</i>	EN-ISO 23999	≤ 0.4% ~ 0.2%
	Residual indentation <i>Typical value</i>	EN-ISO 24343-1	≤ 0.10 mm ~ 0.03 mm
	Castor chair continuous use	ISO 4918	Pass
	Light fastness	EN-ISO 105-B02	≥ 7
	Flexibility	EN-ISO 24344	ø 10 mm
	Resistance to chemicals	EN-ISO 26987	Very good
	Slip resistance	DIN 51130	R9
	Bacteria resistance	EN 846	Does not support growth
	Indoor air emissions: TVOC after 28 days	ISO 16516	≤ 0.01 mg/m ³
	Cleanroom particle emission	ISO 14644-1	ISO 6
	Creating better environments		
	Renewable electricity	Sphera is manufactured using 100% electricity made from renewable sources	
	Sphera meets the requirements of EN 14041	EN 14041 CE 0200304-DoP-003	EN 14041 CE 0200305-DoP-003
	Reaction to fire	EN 13501-1	B _{f1} -s1, G, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Thermal conductivity	EN 12524	0.25 W/m·K
	Body voltage	EN 1815	≤ 2 kV
	Electrical behaviour – static dissipative	EN 1081	≤ 1 x 10 ⁹ Ω
	Electrical behaviour – conductive	EN 1081	n.a.

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Sphera is manufactured in a facility certified to SA8000 and OHSAS 18001.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.

SAMPLE SERVICE
0800 731 2369
samples.uk@forbo.com

Forbo BIM
REVIT | ARCHICAD

For more information:

e: info.flooring.uk@forbo.com

t: **0800 0282 162**

w: forbo-flooring.co.uk/sphera



FLOORING SYSTEMS