
























Technical specifications

Basis Pro Phase carpet tile planks and Basis Pro carpet tiles meet the requirements of EN 1307

		Basis Pro Phase	Basis Pro
	Description	Tufted low level loop carpet tile plank	Tufted low loop carpet tile
	Plank/Tile size	EN ISO 24342:2018 100 cm x 25 cm	50 cm x 50 cm
	Total thickness	ISO 1765 5.6 mm	5.6 mm
	Pile height	ISO 1766 2.6 mm	2.6 mm
	Collection size	12 colourways	15 colourways (32 in full collection)
	Packaging per carton of tiles	18 (4.5 m ²)	20 (5 m ²)
	Commercial use	EN ISO 10874 Class 33	Class 33
	Pile composition	100% Aquafil polyamide 6	100% Aquafil polyamide 6
	Dye method	100% solution dyed	100% solution dyed
	Stitch density	ISO 1763 197,000 per m ²	197,000 per m ²
	Pile weight	ISO 8543 540 g/m ²	540 g/m ²
	Total weight	ISO 8543 3880 g/m ²	3880 g/m ²
	Primary backing	Polyester	Polyester
	Secondary backing	ProBac™ recycled mineral filler with low amount of modified bitumen and polyester fleece	
	Acoustical impact noise reduction	ISO 10140-3 25 dB	25 dB
	Acoustical sound absorption	ISO 354 α _w = 0.15 (H)	α _w = 0.15 (H)
	Castor chair continuous use	ISO 4918 r ≥ 2.4	r ≥ 2.4
	Colour fastness to light	EN ISO 105-B02 ≥ 5	≥ 5
	Dimensional stability	EN 986 ≤ 0.2%	≤ 0.2%
	Indoor air emissions: TVOC after 28 days	EN 16516 ≤ 0.1 mg/m ³	≤ 0.1 mg/m ³
	Creating Better Environments		
	Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)	
	Recycled Content	Basis Pro Phase carpet tile planks and Basis Pro carpet tiles contain 62% recycled content by weight	
	Indoor air quality	Basis Pro Phase carpet tile planks and Basis Pro carpet tiles achieve Indoor Air Comfort Gold 8.0 (2023)	
	Ska Rating	Basis Pro Phase carpet tile planks and Basis Pro carpet tiles meet Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
	Prodis-GUT	www.pro-dis.info AF1485CC	AF1485CC
	Installation method	Half drop, herringbone, double herringbone	Monolithic, quarter turn or tessellated

Basis Pro Phase carpet tile planks and Basis Pro carpet tiles meet the requirements of EN 14041:2004 and BS EN 14041:2004

 
EN 14041 BS EN 14041

	Product code	EN 14041:2004 1170100-DoP-109	1170100-DOP-109
	Product code	BS EN 14041:2004 1170100-DoP-GB109	1170100-DoP-GB109
	Reaction to fire	EN 13501-1 B _{fl} -s1, G, NCS	B _{fl} -s1, G, NCS
	Slip resistance	EN 13893 μ ≥ 0.30	μ ≥ 0.30
	Body voltage	ISO 6356 < 2.0 kV	< 2.0 kV
	Thermal conductivity	EN 12524 0.06 W/mK	0.06 W/mK

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001. Tessera carpet tiles and planks are manufactured in a facility certified to SA8000® and ISO 45001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPDs).