

Technical specifications

Coral meets the requirements of EN 1307

	Coral Brush (57xx)	Coral Brush tile (57xx)	Coral Brush FR (57xx)
	Total thickness		
	Approx. 9 mm		Approx. 9 mm
	Area of use		
	33, commercial heavy		33, commercial heavy
	Colours		
	Available sizes (all sizes are approx.)		
	Rolls	Mats	Tiles
	105cm	55 x 90 cm	50x50cm
	155cm	90 x 155 cm	3m2, 12 tiles in a box. 28 boxes on a pallet 110x110cm
	205cm	135 x 205 cm	
	Roll lengths approx. 27,5m	205 x 300 cm	
	Rolls FR have no edges		Roll lengths approx. 27,5m
	Colour fastness ratings:		
	Light	>5	>5
	Rubbing	5	5
	Water	4-5	4-5
	Seawater	4-5	4-5
	Waterstains	5	5
	Shampoo	4-5	4-5
	Organic solvents	4-5	4-5
	Manufacturing method/type		
	Tufted, 5/32" cut-pile		Tufted, 5/32" cut-pile
	Designs		
	Plain designed/coloured blend		Plain designed/coloured blend
	Pile material		
	100% regenerated Econyl polyamide		100% regenerated Econyl polyamide
	Tuft base		
	Non-woven polyester		Non-woven polyester
	Backing		
	EVERFORT vinyl		EVERFORT Vinyl tile
	FR-latex		
	Total weight		
	Approx. 4050 gram/m ²		Approx. 4700 gram/m ²
	Pile installation weight		
	Approx. 920 gram/m ²		Approx. 920 gram/m ²
	Pile thickness		
	Approx. 7 mm		Approx. 7 mm
	Pile density		
	0,105 gram/cm ³		0,105 gram/cm ³
	Number of tufts		
	Approx. 58.000/m ²		Approx. 58000/m ²
	Comfort class		
	LC3		LC2
	Other remarks		
	All Coral products meet the requirements of EN 14041, excluding loose-lay		
	Fire behaviour		
	B _{s1}		B _{s1}
	Slip resistance		
	R ₁₃		R ₁₃
	Personal charging		
	< 2 kV		< 2 kV