

This document is for internal use only

Acceptable substrates for adhesive-free sheet material

Subfloor Type	Can Eternal Next, Modul'up, Surestep Fast Fit be installed over the subfloor type?
Magnesite	No
Underfloor Heating	Yes
Painted Concrete	Yes
Fresh Concrete up to 92%	Yes
Existing Linoleum	Yes
Tarmac	No
Ceramic Tiles	Yes
Concrete RH98% +	No
Textile	No
Wood or Particle Boards	Yes
Raised access flooring	Yes
Tiles containing Asbestos	Yes
Wood Block Flooring (ground Level)	No
Calcium Sulphate Screed	No
Ability to be Covered	Yes
SP101 Plywood	Yes
Laminate flooring	No
New Latex Screed	Yes
Quarry Tiles without DPM	No
Wood Block flooring (upper levels)	Yes
Existing Vinyl	Yes

NOTE:

- Please refer to the [installation guide\(s\)](#) when advising subfloor recommendation.
- Modul'up TE can be installed on subfloor up to 97RH with ventilated skirting ([refer to guidance](#))
- For all adhered products the RH value is required to be 75RH as per [BS8203:2017](#) and [BS5325:2021](#).

If in any doubt, contact UK Technical Support uktechnicalsupport@forbo.com