

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Forbo Eurocol Nederland 658 Wandoforte; cement-bound levelling mortar for walls.	
3. Application	For levelling and repairing cement-bound and other stony walls, such as concrete, aerated concrete, sand-lime brick, layer thickness between 2 and 10 mm, upon which tiling is to be applied. Suitable for interior and exterior application.	
4. Name and contact address manufacturer	<i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i>	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	n/a	
8. European Technical Assessment	n/a	
9. Declared performance	GP-CSIV in accordance with NEN-EN 998-1:2010; Multifunctional plaster mortar with increased compressive strength (CSIV) and decrease water absorption (W2) for use under tiling in interior and exterior situations.	
<b>Essential characteristics</b>	Performance	Test method
Dry bulk density	1500 Kg/m <sup>3</sup>	NEN-EN 1015-10:1999+A1:2007
Compressive strength after 28 days	CSIV = > 6 N/mm <sup>2</sup>	NEN-EN 1015-11:1999+A1:2007
Initial adhesive strength	2.3 N/mm <sup>2</sup>	NEN-EN 1015-12:2000
Capillary water absorption	W2 = ≤ 0.20 kg/m <sup>2</sup> • min 0,5	NEN-EN 1015-18:2003
Compressive strength after water exposure and freeze/thaw cycles	10 N/mm <sup>2</sup>	
Water vapour permeability coefficient	μ 5/20	NEN-EN 1015-19:1998+A1:2004
Heat conduction coefficient	λ 0,47W/mK	NEN-EN 1745:2012 tabel A.12
Material behaviour in case of fire	Class E	NEN-EN 13501-1:2007+C1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 998-1:2010.		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 11-07-2013 signed: ing. T.W. Breeuwer; Manager R&D 