

Data Sheet

Punching Press for Z-Splices PP-ZP-V/40-3



Punching presses of the PP-ZP-V/40-3 type are used to prepare Z-splices for belt widths up to 40 mm. Splices 35, 75 and 110 mm in length can be punched symmetrically. The adjustable that can be set to punch symmetrically is included in the scope of delivery. Without punching set!

When you use the practical tool, you will require little force because the leverage is good.

The tool does not cause any wastage, because you can work continuously from the roll. When punching on one side, the material required is cut to length from the roll and the end of the belt prepared accordingly. In doing so, the beginning of the belt is made for each new splice so that set-up times are shortened.

Punching Press for Z-Splices
PP-ZP-V/40-3

Should you need any further information, please contact directly the manufacturer:

Müssel Maschinenbau GmbH
Reichelsweiherstraße 8,
95615 Marktredwitz
GERMANY
www.muessel.com



Technical Data	PP-ZP-V/40-3	
Belt width max. (only 90°)	[mm]	40
Length	[mm]	185
Width	[mm]	205
Height	[mm]	265
Height without opera. lever	[mm]	135
Weight (net)	[kg]	2,1
Splicing angle	[°]	90
Type of splice		Z 35 x 5,75 Z 35 x 11,5 Z 70 x 11,5 Z 110 x 11,5

Material number	Designation
872937	PP-ZP-V/40-3 Basic tool incl. symmetrical adjustment table

Data Sheet

Available accessories:

Accessories are not included in the scope of delivery and must be ordered separately!

Material number	Designation
872071	Punching set 35 x 5,75 mm pivotable
872480	Punching set 35 x 11,5 mm not pivotable
872877	Punching set 70 x 11,5 mm not pivotable
872878	Punching set 110 x 11,5 mm not pivotable