






















Technical specifications

Enduro meets the requirements of EN ISO 10582

enduro

		Enduro Dryback	Enduro Click
 Total thickness	EN-ISO 24346	2.0 mm	4.0 mm
 Wearlayer thickness	EN-ISO 24340	0.30 mm	0.30 mm
 Collection size		20	20
 Domestic use	EN-ISO 10874	23	23
 Commercial use	EN-ISO 10874	31	31
 Tile size	EN-ISO 24342	60.96 x 30.48 cm	61 x 30.5 cm
 Plank size	EN-ISO 24342	121.9 x 17.8 cm	121.2 x 18.5 cm
Packaging per carton tiles		4.09 m ² (22 pcs)	2.23 m ² (12 pcs)
Packaging per carton planks		4.77 m ² (22 pcs)	2.24 m ² (12 pcs)
 Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
 Total weight	ISO 23997	ca. 3000 g/m ²	ca. 6700 g/m ²
Wear layer Binder Content	EN-ISO 10582	Type 1	Type 1
 Slip resistance	DIN 51130	R10	R10
 Impact sound reduction	EN-ISO 717-2	5 dB	6 dB / 15 dB in combination with Forbo underlay
 Castor chair continuous use	ISO 4918	Good	Good
 Residual indentation	ISO 24343-1	≤ 0.10 mm	≤ 0.10 mm
 Light fastness	ISO 105-B02	≥ 6	≥ 6
VOC emissions reaction to fire	EN-ISO 160009	≤ 100 µg/m ³	≤ 100 µg/m ³
 Resistance to chemicals	ISO 26987	Good	Good
 Dimensional stability	EN-ISO 23999	≤ 0.10%	≤ 0.10%
 Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact	
 Reaction to fire	EN 13501	B _f -s1, G, NCS	B _f -s1, L, NCS with and without Forbo underlay
 Slip resistance	EN 13893	DS - µ > 0.30	DS - µ > 0.30
 Thermal conductivity	ISO 8302	0.25 W/mK	0.25 W/mK
 Body voltage	EN 1815	< 2 kV	< 2 kV

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 121 4780**

w: forbo-flooring.co.uk/enduro