






















# Technical specifications

Eternal meets the requirements of ISO 10582 and EN 649



	Total thickness	EN - ISO 24346	2.0 mm
	Wear layer thickness	EN - ISO 24340	0.7 mm
	Commercial use	EN- ISO 10874	Class 34, very heavy
	Industrial use	EN - ISO 10874	Class 43, heavy
	Collection size		90
	Roll width	EN - ISO 24341	2.0 m
	Roll length	EN - ISO 24341	≤ 25 m
	Total weight	EN - ISO 23997	ca. 2.8 kg/m²
	Dimensional stability	EN - ISO 23999	< 0.1%
	Residual indentation <i>Typical value</i>	EN - ISO 24343-1	≤ 0.05 mm ~0.02 mm
	Castor chair continuous use	ISO 4918 / EN 425	Pass
	Water tight installation	EN 13553	Yes
	Light fastness	ISO 105-B02	≥ 6
	Flexibility	EN ISO 24344	ø 10mm
	Resistance to chemicals	EN ISO 26987	Very good
	Suitable for floor heating		Yes*
	Indoor Air Emissions: TVOC after 28 days	ISO 16516	< 50 µg/m³
	LCA Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact	
	Creating better environments		
	Renewable electricity	Eternal is manufactured using 100% electricity from renewable sources.	
	Recycled content	Eternal contains at least 60% recycled content in the backing.	

Eternal meets the requirement of EN 14014



	Reaction to fire	AS/NZS 9239-1	CRF: 8.6kW/m <sup>2</sup> Smk Dvlp: 203%.min
	Slip resistance	AS 4586:2013	R10**
	Body voltage	EN 1815	< 2kV
	Thermal conductivity	EN 12524	0.25 W/m-K

\*Temperature < 27°C

\*Slip test result achieved in an independent laboratory on new sample. On-site testing is variable and may not guarantee the same result. For sustainable slip a particle based floor must be used.

The recommended adhesive for Eternal is 540 Eurosafe Special or 640 Eurostar Special

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's). Eternal is manufactured in a facility certified to SA8000 and OHSAS 18001.



ETERNAL FLOOR FIRE REPORT

ETERNAL INSTALLATION GUIDE

ETERNAL SLIP REPORT

ETERNAL CLEANING GUIDE

For more information contact your Forbo representative or call 1800 224 471.



FLOORING SYSTEMS

creating better environments