

Certificate of Assessment

NK6500

No. 1620

"Copyright CSIRO 2011 ©"
Copying or alteration of this report
without written authorisation from CSIRO is forbidden.

This is to certify that the specimen described below was tested by the CSIRO Division of Materials Science and Engineering in accordance with Australian/ New Zealand Standard 3837, Method of test for heat and smoke release rates for materials and products using an oxygen consumption calorimeter, 1998, at 50 kW/m², on behalf of:

Forbo Floorcoverings Pty Ltd
23 Ormsby Place
WETHERILL PARK NSW
AUSTRALIA

A full description of the test specimen and the complete test results are detailed in the Division's sponsored investigation report numbered FNK 10280.

SAMPLE

IDENTIFICATION: Forbo Colorex 2mm Tile

DESCRIPTION OF SAMPLE:

The sponsor described the tested specimen as 2-mm thick highly-compressed homogeneous flooring tile comprising of PVC powder and limestone, and has embedded graphite particles design patterns. The specimen contained no chemical antistatic additives. The floor covering was adhered to a 4.5-mm thick fibre-reinforced cement board backing.

Nominal total thickness: 7.0 mm
Nominal total mass: 9.44 kg/m²
Colours: various colours

SAMPLE

CLASSIFICATION: Group Number: Group 3
(In accordance with Specification A2.4 of the Building Code of Australia.)

Average specific extinction area: 134.7 m²/kg
(Refer to Specification C1.10a section 3(c) of the Building Code of Australia.)

Testing Officer: Heherson Alarde

Date of Test: 29 September 2011

Issued on the 25th day of October 2011 without alterations or additions.



Garry E Collins
Manager, Fire Testing and Assessments



CSIRO Materials Science and Engineering

14 Julius Avenue, Riverside Corporate Park, North Ryde NSW 2113 AUSTRALIA
Telephone: 61 2 9490 5444 Facsimile: 61 2 9490 5555