

## Product quick info

**E 3/1 U2/U2 BT/SMT-HACCP-  
PS blue FDA**

Sketch of cross-section (not actual size)

**Applications**

- Dough conveying
- Meat, poultry and seafood processing
- Processing of dairy products
- Fruit and vegetable processing
- Mini conveyor

**Properties/Advantages**

- Both sides coated
- Hydrolysis resistant urethane coating with semi-matt top face pattern
- Broken twill (BT) pattern coated underside
- Pre-shrunk (PS) tension member
- Laterally stiff fabric
- HACCP design
- Complies to FDA, EU and MHLW# 370 regulation for direct contact to foodstuffs

**Basic technical data**

Top face	Polyurethane, SMT
Underside	Polyurethane, BT
Article no.	904499
d <sub>min</sub> [mm]	20
Total thickness [mm]	1.5
k <sub>1%</sub> relaxed [N/mm width]	2.5
Weight [kg/m <sup>2</sup> ]	1.6
Permitted operating temperature [°C]	-30 to +100

Product Quick Info | EN | 02.2024

FMS - Reproduction of text or parts thereof only with our approval. Modifications reserved.

Forbo Siegling GmbH  
Lilienthalstrasse 6/8, D-30179 Hannover  
Phone +49 511 67 04 0  
www.forbo-siegling.com, siegling@forbo.com