

# 520 Linoleum Doctor

## RENOVATION ADHESIVE FOR LINOLEUM

### PRODUCT DESCRIPTION

Pressure sensitive renovation adhesive to repair hollow areas under linoleum. Hardens fast after rubbing down the injected adhesive under the floor covering.

The adhesive is castor wheel resistant in acc. To DIN EN 12529 and can be applied over underfloor heating systems. For indoor use only.



### PRODUCT FEATURES

The adhesive hardens extremely fast, to allow an immediate use of the surface after application.

**Repair kit include:**  
1 bottle linoleum doctor 0,5 L  
2 syringes with injection needles  
1 operation instruction

### TECHNICAL DATA

Base	Latex
Colour	white
Density	Approx. 0,9 g/cm <sup>3</sup>
Consistency	Flowable, medium viscosity
Cleaning agent	water
Processing conditions	not below 15 °C on the subfloor, minimum 18°C material- and room temperature 35-75% relative air moisture, recommended <65%
Mode of application	Syringe, latexbrush
Consumption	Depending on the damaged area
Drying time	immediately
Curing time	Approx. 24 hours
Permitted shelf-life	within approx. 6 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C,
Frost sensitivity	yes

# 520

## Linoleum Doctor

Code acc. to GHS	no	
Enviroment/Work safety	DGNB:	VOC 2,3 %/quality level: 4
	LEED:	VOC 20,7 g/l
	Contains: nature latex	
	Infomration for allergy suffers: +49 361 730410	

### FLOOR PREPARATION

The materials to be bonded must be water-absorbent.  
Application is only suitable on hollow areas that are not caused by the influence of moisture from the subfloor.

### INSTRUCTIONS OF USE

Stri well before use!  
Drill holes with a 4mm drill. Insert the repair adhesive into the supplied syringe and inject it into the hole, if necessary, also into an open hollow area. Distribute immediately from the center outwards with a stapling hammer and rub it from the outside to the inside. Remove the adhesive immediately with a damp cloth and clean the area with clear water.  
The adhesive builds strength immediately, so that rework is generally not necessary.

The drilled hole can be closed "invisible" with a fusion wire.

### NOTES

Please pay attention to the technical datasheet and technical datasheet issued by the floor covering.  
When using brushed, only use of latex brushes is recommended. Brushing with conventional brushed leads to coagulations of the adhesive which becomes then useless.  
After the repair, it is advisable to clean the floor. Eurocol recommends 898 Euroclean Longlife or 887 Euroclean Multi.

### PACKAGING

0,5 kg nonreturnable package (repair set contains as well instruction guide and two syringes)

### SPECIAL NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.  
This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.  
The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.  
As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!  
Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.  
The manufacturer's terms and conditions are binding

Latest update 2017-07-11  
Supersedes issue as of 2009-04-29

Version Nr.:03  
73150\_520-01